

Illusions

tents | rentals | event design

44' MOBILE KITCHEN *nickname: baby beast*

Our 44-foot mobile kitchen is a strategic mobile kitchen custom-designed for the diverse needs of varied deployment missions, containing industrial-scale equipment for food cooking production, preparation, and cold storage. The vehicle's production equipment includes numerous ovens, a 6-burner range, griddle, car-broiler, fryers, tilting skillet and pan steamer on-board.

see back for specifications



SPECIFICATIONS

Nickname – ‘Baby Beast’
Dimensions: Overall Length – 44’

Trailer Specifications

Trailer weight: 16,300 lbs; tongue weight ~4,200 lbs; overall length – 44’;
overall width – 8.5’; deck height – 25”; (3) exit doors; ESA, NFPA, UL, NSF,
DOT approved

Cooking/Production Equipment

| | |
|--|------------------------|
| Convection ovens full size, double stack | BLODGETT/DFG100 |
| 6-burner restaurant range w/(1) standard oven | GARLAND/G60-6G24CC |
| 36” countertop griddle range w/(1) standard oven | GARLAND/G60-6G24CC |
| 24” char-broiler | GARLAND/S280-36B |
| Double basket deep fryers | PITCO/SG14S |
| Tilting skillet; 35 gal | CLEVELAND RANGE/SGL30T |
| 5 pan steamer | CLEVELAND RANGE/21CGA5 |

Plumbing & Sanitation

119 gal hot water heater; 20 gal/min @ 50 PSI water pump; city water fill
valve w/back flow prevention; (3) full-size sink compartments; hand wash
sink with towel & soap dispenser

HVAC/Fire Suppression

Custom 36’ horizontal pull vent hood; (2) air curtains; (2) Class K
extinguishers; (2) ABC extinguishers

Electrical & Lighting

(10) interior quad plugs; duplex to power hot water heater & water pump;
(4) exterior plugs w/waterproof boxes; (9) Jelly Jar LED vent hood lights; (2)
Jelly Jar LED walk-in cooler lights; (6) exterior LED wall pack lights; GE 200
amp electrical panel; extension cord w/waterproof connectors

Towing & Hook-up

Vehicle: 5th wheel, 2” king pin; round 7-pin 7 pin/slot plug to tow vehicle for
lights and electric wheel brakes

Electric: 120/240V, single phase; 100 amp

Propane: 1M BTU; uses (3) 100lb tanks manifolded together OR (1) 420lb
(80 gal) tank with POL connector

Freshwater: Uses 3/4” standard food-grade city water hook-up w/backflow
prevention

Grey Water: 2” Quick Connect Cam lock valve

