

PRESS MAINTENANCE LOG (EVERY 6 MONTHS)

PRESS ID: _____

DATE OF INSPECTION :													
PRESS INSPECTED BY :													
CHECK AND TIGHTEN INTERNAL SLIDE BOLTS													
CHECK AND TIGHTEN CON ROD CAP BOLTS													
ADD OIL TO CONNECTING ROD THREAD THRU WEEP HOLE IN FRONT OF CASTING (SAME OIL AS MAIN TANK)													
CLEAN OUT INTERIOR OF SLIDE													
CHECK SLIDE GIB & CRANK BUSHING DISTRIBUTOR BLOCK BEHIND SLIDE AND MAKE SURE IN NO LEAK CONDITION													

PRESS MAINTENANCE LOG (EVERY 12 MONTHS)

CHECK PARALLELISM OF SLIDE TO BOLSTER AT 90-180-270 DEGREES													
CHECK SLIDE GIBS FOR CLEARANCE AND ANY SIGN OF WEAR													
FULL COUNTERBALANCE AIR PRESSURE TO BE COMPARED TO JIS 1ST CLASS INSPECTION DOCUMENT FROM WHEN PRESS WAS NEW													
CHECK FLYWHEEL BEST TENSION													
CONFIRM ENCODER MOUNT IS SECURE													
CONFIRM OVERRUN SENSOR AND MECHANICAL CAM IN ENCODER HOUSING IS SECURE													
CONFIRM ENCODER BELT, PULLIES AND KEYWAYS ARE SECURE													
LUBRICATE FLYWHEEL BEARING (SEE LUBE INSTR)													
CLEAN PRESS INSIDE AND OUT													
CHECK ALL BOLTS AND CAP SCREWS AND MAKE SURE EVERYTHING IS SECURE													



SUTHERLAND

1-800-43-PRESSES

service@sutherlandpresses.com