

REKOLA

REFLEX S MOPCLOTH

Make a difference with REFLEX:



Outstanding Performance & Versatility:

Deep Cleaning. Multifunctional and Ergonomical. Up to 50 sqm more per mopcloth.



Climate & Eco-friendly:

Less water and chemicals. Residue Free Cleaning.




Improves cleaning economy:

Saves time and space and cuts total costs.



Product code: Colour Dimensions:
code:

18-7050	blue	54 x 22,5 cm	REFLEX S MOPCLOTH 50% UMF, Multiple use, 115 grs/pcs
18-7054	red	54 x 22,5 cm	REFLEX S MOPCLOTH 50% UMF, Multiple use, 115 grs/pcs
Package:	5 pcs pp bag  20 pcs x 5-pack per transport box		

Application areas:

The REFLEX 2-in-1 cleaning system is designed for all types of smooth and sealed hard top floorings. Main application areas:



Healthcare sector



Public Areas & General Buildings



Food Industry & HoReCa

How to use the system:

REFLEX S MOPCLOTH is double-sided and is used in conjunction with REFLEX POWER SQUEEGEE 50 cm and REFLEX EXTENDABLE HANDLE 100/180 cm.



CHARGING:

REFLEX S MOPCLOTHS can be pre-prepared/charged with clean tap water or processed water. Optional: Chemicals suitable for UMF can be diluted according to manufacturer's instructions.

CHARGING S MOPCLOTHS ON THE TROLLEY:

1. Put S MOPCLOTHS in a container, e.g. 6 Ltr. rectangle bucket or box with lid.
2. Pour the desired fluid equally over the cloths inside the container.
3. Leave for a while with closed lid. Ready to clean!

ABOUT DOSING:

Avoid overdosing regardless of the charging liquid.

Some chemicals may cause damage to user, material and/or environment.

Depending on floor circumstances, charge the S MOPCLOTHS with 60-120 ml per cloth.

Eco-labelled:



3083
0027



Rekola supports Residue Free Cleaning.

Rekola is part of a group of manufactures determined to eliminate residue of dirt and chemicals that can harm people's health. REFLEX S MOPCLOTHS are designed to reduce and remove residue that resist traditional cleaning methods.

For more information please contact Rekola.

REKOLA

Maintenance

Laundry:



Rinse twice with cold water to ensure all cleaning chemicals are removed.
 Main program for synthetic fibres at 60°C or less is preferred.
 Rinse twice at 40°C to ensure all laundry agents are removed.
 Adjust temperatures and water volumes accordingly.
 Machine drum can be filled with 5 MOPCLOTHS up to 80% load (according to Weber & Leucht laundry test DIN EN ISO 6330).
 In case of drying use tumble drying at 40°C.
 Do not use bleach or softener.
 Low water level during processing or overloading the washing machine (max 80% of door window) may cause irreversible damage to cloths.

Disinfection:

Non-bleach disinfectant* laundry agent and autoclaving may be used if required.
 *e.g. peroxide based; this may affect colours

Durability:



500 washing cycles at 60°C or 200 washing cycles at 85°C. Rough surfaces like safety flooring may reduce the cloth's lifetime expectations.

Components

Body:

50% split **Ultra Microfibre**; 80% **PES**, 20% **PA** / 50% **PET**. UMF F= 0,154 Dtex.

Borders:

Overlock 100% **PES**. Sliding strip TPU and PES Mesh.

Washing label:

PES colour fast.

Characteristics

Shrinkage:

SGS tested <6% at recommended washing instructions. This can cause slight deformation, which does not affect the functionality.

Colour fastness:

4-5 *standard request ≥ 3-4*

Charging:

4,2 DAC value *standard request minimum 2,5*

Abrasion:

It is not advised to predispose softer material surfaces to the abrasion generated during use.

Weber & Leucht S301/1.3 dirt removal:

Ceramic tile SF 11	Dust A23	Damp	93%	<i>standard request ≥ 70</i>
PVC flooring PL-03	Dust A23	Damp	87%	<i>standard request ≥ 70</i>
Ceramic tile SF 11	Muddy dirt A05	Damp	100%	<i>standard request ≥ 70</i>
PVC flooring PL-03	Muddy dirt A05	Damp	100%	<i>standard request ≥ 70</i>

Bacteria reduction:

E-coli 99,89% log > 2,96
 S. Aureus 99,31% log 2,16



Non-touch:

In conjunction with REFLEX POWER SQUEEGEE, dirty cloths are not touched when demounting.

Patent:

FI2010000028 Floor Maintenance Device and Cloth

Disposing:

REFLEX S MOPCLOTHS are purely synthetic: they may be used for recycling programs, or because of their high energy value and zero emissions other than CO₂ and water, can be safely disposed by controlled energy-supply programs.

Guarantee

500 times use and laundry according to producer's guidelines at 60°C, under general hygiene cleaning circumstances, and at a maintained non-safety sealed floor.
 Extended usage can be achieved if optimal laundry and cleaning conditions are considered.
 For instructions and details, contact your local distributor.