



MOBILE KITCHENS
+ EVENT SUPPORT

44' KITCHEN TRAILER

See back for specifications

#430





SPECIFICATIONS

TRAILER SPECIFICATIONS:

Trailer Weight: 16,300 lbs.
Tongue Weight: ~4,200 lbs.
Length: 44'; Width: 8.5';
Deck height: ~25"

CURRENT PRODUCTION EQUIPMENT/MANUFACTURER:

*Customizable configuration currently includes:

(2) Convection ovens, full size / Vulcan – VC4D-21D150K

(1) 36" Charbroil Grill / Wolf

(1) 36" Flat Top Grill / Wolf

(1) 6-burner Stove w/ Under Oven / Wolf

(1) 30-gal. Tilt Skillet / Cleveland

(1) Fryer (50 lb. vat) / Vulcan – 1GR45M2

*Equipment swaps easily, strapped for transport with E-tracks

REFRIGERATION & HVAC/MANUFACTURER:

(1) Walk-in Refrigerator (9'6"L X 6'6"W) (8' x 5' interior)/Master Built

(2) 4-Ton, Split HVAC System for refrigeration & climate control/Trane Model #4TTR4048L1000AAA

SANITATION/ PREP & SAFETY:

(1) Large 3-Compartment Sink

(1) Hand wash sink

(1) Full Size (30-gal.) water heater

(2) 36" Stainless steel prep tables

Fire Suppression & Vent Hood

Eco-Grip Flooring (anti-bacterial, grease & water resistant non-slip surfaces)

California HCD Certified

POWER, WATER & LIGHTING:

(2) 200-Amp hookups at 120/240 single phase power

Flexible, dual 120/240v single phase, four-wire shore power inputs.

(Dual power inputs can be combined for as little as a single 200A supply connection; 400 Amps to operate all equipment simultaneously)

Standard Propane Connection/ Tank Flexibility – off board

Large 2X2 ft LED interior lighting

(8) Exterior 120V outlets w/ waterproof boxes & 8 interior of 4 circuits (#Interior 120V outlets)

TOWING & HOOK-UP:

Vehicle 5th Wheel, 2" King Pin, Round 7-pin/slot plug to tow vehicle for lights and electric wheel brakes.

PROPANE:

Standard Propane Connection/ Off-Board Tank Flexibility

FRESHWATER & GREYWATER:

Uses ¾" standard food grade city water hook-up with backflow prevention

Uses 2" PVC drain, can be coupled with cam lock valve.