



GLASS & SCREEN INSERT INTERCHANGING INSTRUCTIONS



CAREFUL!! GLASS UNIT IS SUBJECT TO BREAKAGE

1. REMOVING GLASS OR SCREEN PANEL

Starting near the bottom of the door, insert a flat head screwdriver into the groove of the panel retaining strip (see Fig. 1). Push forward on the screwdriver to disengage retaining strip from door frame and push towards the center of the door to move retaining strip away from door frame. Once several inches of the retaining strip have been freed, hold the free portion in your hand and gently pull towards the center of the door to release the balance of the retaining strip. Repeat the process with the second retaining strip on the opposite side of the door.

WARNING: Be prepared to support the glass panel as it comes away from the door. Keep glass panel in a vertical position. Never carry or store the glass unit flat.

2. INSTALLING GLASS OR SCREEN PANEL

If installing screen, hold screen panel with the center horizontal bar towards the outside. Insert the glass or screen panel into the door frame. Starting near the top of the door, use your fingers to snap the top end of the panel retaining strip into place. Work your way approximately two (2) feet down the retaining strip, snapping it into place as you go. Now start near the bottom of the door and repeat the process until the entire retaining strip is secure. Repeat the process with the second retaining strip on the opposite side of the door.

