



The **LEED®** (Leadership in Energy and Environmental Design) Green Building Rating System is the nationally accepted benchmark for the design, construction, and operation of high performance green buildings.

**Envelope 2000® (4mm), manufactured by Citadel Architectural Products, Inc.,** carries the following attributes under the context of this standard:

- The product is manufactured in Indianapolis, IN.
- The composite panel is warranted for a period of 5 years.
- Kynar 500® painted finishes are warranted for a period of 30 years.
- Anodized finishes are warranted for a period of 20 years.
- The bonding agent used contains no VOCs, no formaldehyde, is non-hazardous, chemically inert, and is 100% solid (no solvents).

In addition, the following information can be used to determine the level of contribution towards satisfying **MR Credit 4.1** and **MR Credit 4.2**<sup>(1)</sup>.

## Envelope 2000® (4mm)

Composition <sup>(2)</sup>	Weight (lbs/ft <sup>2</sup> )	Recycled Content By Weight	
		Post-Consumer	Post-Industrial <sup>(4)</sup>
<ul style="list-style-type: none"> <li>• Prefinished Smooth Aluminum</li> <li>• Thermoset Phenolic Resin</li> <li>• Primed Smooth Aluminum</li> </ul>	<b>1.25</b>	<b>0.5%</b>	<b>23.3% to 23.9%</b>

(1) MR Credit 4.1 and MR Credit 4.2 are based upon recycled content (as defined by the Green Building Rating System For New Construction & Renovations, ver 2.2) and are used to determine the overall dollar value of recycled material within the building.

(2) General composition listed. For a detailed listing of components, refer to the Product Data Sheet.

(3) Due to variables within the manufacturing process, recycled content is based upon an average.

(4) Post-Industrial is also referred to as Pre-Consumer.

LEED® is a registered trademark of USGBC.

