

### SC05-AE COMBINATION SMOKE AND CARBON MONOXIDE ALARM (CO)


<b>Sensor type</b>	Optical (smoke) Electrochemical (CO)
<b>Battery type</b>	1 year replaceable battery (2 x AA batteries)



- Ideal for bedrooms and living areas.
- One alarm protects against two deadly threats.
- Advanced optical sensing technology reduces nuisance alarms.
- Advanced electrochemical technology for better CO detection.
- Easy alarm identification with 2 different alarms and indicator lights.
- Sliding battery drawer with locking pin for safe and easy.
- Equipped with test and "hush" button.
- 30 day low battery warning.
- LED light to indicate power and alarm mode.
- Easy to install 2 x AA batteries (with a minimum of 1 year life) and fittings included.
- Loud 85 decibel alarm.



## Technical Specification

<b>Dimensions</b>	127mm (diameter) x 45mm (depth)	
<b>Supply voltage</b>	3V DC	
<b>Battery</b>	1 year replaceable battery	
<b>Technology</b>	Optical (smoke) Electrochemical (CO)	
<b>Alarm sound level</b>	85dB(A) at 3m (minimum)	
<b>Installation positions</b>	Wall / Ceiling	
<b>Alarms at temperature range</b>	-10°C to +40°C	
<b>Operating temperature</b>	+4°C to +38°C	
<b>Operating humidity</b>	Up to 90% RH non-condensing	
<b>Storage temperature</b>	-20°C to +60°C	
<b>Storage humidity</b>	Up to 93% RH non-condensing	
<b>Plastic material</b>	ABS, UL94 VO fire retardant	
<b>Warranty</b>	7 years	
<b>Weight</b>	225g	
<b>Certified to</b>	BS EN 14604:2005 / BS EN 50291-1:2010	
<b>Independently tested to</b>	N/A	
<b>Maximum number of connected units</b>	N/A	
<b>Operating Frequency</b>	N/A	
<b>Range</b>	N/A	