

Protection Unit for 3-phase AC Motors TC70

- ◆ Low cost
- ◆ Monitors LINE (phase) presence and order
- ◆ Monitors phase voltage magnitude
- ◆ Monitors NEUTRAL (zero) presence
- ◆ Overheating-protection input from PTC
- ◆ High reliability

TC70 is a specialized device for monitoring and protection of 3-phase asynchronous motors, designed for DIN-rail mounting. It monitors phase presence and order, phase line voltage, and zero presence, and switches off its relay output in the cases of failure. An additional input for connecting a thermistor with positive temperature coefficient (posistor) is used for monitoring motor temperature. A cheap, yet highly reliable device, TC70 can be used not only for motor protection, but also in all cases, in which 3-phase system power supply should be monitored.



Technical specifications

Input

| | |
|-------------------------------------|--|
| LINE control input (3-phase) | 3 x 380 VAC ± 15% |
| NEUTRAL control input | 220 VAC ± 15% |
| Temperature input | PTC (R _{PTC} at 25 °C = 1k, 2k, or other) |

Output

| | |
|--------------------------------|---|
| Relay electromechanical | 3A/250V w/ NO/NC contact |
| Solid state relay | 1A/250VAC |
| Output function | switches off in situations ⁽¹⁾ : (a) missing line (R/S/T) or neutral (N), (b) line voltage exceeds 270 ± 10 V, (c) line voltage drops below 170 ± 10 V, (d) line order is not RST, STR, or TRS |
| Temperature control | switches off when PTC indicates 70 °C |
| Indication | LED for relay ON |

Power supply

| | |
|-----------------------|------------------|
| Supply voltage | 230 VAC +10/-15% |
| Consumption | max. 4 VA |

Operating conditions

| | |
|----------------------------|-------------|
| Ambient temperature | -10...65 °C |
| Ambient humidity | 0...85 %RH |

Design and materials

| | |
|-----------------------------------|-------------------|
| Case material | plastic |
| Mounting | on 35 mm DIN rail |
| Wiring | screw terminals |
| Dimensions | 45x78x108 mm |
| Weight | max. 300 g |
| Protection, case/terminals | IP40 / IP00 |

⁽¹⁾ Other phase voltages than the described in points (b) and (c) may be monitored if requested.

Ordering code TC70 - G5.G6

| Code | Feature or option | Code values |
|-----------|---------------------------|--|
| G5 | Relay output | C - relay NO/NC, D - SSR |
| G6 | Temperature control input | BP - PTC 1k, BQ - PTC 2k, BZ - other PTC (specify!) |