

Temperature

Nagman
 Universal Dry Block
 Medium Temperature Calibrator

Portable / Bench-top
 Precision Dry Block Calibrator
 with Interchangeable Thermowells

*Ideal for quick / fast Site Calibration of
 RTDs / TCs / Bi-Metal Thermometers,
 Temperature Switches / Indicators etc. in
 Industrial & Marine Applications*

*High Accuracy, Resolution & Stability with
Measurement Capability for mV / V / mA,
 Resistance TC (ISA Types : J, K, R, S, N),
 RTD (Pt100 : IEC Standard) Signals*

Model

MTC 650

- Range : 50°C to 650°C
- Accuracy : $\pm 0.6^\circ\text{C}$
- Advanced – Micro-controller based Technology
- Heavy Duty Portable / Bench-top Model
- High Accuracy, Resolution & Stability
- 128 x 64 Graphic Display
- Measurement Capability for TC, RTD, mV / mA / V & Resistance Signals
- Touch Membrane Keypad
- Switch Test Contact Measurement
- Interchangeable Thermowell Inserts, Single / Multihole
- RS-232 Interface & Calibration Software



Specifications

MTC 650

Range	50°C to 650°C		
Resolution	0.1°C		
Accuracy	±0.6°C		
Stability	±0.05°C		
Stabilisation Time	15 to 20 Minutes		
Temperature Readout	°C / °F Switchable		
Well Diameter	25 mm		
Immersion Depth	110 mm		
Heating Time (Ambient to max.)	20 Minutes approx.		
Cooling Time max. (to 100°C)	42 Minutes		
Switch Test facility	Provided		
Interchangeable Thermowells	Single hole to suit 1/4" & 1/2" Probes. Other Sizes / Multihole available as optional.		
Housing / Mounting	Bench-top		
Power Supply / Consumption	230V AC, 50 Hz, 1230 W		
Instrument Dimensions (L x D x H)	160 x 365 x 350 mm		
Instrument Weight (approx.)	11 Kg.		
Measurement Capability	Thermocouples	ISA Types J, K, R, S, N	RTD Pt100 IEC Std.
	mA	0 to 25 mA	mV 0 to 100 / 1000 mV
	Volt	0 to 10 V	Resistance 0 to 500Ω / 3.5 KΩ

Measurement : Range, Resolution & Accuracy

Type	Range	Resolution	Accuracy
mV (Low)	0 to 100	0.01	±0.05% F.S.
mV (High)	0 to 1000	0.1	
Volts	0 to 10	0.001	
mA	0 to 25	0.001	
Ohms	0 to 500	0.01	
KOhms	0 to 3.5	0.0001	
TC Type J	-100 to 1200	0.1	±0.1% F.S.
TC Type K	-60 to 1260		
TC Type R	150 to 1700		
TC Type S	170 to 1700		
TC Type N	0 to 1300		
RTD Pt100	-100 to 800		±0.05% F.S.

STANDARD DELIVERY

- Basic Instrument
- Test Leads
- Mains Cable
- Insertion Tubes (to suit 1/4" & 1/2" probes)
- Tool for Insertion Tubes
- Spare Fuses
- RS-232 Computer Interface
- "MTCCal" Calibration Software
- Traceable Calibration Certificate
- Instruction Manual
- Carrying Case

OPTIONALS

- Additional Thermowells / Insertion Tubes :
(to choose from) :
Single hole standard sizes to suit
1/8", 1/4", 3/8", 1/2", 3/4", 7/8" & 3, 4, 5, 6, 7, 8, 10, 12, 13, 15, 17, 19 & 21 mm probes
Multihole (Typical) : (1x6 + 1x8), (3x6), (1x10 + 1x4) mm
- 115V AC, 60 Hz Power Supply
- Calibration Certificate from NABL Accredited – as per ISO/IEC 17025:2005 Laboratory

Manufactured by

Nagman Instruments & Electronics (P) Ltd.

27th KM Stone, Chennai-Bangalore NH-4, Nazarethpet P.O., Chembarambakkam, Chennai – 600 123. INDIA.

Domestic Sales

Phone 044 – 26810280, 1280, 0600, 1300

Fax 044 – 26811703

E-Mail mktgchennai@nagman.com

International Sales

+91-44-26811704, 26811708

+91-44-26811703

exports@nagman.com

www.nagman.com

