



Securities Industry Automation Corporation
11 Wall Street, New York, NY 10005

November 19, 2020

OPRA Market Data Subscribers: Capacity Testing Notice Reminder

The OPRA Participants have updated their traffic projections based on messages per 100-millisecond (MPHM) intervals. The use of a 10-millisecond interval reflects system utilization during bursts of traffic. The bandwidth required to receive data via your SFTI connection is reflected in Gigabits.

Please note that the traffic projections are for one stream only. For fault tolerance purposes, two redundant streams of data are available from SIAC. For those Multicast Data Subscribers who elect to receive both streams of data, the bandwidth requirements would be double.

SIAC is providing Saturday capacity testing opportunities to allow direct Multicast Data Subscribers to validate processing OPRA projected maximum output traffic rates. Testing will be a half hour period dedicated to maximum packet testing, followed by a half hour period dedicated to maximum capacity rates.

All OPRA Multicast Data Subscribers are invited to participate in capacity tests occurring on the same dates as the SIP Failover testing as follows:

- 12/5/2020 - from approximately 12:00 pm - 1:00 pm ET
- 5/1/2021 - from approximately 12:00pm - 1:00pm ET
- 8/21/2021 - from approximately 12:00pm - 1:00pm ET
- 12/4/2021 - from approximately 12:00pm - 1:00pm ET

The maximum output traffic rates for OPRA data services will be as follows:

Capacity Projections

Effective Date	100-Milliseconds			10-Milliseconds			Total Messages Per Day (billions)	Maximum Output Rate per Output Line MPHMM (thousands)
	Maximum Output Traffic Rates (millions)	Bandwidth Gigabits	Peak Packets (thousands)	Maximum Output Traffic Rates (millions)	Bandwidth Gigabits	Peak Packets (thousands)		
Current	8.939	2.91	870	1.011	0.354	87	60	500
1/2021	9.189	3.00	900	1.039	0.364	90	108	500
7/2021	9.708	3.18	940	1.098	0.385	94	110	500
1/2022	10.224	3.35	970	1.156	0.406	97	113	500

Retransmissions

The required bandwidth should be increased by 10% to account for retransmissions.

Latency

The median latency for OPRA is 33 microseconds. Message latency is measured beginning with the time-stamp taken as an inbound Participant message arrives at the network entrance to the OPRA environment, through processing by the system into a consolidated message for Data Recipients, to the time-stamp taken as the outbound message arrives at the network exit from the environment. These time-stamps are taken and correlated by a process external to the data processing applications. If the external process cannot correlate an inbound message to its corresponding outbound message or measures negative latency for a message, the message is excluded from broader latency calculations such as median message latency.

Testing Coordination (Required)

To coordinate testing, and to provide verbal or written confirmation of testing (as required of all Multicast Data Subscribers), please register as follows:

- E-mail your name, organization name, phone number to:
CTA-OPRA-Support@siac.com

*Please note that if no Multicast Data Subscribers register for capacity testing, capacity testing **will not** take place.*

Data Subscribers who receive CTS/CQS from connectivity service providers other than ICE Global Network must contact their connectivity service providers to coordinate testing.

Questions

Questions regarding the bandwidth requirements should be addressed to: CTA-OPRA-Support@siac.com. Multicast Data Subscribers can also contact the SIAC NMS Product Management Desk at 212-656-8177, Option 2. If support team members are engaged with other customers, please leave a detailed voice message of the purpose of your call, which will produce an email of your message to the support team.