



AUTECH POWER SYSTEMS PRIMARY (NON-RECHARGEABLE) LITHIUM BASED BATTERIES

Part No.	Size	Open current Voltage	Nominal Voltage	Nominal Capacity	Max. Working Current	Max. Pulse Current	Working temp.	Diameter	Height	Weight
LiSoCl2--Energy Type										
ER10240	2/3AAA	3.66V	3.6V	0.4Ah	10mA	20mA	- 55°C ~ + 85°C	10.5mm	24.0mm	4g
ER10280	2/3AAA	3.66V	3.6V	0.5Ah	10mA	20mA	- 55°C ~ + 85°C	10.5mm	28.0mm	5g
ER10450	AAA	3.66V	3.6V	1.0Ah	10mA	20mA	- 55°C ~ + 85°C	10.5mm	45.0mm	9g
ER14250	1/2AA	3.66V	3.6V	1.2Ah	20mA	50mA	- 55°C ~ + 85°C	14.5mm	25.2mm	9.3g
ER14335	2/3AA	3.66V	3.6V	1.65Ah	35mA	75mA	- 55°C ~ + 85°C	14.5mm	33.5mm	12g
ER14505	AA	3.66V	3.6V	2.7Ah	100mA	200mA	- 55°C ~ + 85°C	14.5mm	50.5mm	17g
ER17335	2/3A	3.66V	3.6V	2.1Ah	100mA	200mA	- 55°C ~ + 85°C	17.5mm	33.5mm	17g
ER17505	A	3.66V	3.6V	3.6Ah	100mA	200mA	- 55°C ~ + 85°C	17.5mm	50.5mm	25g
ER18505	A	3.66V	3.6V	4.0Ah	100mA	200mA	- 55°C ~ + 85°C	18.5mm	50.5mm	27g
ER26500	C	3.66V	3.6V	9.0Ah	200mA	400mA	- 55°C ~ + 85°C	26.2mm	50.0mm	55g
ER34615	D	3.66V	3.6V	19.0Ah	200mA	400mA	- 55°C ~ + 85°C	34.0mm	61.5mm	100g



ER341245	DD	3.66V	3.6V	38.0Ah	400mA	500mA	- 55°C ~ + 85°C	34.0mm	124.5mm	195g
ER2450	/	3.66V	3.6V	0.5Ah	5mA	10mA	- 55°C ~ + 85°C	24.5mm	5.8mm	10g
ER9V	/	10.9V	10.8V	1.2Ah	20mA	100mA	- 55°C ~ + 85°C	26.9*17.4*49.3mm		32g
ER32L65	1/10D	3.66V	3.6V	1.0Ah	10mA	20mA	- 55°C ~ + 85°C	32.9mm	6.5mm	19g
ER32L100	1/6D	3.66V	3.6V	1.7Ah	10mA	20mA	- 55°C ~ + 85°C	32.9mm	10.5mm	24g
ER261020	CC	3.66V	3.6V	18Ah	200mA	400mA	- 55°C ~ + 85°C	26.2mm	102mm	110g

LiSoCl2--Power Type

ER14250M	1/2AA	3.66V	3.6V	0.75Ah	100mA	250mA	- 55°C ~ + 85°C	14.5mm	25.5mm	10g
ER14335M	2/3AA	3.66V	3.6V	1.3Ah	200mA	500mA	- 55°C ~ + 85°C	14.5mm	33.5mm	13g
ER14505M	AA	3.66V	3.6V	2.0Ah	400mA	800mA	- 55°C ~ + 85°C	14.5mm	50.5mm	19g
ER17335M	2/3A	3.66V	3.6V	1.7Ah	400mA	800mA	- 55°C ~ + 85°C	17.5mm	33.5mm	18g
ER17505M	A	3.66V	3.6V	2.8Ah	600mA	1000mA	- 55°C ~ + 85°C	17.5mm	50.5mm	27g
ER18505M	A	3.66V	3.6V	3.5Ah	600mA	1000mA	- 55°C ~ + 85°C	18.5mm	50.5mm	29g
ER26500M	C	3.66V	3.6V	6.5Ah	1000mA	2000mA	- 55°C ~ + 85°C	26.2mm	50.0mm	55g
ER34615M	D	3.66V	3.6V	14.5Ah	2000mA	3000mA	- 55°C ~ + 85°C	34.0mm	61.5mm	106g

LiSoCl2--High Temperature Type



ER14505S	AA	3.66V	3.6V	1.6Ah	100mA	200mA	- 55°C ~ + 150°C	14.5mm	50.5mm	17g
ER18505S	A	3.66V	3.6V	2.8Ah	100mA	200mA	- 55°C ~ + 150°C	18.5mm	50.5mm	27g
ER26500S	C	3.66V	3.6V	6.0Ah	200mA	400mA	- 55°C ~ + 150°C	26.2mm	50.0mm	55g
ER34615S	D	3.66V	3.6V	13.0Ah	200mA	400mA	- 55°C ~ + 150°C	34.0mm	61.5mm	100g

LiMnO2 Battery

CR11108	CR1/3N	3.0V	170mAh	60mA	80mA	- 40°C ~ + 80°C	11.6mm	10.8mm	3g
CR15270	CR2	3.0V	800mAh	500mA	1000mA	- 40°C ~ + 80°C	15.0mm	27.0mm	11g
CR17335	CR123A	3.0V	1500mAh	1500mA	3000mA	- 40°C ~ + 80°C	17.0mm	33.5mm	16g
CR14250	1/2AA	3.0V	800mAh	100mA	200mA	- 40°C ~ + 80°C	14.5mm	25.0mm	9g
CR14250SE	1/2AA	3.0V	950mAh	7mA	70mA	- 40°C ~ + 80°C	14.5mm	25.0mm	11g
CR14505	AA	3.0V	1500mAh	1000mA	2500mA	- 40°C ~ + 80°C	14.5mm	50.5mm	16g
CR17450	4/5A	3.0V	2200mAh	1500mA	3000mA	- 40°C ~ + 80°C	17.0mm	45.0mm	23g
CR17450SE	4/5A	3.0V	2400mAh	15mA	150mA	- 40°C ~ + 80°C	17.0mm	45.0mm	28g
CR18505	A	3.0V	2800mAh	1500mA	3000mA	- 40°C ~ + 80°C	18.5mm	50.5mm	35g
CR26500	C	3.0V	5000mAh	2000mA	3000mA	- 40°C ~ + 80°C	26.0mm	50.0mm	62g
CR34615	D	3.0V	11000mAh	2000mA	3000mA	- 40°C ~ + 80°C	34.2mm	61.5mm	125g



CR9V		9.0V	800mAh	120mA	400mA	- 40°C ~ + 80°C	26.2*17.2*49.2	32g
------	--	------	--------	-------	-------	-----------------	----------------	-----

Li-CuO: 1.5v Lithium Copper Oxide

APS-LR08425-4A	AAAA	1.5V	1000mAh	500mA	1000mA	- 40°C ~ + 60°C	8.5mm	42.5mm	5.5g
APS-LR03-3A	AAA	1.5V	1700mAh	1000mA	2000mA	- 40°C ~ + 60°C	10.5mm	45.0mm	8.3g
APS-R6-AA	AA	1.5V	4000mAh	2000mA	3000mA	- 40°C ~ + 60°C	14.5mm	50.5mm	15.5g