



*Near Field Communication controller


RoHS
Compliant



- Power Rating: 680W
- Input Voltage: 120-277Vac
- CC & CV (Constant Power Output)
- Output Current (800mA-20000mA)
- Output programmable w/ Near Field controller
- Efficiency to 95%
- Compatible with 0-10V, PWM, Timer, Dim-to-off option, Isolated Dimming, 12V/200mA AUX
- Optional Thermal Protection NTC
- Lightning, OVP, SCP, OTP, & Over Current Protection
- UL Class P Type HL
- IP67
- 5-year warranty
- Surge Protection: Diff: 6kV, Common: 10kV

Mechanical Design

-Models with UL certified cables
L2WCP680SXXXST-XYZ-H



Application Options:

- High Power Series, current programmable
- Near Field Communication Controller
- Dimming Options

Contact your Autec Technical Sales Rep today and discover if our LED Driver “The Arbiter” is the perfect solution to your unique lighting application!

Model Number	Input Voltage Range	Output Power	Output Voltage	Output Current Min.	Output Current Max.	Efficiency	Certification
L2WCP680S1420ST-XYZ-H	120-277Vac	680W	25-48V	5700mA	14200mA	95%	UL/cUL
L2WCP680S1250ST-XYZ-H	120-277Vac	680W	28-56V	5000mA	12500mA	95%	UL/cUL
L2WCP680S0937ST-XYZ-H	120-277Vac	680W	38-80V	3750mA	9370mA	95%	UL/cUL
L2WCP680S536ST-XYZ-H	120-277Vac	680W	67-140V	2140mA	5360mA	95%	UL/cUL
L2WCP680S428ST-XYZ-H	120-277Vac	680W	84-180V	1710mA	4280mA	95%	UL/cUL
L2WCP680S313ST-XYZ-H	120-277Vac	680W	115-240V	1250mA	3130mA	95%	UL/cUL
L2WCP680S250ST-XYZ-H	120-277Vac	680W	144-300V	1000mA	2500mA	95%	UL/cUL
L2WCP680S200ST-XYZ-H	120-277Vac	680W	180-375V	800mA	2000mA	95%	UL/cUL
L2WCP680S160ST-XYZ-H	120-277Vac	680W	225-460V	400mA	1600mA	95%	UL/cUL

Applications:

- Indoor and Outdoor use
- Greenhouse & horticultural
- Industrial grade

Packing:





- Unit Weight: 2.25kg
- 4pcs/Carton
- Carton Weight/Dims: 9.2kg (382x277x141mm)
- #Cartons/pallet: TBA

Autec Power Systems
31328 Via Colinas Suite 102
Westlake Village, CA 91362


818-338-7788
sales@autec.com
#autecpower

**AUTEC PANEL MOUNTED CONNECTORS FOR HIGH
POWER LED DRIVERS IN 320W, 400W, 600W, 680W, 1200W,
AND 1400W SINGLE CHASSIS SOLUTION, FULLY POTTED
IP67 UNITS WITH WATERPROOF CONNECTORS.
AVAILABLE IN 90-305VAC INPUT AND 277-347-480VAC
INPUT CONFIGURATION, UL CLASS "P"**

**YOU CAN GROW WITH AUTEC!
AUTEC POWER SYSTEMS
YOUR HIGH-POWER SPECIALIST SINCE 1989**



TC POINT

		DIMENSIONS ARE IN INCHES TOLERANCES: FRACTIONAL ± ANGULAR: MACH ± BEND ± TWO PLACE DECIMAL ± THREE PLACE DECIMAL ±		DRAWN	NAME	DATE	
				CHECKED			
				ENG APPR.			
				MFG APPR.			
				Q.A.			
		MATERIAL		COMMENTS:			TITLE:
							L2WCP680
							PANEL MOUNT DWG
NEXT ASSY	USED ON	FINISH					SIZE: A
APPLICATION		DO NOT SCALE DRAWING					DWG. NO.
							REV.
							SCALE:
							WEIGHT:
							SHEET OF