





ELECTRIC PIZZA OVEN

The Michelangelo's stunningly stylish appearance matches the amazing performance of the oven itself, making it the perfect model for front of house. These electric ovens are built for high output and will deliver outstanding results for long hours. They are highly energy efficient and are designed and built to last.

This oven features an innovative touch screen control panel with up to 100 programmes, cleaning mode, and end of cooking buzzer. The intuitive control system has the ability to individually control the top and bottom element of each deck with 0% to 100% power.

The oven door has a full length, double glazed, panoramic window and internal lights so you can see the progress of your pizzas whilst cooking. The doors are fitted with a heavy duty compression spring system and seal to optimise heat retention. It has a revolutionary heat regeneration system so when the oven door is opened it immediately circulates the heat back inside to minimise heat-loss.

The cooking chamber is manufactured entirely from stainless steel to ensure a totally hygienic finish and no chance of rust. Like all Cuppone ovens, the Michelangelo has a cordierite stone cooking base to retain heat and ensure a perfect, authentic, Italian stone-baked flavour.



linda-lewis.co.uk

Beautifully designed with a premium finish for front of house, whilst still retaining heavy usage features.



Cuppone ovens are incredibly versatile and can be used to cook so many different dishes including: pasta, jacket potatoes, fish, meat, vegetables, and much more. They are often used to reheat or finish off dishes that have been prepared in advance.

Choose the Michelangelo if you need a high output, highly energy efficient oven that looks stylish for front of house positioning.

Why choose a Michelangelo?

- Intuitive touch screen control panel
- 100 cooking programmes
- Perfect for front of house
- Heavy duty sprung doors
- Power boost button
- Heat regeneration system
- Highly energy efficient
- Low voltage floodlit lighting system
- 7 day programmer
- Auto cleaning programme
- Electronically adjustable steam vents

INGLE DECK Ingo 1100 440 720 720 140 4 x 14" 4 x 12" 140kg 5.8kw Single or 3 phase LKML6351TS 1190 1460 440 720 720 140 6 x 14" 4 x 12" 140kg 5.8kw Single or 3 phase LKML6351TS 1190 1460 440 720 1080 140 6 x 14" 6 x 12" 179kg 8.4kw Single or 3 phase LKML6351TS 1550 1100 440 1080 720 140 6 x 14" 6 x 12" 183kg 8.6kw Single or 3 phase LKML9351TS 1550 1460 440 1080 1080 140 9 x 14" 9 x 12" 233kg 12.6kw WIN DECK 720 140 8 x 14" 8 x 12" 245kg 11.6kw Single or 3 phase LKML6352TS 1190 1460 780 720 140 8 x 14" 8 x 12" 310kg 16.8kw Single or 3 phase LKML6352TS 11
LKML4351TS 1190 1100 440 720 720 140 4 × 14" 4 × 12" 140kg 5.8kw Single or 3 phase LKML6351TS 1190 1460 440 720 1080 140 6 × 14" 6 × 12" 179kg 8.4kw Single or 3 phase LKML6351TS 1550 1100 440 1080 720 140 6 × 14" 6 × 12" 183kg 8.6kw Single or 3 phase LKML6351TS 1550 1100 440 1080 720 140 6 × 14" 6 × 12" 183kg 8.6kw Single or 3 phase LKML9351TS 1550 1460 440 1080 720 140 9 × 14" 9 × 12" 233kg 12.6kw 3 phase only WIN DECK HKML4352TS 1190 1100 780 720 720 140 8 × 14" 8 × 12" 245kg 11.6kw Single or 3 phase LKML6352TS 1190 1460 780 720 140 12 × 14" 12 × 12" 310kg 16.8kw Single or 3 phase LKML6352LTS 1550 1400 780 720 140 12 × 14"
LKML6351TS 1190 1460 440 720 1080 140 6 x 14" 6 x 12" 179kg 8.4kw Single or 3 phase LKML6351TS 1550 1100 440 1080 720 140 6 x 14" 6 x 12" 179kg 8.4kw Single or 3 phase LKML6351TS 1550 1100 440 1080 720 140 6 x 14" 6 x 12" 183kg 8.6kw Single or 3 phase LKML9351TS 1550 1460 440 1080 1080 140 9 x 14" 9 x 12" 233kg 12.6kw 3 phase only WIN DECK UN DECK UN UN UN UN UN 720 720 140 8 x 14" 8 x 12" 245kg 11.6kw Single or 3 phase LKML6352TS 1190 1100 780 720 720 140 8 x 14" 8 x 12" 245kg 11.6kw Single or 3 phase LKML6352TS 1190 1460 780 720 140 8 x 14" 12 x 12" 310kg 16.8kw Single or 3 phase LKML6352TS 1550 1100 780 720 140<
LKML6351LTS 1550 1100 440 1080 720 140 6 × 14" 6 × 12" 183kg 8.6kw Single or 3 phase LKML9351TS 1550 1400 440 1080 720 140 6 × 14" 6 × 12" 183kg 8.6kw Single or 3 phase LKML9351TS 1550 1460 440 1080 1080 140 9 × 14" 9 × 12" 233kg 12.6kw WIN DECK 8 × 14" 8 × 12" 245kg 11.6kw Single or 3 phase LKML6352TS 1190 1100 780 720 720 140 8 × 14" 8 × 12" 245kg 11.6kw Single or 3 phase LKML6352TS 1190 1460 780 720 140 12 × 14" 12 × 12" 310kg 16.8kw Single or 3 phase LKML6352LTS 1550 1100 780 720 140 12 × 14" 12 × 12" 316kg 17.2kw Single or 3 phase LKML9352TS 1550 <td< td=""></td<>
LKML9351TS 1550 1460 440 1080 1080 140 9 x 14" 9 x 12" 233kg 12.6kw 3 phase only WIN DECK 3 phase only LKML4352TS 1190 1100 780 720 720 140 8 x 14" 8 x 12" 245kg 11.6kw Single or 3 phase LKML6352TS 1190 1460 780 720 140 8 x 14" 8 x 12" 245kg 11.6kw Single or 3 phase LKML6352TS 1190 1460 780 720 1080 140 12 x 14" 12 x 12" 310kg 16.8kw Single or 3 phase LKML6352TS 1550 1100 780 720 140 12 x 14" 12 x 12" 310kg 17.2kw Single or 3 phase LKML9352TS 1550 1460 780 1080 140 18 x 14" 18 x 12" 405kg 25.2kw
WIN DECK Image: Second sec
LKML4352TS 1190 1100 780 720 720 140 8 × 14" 8 × 12" 245kg 11.6kw Single or 3 phase LKML6352TS 1190 1460 780 720 1080 140 12 × 14" 12 × 12" 310kg 16.8kw Single or 3 phase LKML6352LTS 1550 1100 780 720 140 12 × 14" 12 × 12" 310kg 17.2kw Single or 3 phase LKML9352TS 1550 1460 780 1080 1080 140 18 × 14" 18 × 12" 405kg 25.2kw
LKML6352TS 1190 1460 780 720 1080 140 12 x 14" 12 x 12" 310kg 16.8kw Single or 3 phase LKML6352LTS 1550 1100 780 1080 720 140 12 x 14" 12 x 12" 310kg 16.8kw Single or 3 phase LKML6352LTS 1550 1100 780 1080 720 140 12 x 14" 12 x 12" 316kg 17.2kw Single or 3 phase LKML9352TS 1550 1460 780 1080 140 18 x 14" 18 x 12" 405kg 25.2kw
LKML6352LTS 1550 1100 780 1080 720 140 12 x 14" 12 x 12" 316kg 17.2kw Single or 3 phase LKML9352TS 1550 1460 780 1080 1080 140 18 x 14" 18 x 12" 405kg 25.2kw
or 3 phase LKML9352TS 1550 1460 780 1080 1080 140 18 x 14" 18 x 12" 405kg 25.2kw

HOODS

🛞 Please note: For twin deck models exceed 14.5Kw, each deck requires a separate power supply.

STANDS

Model	W	D	Н	Net Weight
SINGLE DECK				
SML4351	1180	950	1100	43kg
SML6351	1180	1310	1100	57kg
SML6351L	1540	950	1100	50kg
SML9351	1540	1310	1100	67kg
TWIN DECK				
SML4352	1180	950	900	39kg
SML6352	1180	1310	900	53kg
SML6352L	1540	950	900	46kg
SML9352	1540	1310	900	63kg

Castors available as extra.

Stands are stainless steel effect finish.

Please note: If stand is purchased separately delivery charges will apply.

Ensure that you keep a distance of at least 50 mm between the oven and other equipment or inflammable materials. We advise that you leave an unrestricted space of at least 500 mm to the right side to allow for easy access to the electrical system.

All Cuppone products are supplied with 2 years parts and 1 year labour warranty as standard. 1 year additional labour warranty available as extra.

— linda-lewis.co.uk

Model		D		Net Weight	Loading	Flue Diameter
HML435	1186	1200	410	60kg	13Amp plug	150mm Ø
HML635	1186	1200	410	60kg	13Amp plug	150mm Ø
HML635L	1546	1200	410	73kg	13Amp plug	150mm Ø
HML935	1546	1200	410	73kg	13Amp plug	150mm Ø

This oven features a 7 day programmer so is great for planning ahead. Hood must be vented out of the building

Images are for display purposes only and might not be a true representation of the product as production changes from time to time.

