

## Generator set data sheet

**Model:** DFEG  
**Frequency:** 60  
**Fuel type:** Diesel  
**KW rating:** 350 standby  
 320 prime  
**Emissions level:** EPA NSPS Stationary Emergency Tier 2

<b>Exhaust emission data sheet:</b>	<b>EDS-187</b>
<b>Exhaust emission compliance sheet:</b>	<b>EPA-1027</b>
<b>Sound performance data sheet:</b>	<b>MSP-186</b>
<b>Cooling performance data sheet:</b>	<b>MCP-110</b>
<b>Prototype test summary data sheet:</b>	<b>PTS-145</b>
<b>Standard set-mounted radiator cooling outline:</b>	<b>0500-3326</b>
<b>Optional set-mounted radiator cooling outline:</b>	
<b>Optional heat exchanger cooling outline:</b>	
<b>Optional remote radiator cooling outline:</b>	

<b>Fuel consumption</b>	<b>Standby</b>				<b>Prime</b>				<b>Continuous</b>
	<b>kW (kVA)</b>				<b>kW (kVA)</b>				<b>kW (kVA)</b>
<b>Ratings</b>	350 (438)				320 (400)				
<b>Load</b>	<b>1/4</b>	<b>1/2</b>	<b>3/4</b>	<b>Full</b>	<b>1/4</b>	<b>1/2</b>	<b>3/4</b>	<b>Full</b>	
<b>US gph</b>	9.0	14.3	19.4	24.1	8.5	13.4	18.1	22.1	
<b>L/hr</b>	34	54	73	91	32	51	69	84	

<b>Engine</b>	<b>Standby rating</b>	<b>Prime rating</b>	<b>Continuous rating</b>
Engine manufacturer	Cummins Inc.		
Engine model	QSX15-G9		
Configuration	Cast iron with replaceable wet cylinder liners, in-line 6 cylinder		
Aspiration	Turbocharged with air-to-air charge air cooling		
Gross engine power output, kWm (bhp)	563.0 (755.0)	507.3 (680.0)	
BMEP at set rated load, kPa (psi)	1716.8 (249.0)	1578.9 (229.0)	
Bore, mm (in)	136.9 (5.39)		
Stroke, mm (in)	168.9 (6.65)		
Rated speed, rpm	1800		
Piston speed, m/s (ft/min)	10.1 (1995.0)		
Compression ratio	17.0:1		
Lube oil capacity, L (qt)	83.3 (88.0)		
Overspeed limit, rpm	2150 ± 50		
Regenerative power, kW	52.0		

### Fuel flow

Fuel flow at rated load, L/hr (US gph)	423.9 (112.0)	
Maximum inlet restriction, mm Hg (in Hg)	127.0 (5.0)	
Maximum return restriction, mm Hg (in Hg)	165.1 (6.5)	

**Our energy working for you.™**

<b>Air</b>	<b>Standby rating</b>	<b>Prime rating</b>	<b>Continuous rating</b>
Combustion air, m <sup>3</sup> /min (scfm)	32.4 (1145.0)	31.1 (1100.0)	
Maximum air cleaner restriction, kPa (in H <sub>2</sub> O)	6.2 (25.0)		
Alternator cooling air, m <sup>3</sup> /min (scfm)	62.0 (2190.0)		

## Exhaust

Exhaust flow at set rated load, m <sup>3</sup> /min (cfm)	73.6 (2600.0)	70.9 (2505.0)	
Exhaust temperature, °C (°F)	432.2 (810.0)	429.4 (805.0)	
Maximum back pressure, kPa (in H <sub>2</sub> O)	10.2 (41.0)		

## Standard set-mounted radiator cooling

Ambient design, °C (°F)	40 (104)		
Fan load, kW <sub>m</sub> (HP)	19 (25.5)		
Coolant capacity (with radiator), L (US Gal)	57.9 (15.3)		
Cooling system air flow, m <sup>3</sup> /min (scfm)	707.5 (25000.0)		
Total heat rejection, MJ/min (Btu/min)	19.6 (18485.0)	17.7 (16680.0)	
Maximum cooling air flow static restriction, kPa (in H <sub>2</sub> O)	0.12 (0.5)		

## Optional set-mounted radiator cooling

Ambient design, °C (°F)	50 (122)		
Fan load, kW <sub>m</sub> (HP)	19 (25.5)		
Coolant capacity (with radiator), L (US gal)	57.9 (15.3)		
Cooling system air flow, m <sup>3</sup> /min (scfm)	707.5 (25000.0)		
Total heat rejection, MJ/min (Btu/min)	19.6 (18485.0)	17.7 (16680.0)	
Maximum cooling air flow static restriction, kPa (in H <sub>2</sub> O)	0.12 (0.5)		

## Optional heat exchanger cooling

Set coolant capacity, L (US Gal.)			
Heat rejected, jacket water circuit, MJ/min (Btu/min)			
Heat rejected, aftercooler circuit, MJ/min (Btu/min)			
Heat rejected, fuel circuit, MJ/min (Btu/min)			
Total heat radiated to room, MJ/min (Btu/min)			
Maximum raw water pressure, jacket water circuit, kPa (psi)			
Maximum raw water pressure, aftercooler circuit, kPa (psi)			
Maximum raw water pressure, fuel circuit, kPa (psi)			
Maximum raw water flow, jacket water circuit, L/min (US Gal/min)			
Maximum raw water flow, aftercooler circuit, L/min (US Gal/min)			
Maximum raw water flow, fuel circuit, L/min (US Gal/min)			
Minimum raw water flow at 27 °C (80 °F) inlet temp, jacket water circuit, L/min (US Gal/min)			
Minimum raw water flow at 27 °C (80 °F) inlet temp, aftercooler circuit, L/min (US Gal/min)			
Minimum raw water flow at 27 °C (80 °F) inlet temp, fuel circuit, L/min (US Gal/min)			
Raw water delta P at min flow, jacket water circuit, kPa (psi)			
Raw water delta P at min flow, aftercooler circuit, kPa (psi)			
Raw water delta P at min flow, fuel circuit, kPa (psi)			
Maximum jacket water outlet temp, °C (°F)			
Maximum aftercooler inlet temp, °C (°F)			
Maximum aftercooler inlet temp at 25 °C (77 °F) ambient, °C (°F)			

<b>Optional remote radiator cooling<sup>1</sup></b>	<b>Standby rating</b>	<b>Prime rating</b>	<b>Continuous rating</b>
Set coolant capacity, L (US gal)			
Max flow rate at max friction head, jacket water circuit, L/min (US gal/min)			
Max flow rate at max friction head, aftercooler circuit, L/min (US gal/min)			
Heat rejected, jacket water circuit, MJ/min (Btu/min)			
Heat rejected, aftercooler circuit, MJ/min (Btu/min)			
Heat rejected, fuel circuit, MJ/min (Btu/min)			
Total heat radiated to room, MJ/min (Btu/min)			
Maximum friction head, jacket water circuit, kPa (psi)			
Maximum friction head, aftercooler circuit, kPa (psi)			
Maximum static head, jacket water circuit, m (ft)			
Maximum static head, aftercooler circuit, m (ft)			
Maximum jacket water outlet temp, °C (°F)			
Maximum aftercooler inlet temp at 25 °C (77 °F) ambient, °C (°F)			
Maximum aftercooler inlet temp, °C (°F)			
Maximum fuel flow, L/hr (US gph)			
Maximum fuel return line restriction, kPa (in Hg)			

## Weights<sup>2</sup>

Unit dry weight kgs (lbs)	3856 (8500)
Unit wet weight kgs (lbs)	3992 (8800)

### Notes:

<sup>1</sup> For non-standard remote installations contact your local Cummins Power Generation representative.

<sup>2</sup> Weights represent a set with standard features. See outline drawing for weights of other configurations.

## Derating factors

<b>Standby</b>	Genset may be operated up to 3650 m (11900 ft) and 40 °C (104 °F) without power deration. For sustained operation above these conditions, derate by 1.8% per 305 m (1000 ft), and 10.0% per 10 °C (5.6% per 10 °F).
<b>Prime</b>	Genset may be operated up to 3650 m (11900 ft) and 40 °C (104 °F) without power deration. For sustained operation above these conditions, derate by 1.8% per 305 m (1000 ft), and 10.0% per 10 °C (5.6% per 10 °F).
<b>Continuous</b>	

## Ratings definitions

<b>Emergency standby power (ESP):</b>	<b>Limited-time running power (LTP):</b>	<b>Prime power (PRP):</b>	<b>Base load (continuous) power (COP):</b>
Applicable for supplying power to varying electrical load for the duration of power interruption of a reliable utility source. Emergency Standby Power (ESP) is in accordance with ISO 8528. Fuel Stop power in accordance with ISO 3046, AS 2789, DIN 6271 and BS 5514.	Applicable for supplying power to a constant electrical load for limited hours. Limited Time Running Power (LTP) is in accordance with ISO 8528.	Applicable for supplying power to varying electrical load for unlimited hours. Prime Power (PRP) is in accordance with ISO 8528. Ten percent overload capability is available in accordance with ISO 3046, AS 2789, DIN 6271 and BS 5514.	Applicable for supplying power continuously to a constant electrical load for unlimited hours. Continuous Power (COP) is in accordance with ISO 8528, ISO 3046, AS 2789, DIN 6271 and BS 5514.

## Alternator data

Three Phase Table <sup>1</sup>		105 °C	105 °C	125 °C	125 °C	125 °C	125 °C	125 °C	150 °C	150 °C	150 °C	150 °C	
Feature Code		B259	B301	B258	B252	B414	B246	B300	B426	B413	B424	B419	
Alternator Data Sheet Number		306	305	305	305	306	305	305	305	305	305	305	
Voltage Ranges		110/190 thru 139/240 220/380 thru 277/480	347/600	110/190 thru 139/240 220/380 thru 277/480	120/208 thru 139/240 240/416 thru 277/480	120/208 thru 139/240 240/416 thru 277/480	277/480	347/600	110/190 thru 139/240 220/380 thru 277/480	120/208 thru 139/240 240/416 thru 277/480	277/480	347/600	
Surge kW		512	515	509	512	514	515	515	509	512	515	515	
Motor Starting kVA (at 90% sustained voltage)	Shunt												
	PMG	1896	1749	1749	1749	1896	1749	1749	1749	1749	1749	1749	
Full Load Current Amps at Standby Rating		110/190 1329	120/208 1214	110/220 1148	115/230 1098	139/240 1052	220/380 665	230/400 631	240/416 607	255/440 574	277/480 526	347/600 421	

### Note:

<sup>1</sup> Single phase power can be taken from a three phase generator set at up to 40% of the generator set nameplate kW rating at unity power factor.

## Formulas for calculating full load currents:

### Three phase output

$$\frac{\text{kW} \times 1000}{\text{Voltage} \times 1.73 \times 0.8}$$

### Single phase output

$$\frac{\text{kW} \times \text{SinglePhaseFactor} \times 1000}{\text{Voltage}}$$

**Warning:** Back feed to a utility system can cause electrocution and/or property damage. Do not connect to any building's electrical system except through an approved device or after building main switch is open.

North America  
1400 73rd Avenue N.E.  
Minneapolis, MN 55432  
USA

Phone 763 574 5000  
Fax 763 574 5298

**Our energy working for you.™**

©2012 Cummins Power Generation Inc. All rights reserved.

Cummins Power Generation and Cummins are registered trademarks of Cummins Inc. PowerCommand, AmpSentry, InPower and "Our energy working for you." are trademarks of Cummins Power Generation. Other company, product, or service names may be trademarks or service marks of others. Specifications are subject to change without notice.

D-3398c (12/12)



[cumminspower.com](http://cumminspower.com)