

Model: DSGAB
Frequency: 60
Fuel type: Diesel
KW rating: 125 standby
113 prime
Emissions level: EPA NSPS Stationary Emergency Tier 3

➤ **Generator set data sheet**



Our energy working for you.™

Exhaust emission data sheet:	EDS-1084
Exhaust emission compliance sheet:	EPA-1118
Sound performance data sheet:	MSP-1056
Cooling performance data sheet:	MCP-171
Prototype test summary data sheet:	PTS-285
Standard set-mounted radiator cooling outline:	A035C611
Optional set-mounted radiator cooling outline:	
Optional heat exchanger cooling outline:	
Optional remote radiator cooling outline:	

Fuel consumption	Standby				Prime				Continuous
	kW (kVA)				kW (kVA)				kW (kVA)
Ratings	125 (156)				113 (141)				
Load	1/4	1/2	3/4	Full	1/4	1/2	3/4	Full	Full
US gph	3.77	6.02	6.36	10.30	3.67	5.51	7.75	9.59	
L/hr	14.3	22.8	31.7	39.0	13.9	20.8	29.3	36.3	

Engine	Standby rating	Prime rating	Continuous rating
Engine manufacturer	Cummins		
Engine model	QSB7-G5 NR3		
Configuration	Cast iron, in-line, 6 cylinder		
Aspiration	Turbocharged and air-to-air aftercooled		
Gross engine power output, kWm (bhp)	242 (324)	208 (279)	
BMEP at set rated load, kPa (psi)	1467 (213)	1331 (193)	
Bore, mm (in)	107 (4.21)		
Stroke, mm (in)	124 (4.88)		
Rated speed, rpm	1800		
Piston speed, m/s (ft/min)	7.4 (1464)		
Compression ratio	17.2:1		
Lube oil capacity, L (qt)	17.5 (18.5)		
Overspeed limit, rpm	2100		
Regenerative power, kW	19		

Fuel flow		
Maximum fuel flow, L/hr (US gph)	106 (28)	
Maximum fuel flow with C174, L/hr (US gph)		
Maximum fuel inlet restriction with clean filter, mm Hg (in Hg)	127 (5)	
Maximum return restriction, mm Hg (in Hg)	152 (6)	

Air	Standby rating	Prime rating	Continuous rating
Combustion air, m ³ /min (scfm)	14.1 (497)	13.9 (492)	
Maximum air cleaner restriction with clean filter, kPa (in H ₂ O)	3.7 (15)		
Alternator cooling air, m ³ /min (cfm)	37.0 (1308)		

Exhaust

Exhaust flow at set rated load, m ³ /min (cfm)	32.9 (1161)	32.1 (1133)	
Exhaust temperature, °C (°F)	446.1 (835)	438.2 (821)	
Maximum back pressure, kPa (in H ₂ O)	10 (40)		

Standard set-mounted radiator cooling

Ambient design, °C (°F)	54 (129)		
Fan load, kW _m (HP)	9.7 (13.0)		
Coolant capacity (with radiator), L (US Gal)	23 (6.1)		
Cooling system air flow, m ³ /min (scfm)	351 (12400)		
Total heat rejection, MJ/min (Btu/min)	7.39 (6997)	7.05 (6677)	
Maximum cooling air flow static restriction, kPa (in H ₂ O)	0.12 (0.5)		

Optional set-mounted radiator cooling

Ambient design, °C (°F)			
Fan load, kW _m (HP)			
Coolant capacity (with radiator), L (US Gal.)			
Cooling system air flow, m ³ /min (scfm)			
Total heat rejection, MJ/min (Btu/min)			
Maximum cooling air flow static restriction, kPa (in. H ₂ O)			

Optional heat exchanger cooling

Set coolant capacity, L (US Gal.)			
Heat rejected, jacket water circuit, MJ/min (Btu/min)			
Heat rejected, aftercooler circuit, MJ/min (Btu/min)			
Heat rejected, fuel circuit, MJ/min (Btu/min)			
Total heat radiated to room, MJ/min (Btu/min)			
Maximum raw water pressure, jacket water circuit, kPa (psi)			
Maximum raw water pressure, aftercooler circuit, kPa (psi)			
Maximum raw water pressure, fuel circuit, kPa (psi)			
Maximum raw water flow, jacket water circuit, L/min (US Gal/min)			
Maximum raw water flow, aftercooler circuit, L/min (US Gal/min)			
Maximum raw water flow, fuel circuit, L/min (US Gal/min)			
Minimum raw water flow at 27 °C (80 °F) inlet temp, jacket water circuit, L/min (US Gal/min)			
Minimum raw water flow at 27 °C (80 °F) inlet temp, aftercooler circuit, L/min (US Gal/min)			
Minimum raw water flow at 27 °C (80 °F) inlet temp, fuel circuit, L/min (US Gal/min)			
Raw water delta P at min flow, jacket water circuit, kPa (psi)			
Raw water delta P at min flow, aftercooler circuit, kPa (psi)			
Raw water delta P at min flow, fuel circuit, kPa (psi)			
Maximum jacket water outlet temp, °C (°F)			
Maximum aftercooler inlet temp, °C (°F)			
Maximum aftercooler inlet temp at 25 °C (77 °F) ambient, °C (°F)			

Our energy working for you.™

www.cumminspower.com

©2011 Cummins Power Generation Inc. All rights reserved. Cummins Power Generation and Cummins are registered trademarks of Cummins Inc. "Our energy working for you." is a trademark of Cummins Power Generation. Specifications are subject to change without notice. D-3350e (8/11)



Optional remote radiator cooling¹

	Standby rating	Prime rating	Continuous rating
Set coolant capacity, L (US gal)			
Max flow rate at max friction head, jacket water circuit, L/min (US gal/min)			
Max flow rate at max friction head, aftercooler circuit, L/min (US gal/min)			
Heat rejected, jacket water circuit, MJ/min (Btu/min)			
Heat rejected, aftercooler circuit, MJ/min (Btu/min)			
Heat rejected, fuel circuit, MJ/min (Btu/min)			
Total heat radiated to room, MJ/min (Btu/min)			
Maximum friction head, jacket water circuit, kPa (psi)			
Maximum friction head, aftercooler circuit, kPa (psi)			
Maximum static head, jacket water circuit, m (ft)			
Maximum static head, aftercooler circuit, m (ft)			
Maximum jacket water outlet temp, °C (°F)			
Maximum aftercooler inlet temp at 25 °C (77 °F) ambient, °C (°F)			
Maximum aftercooler inlet temp, °C (°F)			
Maximum fuel flow, L/hr (US gph)			
Maximum fuel return line restriction, kPa (in Hg)			

Weights²

Unit dry weight kgs (lbs.)	
Unit wet weight kgs (lbs.)	1225 (2700)

Notes:

¹ For non-standard remote installations contact your local Cummins Power Generation representative.

² Weights represent a set with standard features. See outline drawing for weights of other configurations.

Derating factors

Standby	Engine power available up to 3048 m (10,000 ft) at ambient temperature up to 40° C (104° F) and 2682 m (8800 ft) at 50° C (122° F). Consult your Cummins Power Generation distributor for temperature and ambient requirements outside these parameters.
Prime	Engine power available up to 3048 m (10,000 ft) at ambient temperature up to 40° C (104° F) and 1829 m (6000 ft) at 50° C (122° F). Consult your Cummins Power Generation distributor for temperature and ambient requirements outside these parameters.
Continuous	

Ratings definitions

Emergency standby power (ESP):	Limited-time running power (LTP):	Prime power (PRP):	Base load (continuous) power (COP):
Applicable for supplying power to varying electrical load for the duration of power interruption of a reliable utility source. Emergency Standby Power (ESP) is in accordance with ISO 8528. Fuel Stop power in accordance with ISO 3046, AS 2789, DIN 6271 and BS 5514.	Applicable for supplying power to a constant electrical load for limited hours. Limited Time Running Power (LTP) is in accordance with ISO 8528.	Applicable for supplying power to varying electrical load for unlimited hours. Prime Power (PRP) is in accordance with ISO 8528. Ten percent overload capability is available in accordance with ISO 3046, AS 2789, DIN 6271 and BS 5514.	Applicable for supplying power continuously to a constant electrical load for unlimited hours. Continuous Power (COP) is in accordance with ISO 8528, ISO 3046, AS 2789, DIN 6271 and BS 5514.

Our energy working for you.™

www.cumminspower.com

Alternator data

Three Phase Table ¹		105° C	105° C	105° C	105° C	125° C	125° C	125° C	125° C	125° C	150° C	150° C	150° C
Feature Code		B418	B415	B268	B304	B417	B414	B267	B246	B303	B416	B413	B419
Alternator Data Sheet Number		209	209	211	208	208	208	211	208	208	208	208	208
Voltage Ranges		110/190 Thru 120/208 220/380 Thru 240/416	120/208 Thru 139/240 240/416 Thru 277/480	120/208 Thru 139/240 240/416 Thru 277/480	347/600	110/190 Thru 120/208 220/380 Thru 240/416	120/208 Thru 139/240 240/416 Thru 277/480	120/208 Thru 139/240 240/416 Thru 277/480	139/240 277/480	347/600	110/190 Thru 120/208 220/380 Thru 240/416	120/208 Thru 139/240 240/416 Thru 277/480	347/600
Surge kW		160	161	163	160	159	159	163	160	160	159	160	160
Motor Starting kVA (at 90% sustained voltage)	Shunt	516	516	672	422	422	422	672	422	422	422	422	422
	PMG	607	607	791	497	497	497	791	497	497	497	497	497

Full Load Current - Amps at Standby Rating	<u>120/208</u>	<u>127/220</u>	<u>139/240</u>	<u>220/380</u>	<u>240/416</u>	<u>254/440</u>	<u>277/480</u>	<u>347/600</u>
	434	411	376	238	217	205	188	151

Single Phase Table		105° C	105° C	105° C	125° C	125° C	125° C	150° C					
Feature Code		B418	B415	B268	B417	B414	B267	B413					
Alternator Data Sheet Number		209	209	211	208	208	211	208					
Voltage Ranges		120/240 ²	120/240 ²	120/240 ³	120/240 ²	120/240 ²	120/240 ³	120/240 ²					
Surge kW		156	156	159	156	156	159	156					
Motor Starting kVA (at 90% sustained voltage)	Shunt	305	305	395	250	250	395	250					
	PMG	360	360	465	290	290	465	290					

Full Load Current - Amps at Standby Rating	<u>120/240²</u>	<u>120/240³</u>
	347	521

¹ Single phase power can be taken from a three phase generator set at up to 2/3 set rated 3-phase kW at 1.0 power factor. Also see Note 3 below.

² The broad range alternators can supply single phase output up to 2/3 set rated 3-phase kW at 1.0 power factor.

³ The extended stack (full single phase output) and 4 lead alternators can supply single phase output up to full set rated 3-phase kW at 1.0 power factor.

Formulas for calculating full load currents:

Three phase output

$$\frac{\text{kW} \times 1000}{\text{Voltage} \times 1.73 \times 0.8}$$

Single phase output

$$\frac{\text{kW} \times \text{Single Phase Factor} \times 1000}{\text{Voltage}}$$

Cummins Power Generation

1400 73rd Avenue N.E.
Minneapolis, MN 55432 USA
Telephone: 763 574 5000
Fax: 763 574 5298

Warning: Back feed to a utility system can cause electrocution and/or property damage. Do not connect to any building's electrical system except through an approved device or after building main switch is open.

Our energy working for you.™

www.cumminspower.com