

VersaLink[®] C7000 Series Color Multifunction Printers are built on Xerox[®] ConnectKey[®] Technology. For more information, go to www.ConnectKey.com.



System Specifications	VersaLink [®] C7020	VersαLink [®] C7025	VersαLink [®] C7030
One-sided Speed 8.5 x 11 in. / A4 / 210 x 297 mm 8.5 x 14 in. / 216 x 356 mm 11 x 17 in. / A3 / 297 x 420 mm	Up to 20 ppm (pages per minute) long edge feed (LEF) Up to 16 ppm Up to 11 ppm	Up to 25 ppm LEF Up to 19 ppm Up to 14 ppm	Up to 30 ppm LEF Up to 23 ppm Up to 17 ppm
Two-sided Speed 8.5 x 11 in. / A4 / 210 x 297 mm 8.5 x 14 in. / 216 x 356 mm 11 x 17 in. / A3 / 297 x 420 mm	Up to 16 ppm LEF Up to 9 ppm Up to 8 ppm	Up to 19 ppm LEF Up to 10 ppm Up to 9 ppm	Up to 23 ppm LEF Up to 12 ppm Up to 11 ppm
Monthly Duty Cycle ¹	Up to 87,000 pages / month ¹	Up to 107,000 pages / month ¹	Up to 129,000 pages / month ¹
Recommended Average Monthly Print Volume ²	Up to 5,500 pages	Up to 6,250 pages	Up to 7,000 pages
Hard Drive	320 GB HDD (Optional on Desktop \ Base Unit)		
Processor	1.05 GHz Dual-Core		
Memory	4 GB		
Connectivity	Ethernet 10/100/1000 Base-T, High-speed USB 3.0, Wi-Fi 802.11n/g/b/a and Wi-Fi Direct with optional Wi-Fi Kit (concurrent wired and wireless connections supported), NFC Tap-to-Pair		
Controller Features	Unified Address Book, Configuration Cloning, Scan Preview, Xerox Extensible Interface Platform [®] , Xerox App Gallery, Xerox [®] Standard Accounting, Network Accounting Enabled, Role Based Permissions, Convenience Authentication Enabled, Online Support		

User Interface Languages		German, Spanish, Brazilian ek, Turkish, Polish, Czech, H		
Device Specifications	VersaLink [®] C7020	VersaLink [®] C7	025 Verse	aLink [®] C7030
Electrical Requirements				
North America	Voltage: 110-127V -10 % / +6 % Frequency: 50/60 Hz +/-3 % , 12A			
Europe and Other Geographies	Voltage: 220-240V +/- 10% Frequency: 50 Hz +/-3%, 8A			
Power Consumption				
Printing⁵		For 110V: 20 ppm = 0.9 kWh; 25 ppm = 1.1 kWh; 30 ppm = 1.5 kWh For 220V: 20 ppm = 0.9 kWh; 25 ppm = 1.1 kWh; 30 ppm = 1.5 kWh		
Standby Mode ⁵	110V: 80 watts or less 220V: 80 watts or less	110V: 80 watts 220V: 80 watts		': 94 watts or less ': 94 watts or less
Sleep Mode ⁵	110V: 1.0 watts or less 220V: 1.4 watts or less			
Operating Environment				
Required Temperature Range (Storage)	32° to 95° F (0° to 35° C)			
Required Temperature Range (Operating)	50 to 90° F (10 to 32° C)			
Required Relative Humidity	10 % to 85 %			
Sound Power Levels	Printing: 6.70 B(A) or less • 20 ppm = 6.45 B(A); 25 ppm = 6.50 B(A); 30 ppm = 6.70 B(A) Standby: 4.10 B(A) or less • 20 ppm = 4.10 B(A); 25 ppm = 4.10 B(A); 30 ppm = 4.10 B(A) Full System (including Finisher and HCF) Printing: 20 ppm = 7.07 B(A); 25 ppm = 7.22 B(A); 30 ppm = 7.37 B(A) Standby: 20 ppm = 4.10 B(A); 25 ppm = 4.10 B(A); 30 ppm = 4.10 B(A)			
Sound Pressure Levels	Printing: 52.0 dB(A) • 20 ppm = 49.5 dB(A); 25 ppm = 50.0 dB(A); 30 ppm = 52.0 dB(A) Standby: 26.0 dB(A) • 20 ppm = 26.0 dB(A); 25 ppm = 26.0 dB(A); 30 ppm = 26.0 dB(A) Full System (including Finisher and HCF) Printing: 20 ppm = 55.5 dB(A); 25 ppm = 57.0 dB(A); 30 ppm = 58.5 dB(A) Standby: 20 ppm = 26.0 dB(A); 25 ppm = 26.0 dB(A); 30 ppm = 26.0 dB(A)			
Boot Time (from Off to UI Ready)	As fast as 98 seconds			
Warm-up Time (from Sleep to UI Ready)	As fast as 12 seconds			
Dimensions and Weight (Unpackaged)	Width	Depth	Height	Weight
Base Unit	23.23 in. / 590 mm	26.41 in. / 670.8 mm	30.23 in. / 767.9 mm	147.71 lbs. / 67.0 kg
Base Unit with Single Tray with Stand Module	24.24 in. / 615.7 mm	26.41 in. / 670.8 mm	44.04 in. / 1118.6 mm	202.83 lbs. / 92.0 kg
Base Unit with High Capacity Tandem Tray Module	24.24 in. / 615.7 mm	26.41 in. / 670.8 mm	44.04 in. / 1118.6 mm	203.71 lbs. / 92.4 kg

Base Unit with Three Tray Module	24.24 in. / 615.7 mm	26.41 i	n. / 670.8 mm	44.04 in. / 1118	.6 mm	208.34 lbs. / 94.5 kg
Base Unit with Three Tray Module and Office Finisher LX (with Booklet Maker)	47.0 in. / 1194.0 mm	7.0 in. / 1194.0 mm 26.8 in. / 681.8		44.04 in. / 1118.6 mm		291.89 lbs. / 132.4 kg
Certifications						
To view the latest list of certification	ons, go to www.xerox.com	/OfficeCe	rtifications.			
Print	VersaLink® C7020	VersaLink [®] C7020 VersaLink [®] C7025		025	VersαLink [®] C7030	
First-Print-Out Time	As fast as 9.4 seconds co	olor	As fast as 9.4 se	econds color	nds color As fast as 7.3 seconds color	
	As fast as 7.2 seconds b	lack	As fast as 7.1 se	econds black	As fast	as 5.6 seconds black
Print Resolution	Up to 1200 x 2400 dpi					
Page Description Languages	PCL [®] 5e, 6 PDF XPS TIFF JPEG HP-GL Adobe [®] PostScript [®] 3 [™] (Optional)					
Maximum Print Area	4 mm from Lead edge o	of paper, 2	mm from Side a	nd Trail edges of po	aper	
Print Features	Adobe® PostScript® 3™ (Optional) 4 mm from Lead edge of paper, 2 mm from Side and Trail edges of paper Application Defaults Banner Pages Enable / Disable Bi-directional Real-time Status Booklet Layout Color Correction Color Adjustments (lightness, contrast, saturation, color balance) Draft Mode Finishing (requires finishing) Fit to New Paper Size Job Identification (Print ID or Banner, Print ID in margins on first page only or all pages) Job Monitoring (Client or Local User Interface) LAN Fax (requires Fax Kit) N-up Page Layout (up to 16 pages per sheet) Paper Selection by Attribute Personal Print Print from USB Sample Set Saved Job Scaling Secure Print Skip Blank Pages Special Pages (exception page programming: covers, inserts, exceptions pages) Store and Recall Driver Settings Stored Jobs Deletion Two-sided Printing (as default) Watermark (predefined and custom) Xeerox® Earth Smart Driver Settings					
Print from USB	Allows walk-up printing from Type A USB port Supports direct printing from computer via Type B USB port Supported file formats: PDF, JPEG, TIFF, XPS, PDF/A					

Operating Systems	macOS [®] 10.11, 10.12, 10.13 Citrix [®] Redhat [®] Enterprise Linux [®] Fedora Core IBM [®] AIX [®] HP-UX [®] Oracle [®] Solaris SUSE [®] SAP [®] Note: For information about sup	er 2008 R2 SP1, Server 2012, Server oported versions for the above opera specify your device at www.support	ating systems, please visit our	
Fonts	PostScript fonts: 136 PCL fonts: 83			
Xerox [®] Mobile Express Driver [®]	Makes it easy for mobile users to find, use and manage Xerox [®] and non-Xerox [®] devices in every new location. Plug into a new network, and Mobile Express Driver [®] automatically discovers available printers and provides status and capability information. Save a list of "favorite" printers for each location, store application print settings for use on any printer in any network, and greatly reduce mobile support calls to IT.			
Xerox [®] Global Print Driver [®]	A truly universal print driver that lets IT administrators install, upgrade and manage Xerox [®] and non-Xerox [®] devices from a single driver. It provides a consistent, easy-to-use interface for end-users, reducing the number of support calls, and simplifying print services management.			
Xerox [®] Pull Print Driver	Makes it easy for IT managers to qualify, deploy and manage all print devices using a single driver in a Pull Print environment. Uses a single queue and single driver. The Xerox [®] Pull Print Driver extends convenience across a broad range of printing assets. IT administrators no longer need to manage and configure multiple drivers. Used in conjunction with Equitrac Office [®] , Ysoft [®] SafeQ [®] , Pharos [®] and others.			
	and others.	in conjunction with Equilibre office		
Сору	and others. VersaLink [®] C7020	VersaLink [®] C7025	VersaLink [®] C7030	
Copy Document Scanner		VersaLink [©] C7025		
	VersaLink [®] C7020	VersαLink [®] C7025 ocument Feeder (DADF) 62.0 x 437 mm		
Document Scanner	VersaLink [®] C7020 110-sheet Duplex Automatic Do Platen: Up to 13.1 x 17.2 in. / 33	VersαLink [®] C7025 ocument Feeder (DADF) 62.0 x 437 mm		
Document Scanner Document Scanner Size	VersaLink® C7020110-sheet Duplex Automatic DoPlaten: Up to 13.1 x 17.2 in. / 33DADF: Up to 11.7 x 17 in. / 297Up to 20 cpm (copies per minute) 8.5 x 11 in. Up to 20 cpm A4 (210 x 297)	VersaLink [®] C7025 becument Feeder (DADF) 32.0 x 437 mm x 431.8 mm Up to 25 cpm (copies per minute) 8.5 x 11 in. Up to 25 cpm A4 (210 x 297	VersaLink [®] C7030 Up to 30 cpm (copies per minute) 8.5 x 11 in. Up to 30 cpm A4 (210 x 297	
Document Scanner Document Scanner Size Simplex Copy Speed	VersaLink® C7020 110-sheet Duplex Automatic Do Platen: Up to 13.1 x 17.2 in. / 33 DADF: Up to 11.7 x 17 in. / 297 Up to 20 cpm (copies per minute) 8.5 x 11 in. Up to 20 cpm A4 (210 x 297 mm) Up to 17 cpm (copies per minute) 8.5 x 11 in. Up to 17 cpm A4 (210 x 297 mm)	VersaLink® C7025boument Feeder (DADF)52.0 x 437 mm x 431.8 mmUp to 25 cpm (copies per minute) 8.5 x 11 in. Up to 25 cpm A4 (210 x 297 mm)Up to 18 cpm (copies per minute) 8.5 x 11 in. Up to 18 cpm (copies per minute) 8.5 x 11 in. Up to 18 cpm A4 (210 x 297	VersaLink® C7030Up to 30 cpm (copies per minute) 8.5 x 11 in. Up to 30 cpm A4 (210 x 297 mm)Up to 18 cpm (copies per minute) 8.5 x 11 in. Up to 18 cpm A4 (210 x 297	
Document Scanner Document Scanner Size Simplex Copy Speed Duplex Copy Speed	VersaLink® C7020 110-sheet Duplex Automatic Doc Platen: Up to 13.1 x 17.2 in. / 33 DADF: Up to 11.7 x 17 in. / 297 Up to 20 cpm (copies per minute) 8.5 x 11 in. Up to 20 cpm A4 (210 x 297 mm) Up to 17 cpm (copies per minute) 8.5 x 11 in. Up to 17 cpm A4 (210 x 297 mm)	VersaLink® C7025 boument Feeder (DADF) b2.0 x 437 mm x 431.8 mm Up to 25 cpm (copies per minute) 8.5 x 11 in. Up to 25 cpm A4 (210 x 297 mm) Up to 18 cpm (copies per minute) 8.5 x 11 in. Up to 18 cpm A4 (210 x 297 mm)	VersaLink® C7030Up to 30 cpm (copies per minute) 8.5 x 11 in. Up to 30 cpm A4 (210 x 297 mm)Up to 18 cpm (copies per minute) 8.5 x 11 in. Up to 18 cpm A4 (210 x 297 mm)	
Document Scanner Document Scanner Size Simplex Copy Speed Duplex Copy Speed	VersaLink® C7020110-sheet Duplex Automatic DoPlaten: Up to 13.1 x 17.2 in. / 33DADF: Up to 11.7 x 17 in. / 297Up to 20 cpm (copies per minute) 8.5 x 11 in. Up to 20 cpm A4 (210 x 297 mm)Up to 17 cpm (copies per minute) 8.5 x 11 in. Up to 17 cpm A4 (210 x 297 mm)Up to 17 cpm A4 (210 x 297 mm)As fast as 9.0 seconds color	VersaLink® C7025bcument Feeder (DADF)32.0 x 437 mm x 431.8 mmUp to 25 cpm (copies per minute) 8.5 x 11 in. Up to 25 cpm A4 (210 x 297 mm)Up to 18 cpm (copies per minute) 8.5 x 11 in. Up to 18 cpm A4 (210 x 297 mm)Up to 18 cpm A4 (210 x 297 mm)As fast as 9.0 seconds color	VersaLink® C7030Up to 30 cpm (copies per minute) 8.5 x 11 in. Up to 30 cpm A4 (210 x 297 mm)Up to 18 cpm (copies per minute) 8.5 x 11 in. Up to 18 cpm A4 (210 x 297 mm)As fast as 7.2 seconds color	
Document Scanner Document Scanner Size Simplex Copy Speed Duplex Copy Speed First-Copy-Out Time	VersaLink® C7020110-sheet Duplex Automatic DoPlaten: Up to 13.1 x 17.2 in. / 33DADF: Up to 11.7 x 17 in. / 297Up to 20 cpm (copies per minute) 8.5 x 11 in. Up to 20 cpm A4 (210 x 297 mm)Up to 17 cpm (copies per minute) 8.5 x 11 in. Up to 17 cpm A4 (210 x 297 mm)As fast as 9.0 seconds color As fast as 6.9 seconds black	VersaLink® C7025bcument Feeder (DADF)32.0 x 437 mm x 431.8 mmUp to 25 cpm (copies per minute) 8.5 x 11 in. Up to 25 cpm A4 (210 x 297 	VersaLink® C7030Up to 30 cpm (copies per minute) 8.5 x 11 in. Up to 30 cpm A4 (210 x 297 mm)Up to 18 cpm (copies per minute) 8.5 x 11 in. Up to 18 cpm A4 (210 x 297 mm)As fast as 7.2 seconds color	
Document Scanner Document Scanner Size Simplex Copy Speed Duplex Copy Speed First-Copy-Out Time Sides (input: output)	VersaLink® C7020110-sheet Duplex Automatic DoPlaten: Up to 13.1 x 17.2 in. / 33DADF: Up to 11.7 x 17 in. / 297Up to 20 cpm (copies per minute) 8.5 x 11 in. Up to 20 cpm A4 (210 x 297 mm)Up to 17 cpm (copies per minute) 8.5 x 11 in. Up to 17 cpm A4 (210 x 297 mm)As fast as 9.0 seconds color As fast as 6.9 seconds black1:1, 1:2, 2:2 and 2:1	VersaLink® C7025bcument Feeder (DADF)32.0 x 437 mm x 431.8 mmUp to 25 cpm (copies per minute) 8.5 x 11 in. Up to 25 cpm A4 (210 x 297 mm)Up to 18 cpm (copies per minute) 8.5 x 11 in. Up to 18 cpm A4 (210 x 297 mm)Up to 18 cpm A4 (210 x 297 mm)As fast as 9.0 seconds color	VersaLink® C7030Up to 30 cpm (copies per minute) 8.5 x 11 in. Up to 30 cpm A4 (210 x 297 mm)Up to 18 cpm (copies per minute) 8.5 x 11 in. Up to 18 cpm A4 (210 x 297 mm)As fast as 7.2 seconds color	
Document Scanner Document Scanner Size Simplex Copy Speed Duplex Copy Speed First-Copy-Out Time Sides (input: output) Quantity	VersaLink® C7020 110-sheet Duplex Automatic Do Platen: Up to 13.1 x 17.2 in. / 33 DADF: Up to 11.7 x 17 in. / 297 Up to 20 cpm (copies per minute) 8.5 x 11 in. Up to 20 cpm A4 (210 x 297 mm) Up to 17 cpm (copies per minute) 8.5 x 11 in. Up to 17 cpm A4 (210 x 297 mm) As fast as 9.0 seconds color As fast as 6.9 seconds black 1:1, 1:2, 2:2 and 2:1 1 to 999	VersaLink [®] C7025 boument Feeder (DADF) 32.0 x 437 mm x 431.8 mm Up to 25 cpm (copies per minute) 8.5 x 11 in. Up to 25 cpm A4 (210 x 297 mm) Up to 18 cpm (copies per minute) 8.5 x 11 in. Up to 18 cpm (copies per minute) 8.5 x 11 in. Up to 18 cpm A4 (210 x 297 mm) As fast as 9.0 seconds color As fast as 9.0 seconds color As fast as 6.9 seconds black	VersaLink® C7030Up to 30 cpm (copies per minute) 8.5 x 11 in. Up to 30 cpm A4 (210 x 297 mm)Up to 18 cpm (copies per minute) 8.5 x 11 in. Up to 18 cpm A4 (210 x 297 mm)As fast as 7.2 seconds color	

Copy Features	Annotation (Page Numbers, Comments, Date Stamp, Bates Stamping)* Auto-color Sensing Automatic Background Suppression Book Copying with Center Erase Booklet Copying* Collation Color Balance Color Effects Darkness Control Edge Erase Front Cover ID Card Copy Image Enhancement Image Shift Lighten / Darken N-up Original Orientation Original Size Original Type Page Layout Reduce / Enlarge 25% to 400% Sample Copy Saturation Sharpness
	*Requires HDD / Productivity Kit
Scan	
Capability	Black-and-white and color scanning
Concurrency	Scan while the system is printing copy or network print jobs, or while it is transferring scan to network or fax jobs
Simplex Input Speed	Black-and-white: Scan up to 55 ipm – 8.5 x 11 in. / A4 (210 x 297 mm) Color: Scan up to 55 ipm – 8.5 x 11 in. / 55 ipm A4 (210 x 297 mm)
Duplex Input Speed	Black-and-white: Scan up to 26 ipm – 8.5 x 11 in. / A4 (210 x 297 mm) Color: Scan up to 26 ipm – 8.5 x 11 in. / 26 ipm A4 (210 x 297 mm)
Resolution	Optical – 600 x 600 dpi
Bit Depth	24-bit color / 8-bit grayscale
Maximum Scan Area	Platen: Up to 13.1 x 17.2 in. / 332 x 437 mm Document Feeder: 11.7 x 17 in. / 297 x 431.8 mm
Network Filing Protocols	FTP SMTP SMB
File Formats	JPG TIFF (single and multi-page) XPS (single and multi-page) PDF (single and multi-page) Searchable PDF via Optical Character Recognition (OCR) Password-protected PDF Linearized PDF (set via embedded web server) and PDF/A
Scan Driver Compatibility (Network Only)	WIA TWAIN
Supported Scan Destinations	Scan to Home Scan to USB Scan to Email Scan to Network (Browse FTP or Browse SMB)

Network Scanning – Software Sc	
Xerox [®] ConnectKey [®] Apps (Found at the Xerox App Gallery)	Increase user productivity by simplifying and shortening everyday tasks. Unlike traditional software, ConnectKey [®] Apps do not require a dedicated server, PC or IT resource. Instead, simply download these lightweight, serverless ConnectKey [®] Apps to the ConnectKey [®] Technology-enabled multifunction printer.
PSTN One-line or Three-line Fax	(Optional)
Fax ³	
Fax Speed	33.6 Kbps
Resolution	Standard 200x100 dpi, Fine 200x200 dpi, Super Fine 300x300, 400x400, 600x600 dpi
Compression	MH, MR, MMR, JBIG
Fax Features	Walk-up Fax, includes LAN Fax, Direct Fax, Fax Forward to Email Fax dialing via Unified Address Book (up to 2,000 contacts)
Fax over IP (Optional)	
Compliance	T.38 compliant IP / SIP
Resolution	Standard 200x100 dpi, Fine 200x200 dpi, Super Fine 300x300, 400x400, 600x600 dpi
Compression	MH, MR, MMR, JBIG
Fax Features	Walk-up Fax, includes LAN Fax, Direct Fax, Fax Forward to Email Fax dialing via Unified Address Book (up to 2,000 contacts)
Mobile Solutions and Mobile De	vice Apps
Apple [®] AirPrint [®]	Print email, photos and important office documents directly from an Apple iPhone [®] or iPad [®] with no drivers to install and no cables to connect. With AirPrint, an iPhone or iPad automatically locates and connects to the AirPrint-enabled device over the office Wi-Fi network.
Google Cloud Print™	Google Cloud Print connects print devices to the web, enabling users to print the applications they use every day from smartphones, tablets, Chromebook™ notebook computers and any other web-connected device.
Mopria [®] Certified	ConnectKey [®] Technology-enabled print devices are Mopria [®] certified. Mopria [®] certification ensures you can print wirelessly from your Mopria [®] supported (Android) smart phone, tablet and other mobile devices instantly and easily.
@PrintByXerox	@PrintByXerox is a free service that allows secure printing from any email-enabled device (computer, phone, tablet, iOS, Android™, Google® Chromebook™ and more) to a Xerox® printer or MFP using a single email address with no IT intervention. No training is needed. End-users simply send attachments to the email address, and release them at the MFP panel.
Xerox® Print Service Plug-in for Android™ (Free at Google Play™ Store)	The Xerox [®] Print Service Plug-in for Android KitKat (4.4 or greater) devices streamlines mobile printing without third-party apps or additional print drivers. You can easily print photos, web pages and documents when your mobile device is connected to multifunction printers using a wireless network. A robust print option set includes two-sided printing, stapling and secure code release. A free download is available from the Google Play [™] store.
Xerox [®] Mobile Link App (Free at Google Play™ Store and Apple [®] App Store)	The Xerox [®] Mobile Link App allows you to scan, email and fax from your phone or tablet by connecting with our multifunction printers and send data to and print data from cloud storage. It is easy to create Mobile Link One-Touch Workflows between a mobile device and a multifunction printer. Using a manual address or QR code identification for pairing, automatic device discovery makes it easy to find and pair a mobile device with a nearby Xerox [®] multifunction printer.
Xerox® Workplace Suite and Xerox® Workplace Cloud	Xerox [®] Workplace Suite is a modular set of workflows designed to save customers time and money by providing effective control over their print fleet, while enabling worker productivity and mobility through a set of robust workflows. Xerox enables ultimate customer flexibility by offering these capabilities in both an on-premises server version (Workplace Suite) and with a cloud based-version (Workplace Cloud) of this solution.

Security	
Security Features	Access Controls AES 256-bit Encryption Audit Log Certificate Path Validation Certificate Revocation List (CRL) / Status Protocol (OCSP) Detection of External Program Falsification (XCP Plug-in) Cisco® Identity Services Engine (ISE) Integration Domain Filtering FIPS 140-2 Firmware Verification Immediate Disk Overwrite* IP Address Filtering IPsec Network Authentication Port Filtering Pre-installed Self-Signed Certificates Role Based Permissions Secure Email Secure Fax Secure Print Security Certificate Management Smart Card Enablement (CAC/PIV/.NET) SNMPv3 Status Protocol (OCSP) TLS / SSL
Accounting	
Xerox [®] Standard Accounting / No	etwork Accounting (Standard)
Tracking	Copy, Print, Fax, Scan and Email usage
Accounting	Xerox [®] Standard Accounting Tool Up to 1,000 User Accounts without HDD Up to 9,999 User Accounts with HDD Up to 500 General Accounts Network Accounting (Job Based Accounting) Up to 1,000 User IDs; Up to 1,000 Account IDs without HDD Up to 60,000 User IDs; Up to 60,000 Account IDs with HDD Up to 14,000 Accounting Records (transactions)
Features	Administrator can manage the feature via the Embedded Web Server.
Accounting Options – Network A	ccounting (Allows central server to manage all accounting)
	 Enhanced network accounting with up to the minute data on how the system is being used Comprehensive management and enterprise scale tracking and reporting of device usage of copy, print, scan and fax Numerous solutions are available through Xerox Alliance Partners. For details visit www.xerox.com Security enhancements include simultaneous support for HTTP/HTTPS protocols Device requests account authentication from third party server enabling larger databases of users and accounts Accept Authentication Login at control panel and pass to third party Networking Account

Paper Handling	
Document Feeder	
Capacity ⁴	Duplex Automatic Document Feeder (DADF): 110 sheets
Sizes One-sided: Two-sided:	Custom sizes: 4.92 x 3.35 in. to 11.69 x 17 in. / 125 x 85 mm to 297 x 431.8 mm 4.92 x 4.33 in. to 11.69 x 17 in. / 125 x 110 mm to 297 x 431.8 mm
Weights One-sided: Two-sided:	11 to 34 lb. bond / 38 to 128 gsm 13 to 34 lb. bond / 50 to 128 gsm
Bypass Tray	
Capacity ⁴	100 sheets
Sizes	Custom sizes: 3.5 x 3.87 in. to 11.69 x 17 in. / 88.9 x 98.4 mm to 297 x 431.8 mm
Weights One-sided: Two-sided:	16 lb. bond to 80 lb. cover / 60 to 216 gsm 16 lb. bond to 60 lb. cover / 60 to 169 gsm
Types	Bond Plain Paper Cardstock Custom Envelopes Hole Punched Labels Heavyweight Labels Letterhead Lightweight Cardstock Lightweight Glossy Cardstock Lightweight Glossy Cardstock Reload Pre-Printed Recycled
Tray 1	
Capacity ⁴	520 sheets
Sizes	Custom sizes: 5.5 x 7.17 in. to 11.69 x 17 in. / 139.7 x 182.0 mm to 297.0 x 431.8 mm
Weights One-sided: Two-sided:	16 lb. bond to 95 lb. cover / 60 to 256 gsm 16 lb. bond to 60 lb. cover / 60 to 169 gsm
Types	Bond Plain Paper Cardstock Custom Hole Punched Labels Heavyweight Labels Extra Heavyweight Labels Letterhead Lightweight Cardstock Lightweight Glossy Cardstock Reavyweight Glossy Cardstock Reload Heavyweight Cardstock Recycled

Single Tray Module (Optional – Base Model only)		
Capacity ⁴	520 sheets	
Sizes	Custom sizes: 5.5 x 7.17 in. to 11.69 x 17 in. / 139.7 x 182.0 mm to 297.0 x 431.8 mm	
Weights One-sided: Two-sided:	16 lb. bond to 95 lb. cover / 60 to 256 gsm 16 lb. bond to 60 lb. cover / 60 to 169 gsm	
Types	Bond Plain Paper Cardstock Custom Hole Punched Labels Heavyweight Labels Extra Heavyweight Labels Letterhead Lightweight Cardstock Lightweight Glossy Cardstock Lightweight Glossy Cardstock Reload Heavyweight Cardstock Pre-Printed Recycled	
Single Tray Module wit	h Stand (Optional)	
Capacity ⁴	520 sheets	
Sizes	Custom sizes: 5.5 x 7.17 in. to 11.69 x 17 in. / 139.7 x 182.0 mm to 297.0 x 431.8 mm	
Weights One-sided: Two-sided:	16 lb. bond to 95 lb. cover / 60 to 256 gsm 16 lb. bond to 60 lb. cover / 60 to 169 gsm	
Types	Bond Plain Paper Cardstock Custom Hole Punched Labels Heavyweight Labels Extra Heavyweight Labels Letterhead Lightweight Cardstock Lightweight Glossy Cardstock Reload Heavyweight Cardstock Pre-Printed Recycled	
Three Tray Module (Op	tional)	
Capacity ⁴	Tray 2: 520 sheets Tray 3: 520 sheets Tray 4: 520 sheets	
Sizes	Custom sizes: 5.5 x 7.17 in. to 11.69 x 17 in. / 139.7 x 182.0 mm to 297.0 x 431.8 mm	
Weights One-sided: Two-sided:	16 lb. bond to 95 lb. cover / 60 to 256 gsm 16 lb. bond to 60 lb. cover / 60 to 169 gsm	

Types	Bond Plain Paper Cardstock Custom Hole Punched Labels Heavyweight Labels Extra Heavyweight Labels Letterhead Lightweight Cardstock Lightweight Glossy Cardstock Lightweight Glossy Cardstock Reload Heavyweight Cardstock Pre-Printed Recycled
High Capacity Tandem Tray M	odule (Optional)
Capacity ⁴	Tray 2: 520 sheets Tray 3: 870 sheets Tray 4: 1,130 sheets
Sizes	Tray 2: Custom sizes: 5.5 x 7.17 in. to 11.69 x 17 in. / 139.7 x 182.0 mm to 297.0 x 431.8 mm Tray 3: Standard Sizes: 8.5 x 11 in. and 7.25 x 10.5 in. / A4 or B5 Tray 4: Standard Sizes: 8.5 x 11 in. and 7.25 x 10.5 in. / A4 or B5
Weights One-sided: Two-sided:	16 lb. bond to 95 lb. cover / 60 to 256 gsm 16 lb. bond to 60 lb. cover / 60 to 169 gsm
Types	Bond Plain Paper Cardstock Custom Hole Punched Labels Heavyweight Labels Extra Heavyweight Labels Letterhead Lightweight Cardstock Lightweight Glossy Cardstock Lightweight Glossy Cardstock Reload Heavyweight Cardstock Pre-Printed Recycled
Envelope Tray – Replaces Tray	1 (Optional)
Capacity ⁴	Up to 60 envelopes
Sizes	#10 commercial, Monarch, DL, C5 Custom sizes: 3.9 x 5.8 in. to 6.4 x 9.5 in. / 98 x 148 mm to 162 x 241 mm
Weights	20 to 25 lb. bond / 75 to 90 gsm
High Capacity Feeder (Optiona	1)
Capacity ⁴	2,000 sheets
Sizes	Standard Sizes: 8.5 x 11 in. and 7.25 x 10.5 in. / A4 or B5
Weights One-sided: Two-sided:	16 lb. bond to 80 lb. cover / 60 to 216 gsm 16 lb. bond to 60 lb. cover / 60 to 169 gsm

Total Capacity		
Base Unit Capacity ⁴	620 sheets	
Single Tray Module Capacity ⁴	1,140 sheets	
Single Tray Module with Stand Capacity ⁴	1,140 sheets	
Three Tray Module Capacity ⁴	2,180 sheets	
High-Capacity Tandem Tray Capacity ⁴	3,140 sheets	
Finishing		
Output Trays (Optional on Base N	lodel)	
Dual Catch Trays ⁴	250 sheets each; Lower tray offsets	
Integrated Office Finisher (Option	nal)	
Stacking Tray	500 sheets of 20 lb. bond / 80 gsm – 8.5 x 11 in. / A4 or 250 sheets of 20 lb. bond / 80 gsm – 11 x 17 in. / A3	
Sizes	3.5 x 3.9 in. to 11.7 x 17 in. / 89 x 98 mm to 297 x 432 mm	
Weights	16 lb. bond to 80 lb. cover / 60 to 220 gsm	
Stapling	Single Auto stapling: 50 sheets maximum: Letter / A4 / B5-size sheets (less than 90 gsm or (2) 220 gsm covers) 30 sheets maximum: Legal / Tabloid / A3 / B4-size sheets (less than 90 gsm or (2) 220 gsm covers)	
Office Finisher LX (Optional)		
Capacity ⁴	Stacking Tray: 2,000 sheets unstapled or 1,000 sheets single stapled or 750 sheets dual stapled (8.5 x 11 in. / A4) (dual stapling only with optional booklet maker)	
Sizes	8.3 x 7.2 in. to 11.7 x 17 in. / 210 x 182 mm to 297 x 432 mm	
Weights	16 lb. bond to 80 lb. cover / 60 to 220 gsm	
Multiposition Stapling	50 sheets of 24 lb. bond / 90 gsm	
Hole Punch (Optional) North America: Europe:	2-3 Hole Punch 2-4 Hole Punch	
Booklet Maker for Office Finisher LX (Score/Crease, Saddle-stitch Staple) (Optional)		
Capacity ⁴	40 booklets (2-15 sheets per booklet – 20 lb. / 80 gsm or less)	
Sizes	Letter – 8.5 x 11 in. / A4 SEF Legal – 8.5 x 14 in. / B4 SEF Ledger – 11 x 17 in. / A3 SEF	
Saddle-stitch Stapling	2-15 sheets / 8-60 page booklet 16 lb. bond to 24 lb. bond / 60 to 90 gsm	
Score / Crease	1-15 sheets / unstapled	
Convenience Stapler and Work Su	rface (Optional)	
Capacity ⁴	50-sheet stapling 5,000 staples Requires a separate outlet	

Device Management	
Network Protocols	TCP/IP: HTTP/HTTPS, Internet Printing Protocol, LPR/LPD, Raw Socket Printing/Port 9100, IPv4/IPv6, WSD LDAP Bonjour [®] / AirPrint™ FTP Most protocols not in use can be disabled
Administrative Protocols	DHCP, SNMP, WINS, HTTP, HTTPS, TLS, SNTP, MDNS
Xerox® CentreWare® Web	
	 A web-based server application for network administrators that permits web browser-based device management from any workstation, whether running Windows or UNIX or any other operating system Works with any SNMP-managed printer from any manufacturer Provides help with device discovery and installations, health checks and troubleshooting, and device upgrades, as well as basic accounting and asset management
Embedded Web Server – Integr	ated Device Web Page
Device Status	 Tray Status / Contents Consumables Status Billing / Usage Quick Links Online Support
Print Queue Viewing	Job print queue management — view and delete
Job Submission	Print-ready files (PS (with optional PostScript option), PCL, PDF, XPS, JPEG)
Device Administration	Allows simple, remote installation setting of configuration options and management of the device
Browsers	Microsoft [®] Internet Explorer [®] Microsoft Edge [™] Mozilla [™] Firefox [®] Apple [®] Safari [®] Google Chrome [™]
Remote Services	
Xerox® Automatic Meter Readings (AMR)	Automates the process of collecting and submitting meter reads for tracking and billing of Xerox [®] device usage. Eliminates the need for time-consuming end-user involvement and ensures that meter reads are submitted to Xerox on time.
Xerox [®] Automatic Supplies Replenishment (ASR)	Automatically orders supplies for Xerox [®] output devices based on actual usage, eliminating the need to manually manage supplies inventory.

Supplies and Accessories	Quantity	Part Number
Supplies		
High Capacity Print Cartridges	Cyan: 9,800 standard pages ⁶ Magenta: 9,800 standard pages ⁶ Yellow: 9,800 standard pages ⁶ Black: 16,100 standard pages ⁶	106R03744 106R03743 106R03742 106R03741
Extra High Capacity Print Cartridges	Cyan: 16,500 standard pages ⁶ Magenta: 16,500 standard pages ⁶ Yellow: 16,500 standard pages ⁶ Black: 23,600 standard pages ⁶	106R03740 106R03739 106R03738 106R03737
Metered Print Cartridges	Cyan: 15,000 standard pages ⁷ Magenta: 15,000 standard pages ⁷ Yellow: 15,000 standard pages ⁷ Black: 22,000 standard pages ⁷	106R03736 106R03735 106R03734 106R03733
Drum Cartridge	Black: 109,000 ⁸ Cyan, Magenta, Yellow: 87,000 standard pages ⁸	113R00780
Waste Toner Bottle	30,000	115R00128
LX Booklet Maker Cartridge (8 cartridges per container)	16,000 staples (2,000 each cartridge)	008R12897
Staple Refills for Finishers (3 refills per container)	15,000 staples (5,000 each refill)	008R12941
Staple Cartridge for Finishers (1 cartridge per container)	5,000 staples (5,000 each cartridge)	008R12964

Accessories / Options	
Single Tray Module (does not include Stand – for Desktop Model only)	097S04910
Single Tray with Stand Module	097S04907
Three Tray Module	097504908
High Capacity Tandem Tray Module	097S04909
Envelope Tray (Replaces Tray 1)	497K17720
Center Output Tray (Dual Catch Tray) (Optional on Desktop Model)	497K17800
HDD (320 GB hard drive) (Optional on Desktop Model)	497K17740
1 Line Fax Kit (PSTN Fax)	497K17750
3 Line Fax Kit (PSTN Fax)	497K17760
Wireless Network Adapter Kit	497K16750
Internal Card Reader / RFID Kit	497K18120
PostScript Kit	497K18340
Fax Over IP Kit	497K18330

¹ Maximum volume capacity expected in any one month. Not expected to be sustained on a regular basis.

- ¹ Maximum volume capacity expected in any one month. Not expected to be sustained on a regular basis.
 ² Expected regular monthly throughput.
 ³ Requires analog phone line.
 ⁴ Paper capacities are based on 20 lb. / 75 gsm stock; capacities will vary with different weight stocks.
 ⁵ Power states defined per ENERGY STAR® Program requirements for Imaging Equipment.
 ⁶ Average standard pages. Declared Yield in accordance with ISO/IEC 19798. Yield will vary based on image, area coverage and print mode.
 ⁷ Assumptions: Toner cartridge yield is based on 5 % area coverage on 8.5 x 11 in. / A4 LEF. Toner yield can vary due to many factors, including but not limited to, image area coverage, image content, media size, run mode, application types, monthly print volumes and image quality set-points.
 ⁸ Approximate angres. Declared vield will vary description.
- 8 Approximate pages. Declared yield will vary depending on job run length, media size/orientation and machine speed. For more information visit: https://www.office.xerox.com/Latest/SUPGL-01.pdf.

Return spent imaging supplies through the Xerox Green World Alliance collection/reuse/recycling program. For more information, visit www.xerox.com/About-Xerox/Recycling.

For more information, visit us at www.xerox.com/Office.

Configurations vary by geography.



©2019 Xerox Corporation. All rights reserved. Xerox®, Xerox and Design®, CentreWare®, ConnectKey®, Global Print Driver®, Mobile Express Driver® and VersaLink® are trademarks of Xerox Corporation in the United States and/or other countries. The information in this brochure is subject to change without notice. 1/19 PN03335_T63 VC7SS-01UD