

Packaging

ROTARY & RECIPROCATING PILLOW UNIT

RECIP MACHINES

PRODUCT CODE

BM-PRP-1302 series

MAIN PERFORMANCE AND STRUCTURE FEATURES

1. Double transducer control, flexible bag length cutting, operator needn't to adjust the unloading working, saving time and saving films.
2. human-machine operation, convenient and quick parameter setting.
3. Self diagnosis failure function, clear failure display.
4. High sensitivity optical electric color mark tracking AND digital input cut position which makes the sealing and cutting more accurate.
5. Separate PID control to temperature, suitable for various packing materials.
6. Stopping the machine in selected position, no sticking to the knife and no waste packing film.
7. Simple driving system, reliable working, convenient maintenance.
8. All the controls are achieved by software, convenient for function adjusting and upgrading.

APPLICATION

Suitable for packing of bread, buns, biscuits & cake products.



CODE	FILM width(mm)	BAG length(mm)	BAG width(mm)	PRODUCT high (mm)	FILM ROLL diam(mm)	PACKAGING RATE (bag/min)	POWER	MACHINE size(mm)	MACHINE weight(kg)
BM-PRP-1302-350 Reciprocating pillow packing machine	Max.350	110-330	30-130	10-60	Max.320	30-120	220V50/60Hz 2.4Kw	3670x820x 1410	800
BM-PRP-1302-450 Reciprocating pillow packing machine	Max.450	120-450	50-160	10-80	Max.320	20-80	220V50/60Hz 3,2Kw	4380x870x 1500	960
BM-PRP-1302-600 Reciprocating pillow packing machine	Max.600	120-450	50-200	10-80	Max.320	20-80	220V50/60Hz 3,2Kw	4380x970x 1500	1160