

ROTARY & RECIPROCATING PILLOW UNIT

ROT MACHINES

PRODUCT CODE

BM-PRP-1301-350X

MAIN PERFORMANCE AND STRUCTURE FEATURES

1. Double transducer control, flexible bag length cutting, operator needn't to adjust the unloading working, saving time and saving films.
2. Human-machine operation, convenient and quick parameter setting.
3. Self diagnosis failure function, clear failure display.
4. High sensitivity optical electric color mark tracking, digital input cut position which makes the sealing and cutting more accurate.
5. Separate PID control to temperature, suitable for various packing materials.
6. Stopping the machine in selected position, no sticking to the knife and no waste packing film.
7. Simple driving system, reliable working, convenient maintenance.
8. All the controls are achieved by software, convenient for function adjusting and upgrading.

APPLICATION

Suitable for packing of bread, buns, biscuits & cake products.

OPTIONAL DEVICE

1. Code applying machine.
2. line sealing wheel.
3. Moire terminal sealing mould.
4. Extra big screen.

Code	BM-PRP-1301-350X
Film Width	Max.350mm
Bag Length	65-190mm or 120-280mm
Bag Width	50-160mm
Product Height	Max.45mm
Film roll diameter	Max.320mm
Packing Speed	40-230 pack/minute
Power Supply	D220V 50/60 Hz 2.8 KVA
Machine Size	(l)4020x(w)720x(h)1320
Machine WeightT	800 Kg

