

Packaging

ROTARY & RECIPROCATING PILLOW UNIT PRODUCT CODE

BM-PRP-1301-250

MAIN PERFORMANCE AND STRUCTURE FEATURES

1. Double transducer control, flexible bag length cutting, operator needn't to adjust the unloading working, saving time and saving films.
2. human-machine operation, convenient and quick parameter setting.
3. Self diagnosis failure function, clear failure display.
4. High sensitivity optical electric color mark tracking digital input cut position which makes the sealing and cutting more accurate.
5. Separate PID control to temperature, suitable for various packing materials.
6. Stopping the machine in selected position, no sticking to the knife and no waste packing film.
7. Simple driving system, reliable working, convenient maintenance.
8. All the controls are achieved by software, convenient for function adjusting and upgrading.



APPLICATION

Suitable for packing of bread, buns, biscuits & cake products.

OPTIONAL DEVICE

1. Code applying machine.
2. line sealing wheel.
3. Moire terminal sealing mould.
4. Extra big screen.

CODE	BM-PRP-1301-250B	BM-PRP-1301-250D	BM-PRP-1301-250S
Film Width	Max.250mm		Max 180mm
Bag Length	65-190mm Or 120-280mm	90-220mm	45-90mm
Bag Width	30-110mm		30-80mm
Product Height	Max40mm	Max.60mm	Max.35mm
Film Roll Diameter	Max.320mm		
Packing Speed	40-230 pack/minute		-60-330bag/min
Power Supply	220V50/60Hz 2.4KVA		
Size	(l)3770x(w)670(h)1450		
Weight	800Kg		
Note	fill gas		