

## ROTARY & RECIPROCATING PILLOW UNIT

### PRODUCT CODE

#### BM-PRP-1301-320

#### MAIN PERFORMANCE AND STRUCTURE FEATURES

1. Dual frequency conversion control, Bag length can be set and cut in one step, saving time and film.
2. Interface features easy and quick setting and operation.
3. Self failure diagnosis, clear failure display.
4. High sensitivity photoelectric eye color tracing, numerical input of cutting/sealing position for extra accuracy.
5. Temperature independent PID control, more suitable for packaging different materials.
6. Positioned stop function, without sticking knife or wasting film.
7. Simple driving system, reliable working, convenient maintenance.
8. All control is realized through software, easy for function adjusting and technical upgrade.

#### APPLICATION

Suitable for packing of bread, buns, biscuits & cake products.

CODE	BM-PRP-1301-320B	BM-PRP-1301-320D
Film Width	Max.350mm	
Bag Length	65-190mm Or 120-280mm	90-220mm 150-330mm
Bag Width	50-160mm	
Product Height	Max45mm	Max.60mm
Film Roll Diameter	Max.320mm	
Packaging Rate	40-230 bag/min	
Power Supply	220V50/60Hz 2.4KVA	
Machine Size	(l)3770x(w)720(h)1450	
Machine Quality	850Kg	
Remarks	Optional Air Filling Device	

