

**Section 1-Chemical Product and Company Identification**

**Company Information:**

PremierRepak Inc.  
8351 W. 185<sup>th</sup> Street  
Tinley Park, IL 60487  
www.premierrepak.com

Phone: (708) 444-2688  
Fax: (708) 429-4280

**InfoTrac** 24-hour Emergency Phone Number: 1 (800) 535-5053

**InfoTrac** Contract Number: 105384

**Product Information:**

**Product:** O-ring Lubricant  
**C.A.S. Number:** Not Applicable  
**Recommended use:** Lubricant (Not for medical purposes)

**Section 2-Hazard Identification**

**Classification:** Not hazardous

**Labeling:** Symbol: None

Signal Word: None

Hazard statements: Not Hazardous

**Precautionary Statements:**

Use personal protective equipment as required. Wear safety glasses and gloves. Avoid contact with eyes.  
Non-flammable or combustible, but may burn if involved in a fire.

**Section 3-Composition and Information on Ingredients**

**Hazardous Ingredients:**

<b>Chemical Name</b>	<b>C.A.S. No.</b>	<b>Wt. %</b>	<b>Impurities</b>
Dimethyl Siloxanes and Silicones (Methyl Silicon)	63148-62-9	40-60	No information provided by manufacturer
Lithium Stearate	4485-12-5	20-40	Lithium Palmitate
Di-2-ethylhexyl sebacate	122-62-3	10-20	No information provided by manufacturer

**Section 4 – First Aid Measures**

**Eye Contact:** Flush eyes with large amounts of water. If signs/symptoms persist, get medical attention.

**Skin Contact:** Wash affected area with soap and water. If signs/symptoms persist, get medical attention. No need for first aid is anticipated.

**Inhalation:** If signs/symptoms develop, remove person to fresh air. If signs/symptoms persist, get medical attention.

**Ingestion:** If swallowed, do not induce vomiting. If irritation or discomfort occurs, obtain medical assistance.

**Section 5- Firefighting Measures**

**Autoignition Temperature:** >300°C

**Flash point:** >300°C

**Flammable Limits (LEL):** Not determined

**Flammable Limits (UEL):** Not determined

**Suitable Extinguishing Media:** On large fires used dry chemical, foam, or water spray. On small fires use carbon dioxide, dry chemical, or water spray. Water can be used to cool fire exposed containers.

**Unsuitable Extinguishing Media:** None.

**Specific hazards in case of fire:** Decomposes on heating and can release formaldehyde. Avoid reaction with oxidizers.

**Special protective equipment and precautions for fire fighters:**

No acute hazard. Move container from fire area, if possible. Avoid breathing vapors or dusts. Keep upwind. Use full firefighting gear (bunker gear). Any supplied-air respirator with full face piece and operated in a pressure-demand or other positive pressure mode in combination with a separate escape air supply. Use any self-contained breathing apparatus with a full face piece. Alert fire brigade and indicate hazard location. Wear breathing apparatus plus protective clothing. Cool fire exposed containers with water spray from a protected location. Do not approach containers suspected to be hot. If safe to do so, remove containers from path of fire.

**Section 6 – Accidental Release Measures**

**Personal precautions:** Use appropriate personal protection. (See SECTION 8)

**Environmental precautions:**

For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water. Collect the resulting residue containing solution. Place in a metal container approved for transportation by appropriate authorities. Dispose of collected material as soon as possible.

**Methods for material containment and cleaning up:**

Observe precautions from other sections. Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Collect as much of the spilled material as possible. Clean up residue with an appropriate solvent. Seal the container.

### **Section 7 – Handling and Storage**

**Precautions for safe handling:**

Avoid contact with skin, inhalation of mist, or ingestion. See section 8 for personal protection equipment. Practice good personal hygiene to prevent accidental ingestion after handling. Properly dispose of clothing that cannot be decontaminated.

**Conditions for safe storage, including any incompatibilities:**

Store away from oxidizing materials. Store product in a closed container located in a dry area. Do not store in open, inadequate, or mislabeled packaging. Check that containers are clearly labeled. Use metal cans, metal drums, plastic, or lined fiber containers. Keep away from heat and flame.

### **Section 8- Exposure Controls and Personal Protection**

**Control Parameters:** Under most handling conditions, this product will not generate mist or dust.

**Engineering Controls:** In most conditions, no special local ventilation is needed. General ventilation recommended. If the product is heated above 150°C or atomized ventilation should be used.

**Personal Protective Equipment (PPE):**

**Eyes:** Safety glasses recommended.

**Skin:** Impermeable gloves should be worn. Product is compatible with most elastomers.

**Inhalation:** No respiratory protection required under most conditions. If concentrations exceed exposure limits, approved respiratory equipment must be used.

### **Section 9- Physical/Chemical Characteristics**

**Physical state:** Solid. Liquid may separate from product.

**Color:** Off-white

**Odor:** Mild

**Odor Threshold:** Not available

**pH Value:** Not applicable

**Melting Point:** 210°C

**Freezing Point:** Becomes very stiff with decreasing temperature around -60°C

**Flash Point:** >300°C COC (Base oil)

**Initial Boiling Point:** >200°C

**Flammability (solid, gas):** Not applicable

**Evaporation rate:** Not available

**Explosion limits:** Not available

**Vapor pressure:** Negligible at 20°C

**Vapor density:** Not available

**Solubility:** Insoluble in water at 20°C

**Partition coefficient:** Not available

**Auto-ignition temperature:** Not available

**Decomposition temperature:** Begins to oxidize at 150°C. Decomposes at 250°C.

### **Section 10- Stability and Reactivity**

**Chemical stability:** Stable under ambient temperatures and pressures

**Possibility of hazardous reactions:** May react with air under very high pressure. Otherwise will not react or polymerize.

**Conditions to avoid:** No specific conditions to avoid have been identified.

**Materials to avoid:** Oxidizers

**Hazardous decomposition products:** Decomposes on heating and produces formaldehyde, silicone dioxide, and incompletely burned carbon compounds.

### **Section 11– Toxicological Information**

**Acute Toxicity:**

Methyl silicone	LD50 (rat) > 10,000 mg/kg
Lithium stearate	LD50 (rat) > 2,000 mg/kg
Di-2-ethylhexyl sebacate	LD50 > 9,5000 mg/kg

**Skin Corrosion/Irritation:** Not irritating/not corrosive to the skin.

**Serious Eye Damage/Irritation:** Possible irritant / not corrosive to the eyes.

**Respiratory/Skin sensitization:** Not sensitizing to the skin.

**Germ-cell Mutagenicity:** Not a germ-cell mutagen.

**Carcinogenicity:** Not a carcinogen.

**Reproductive Toxicity:** There are currently no reliable scientific data available indicating adverse effects on reproduction or fertility.

**Aspiration Hazard:** Not applicable (not an aerosol/mist).

### **Section 12 – Ecological Information**

**Toxicity:** No data available.

**Persistence and degradability:** In soil, siloxanes are degraded.

**Bioaccumulative potential:** Not expected to bioaccumulate.

**Mobility in soil:** Siloxanes are removed from water by sedimentation or binding to sewage sludge. Lithium stearate is not mobile.

### **Section 13 – Disposal Considerations**

**Waste treatment methods:** Waste (substance and container material) shall be recycled/recovered or disposed of as applicable and in accordance with community (EU) and local legislation. Recycle wherever possible. Consult state land waste management authority for disposal. Bury at an approved site. Recycle containers if possible, or dispose of in an authorized landfill.

**According to the European Waste Catalogue:** Waste Codes are not product specific but application specific. Waste Codes should be assigned by the user based on the application in which the product is used.

**For USA Disposal:** Waste must be disposed of in accordance with federal, state, and local environmental control regulations

**Section 14 – Transport Information**

Class or Type: US DOT, IMO, ADR, RID, ADN, IMDG, and IATA: Non-hazardous

**Section 15- Hazard Classification**

Safety, health and environmental regulations/legislation specific for the mixture:

Other Information:

U. S. Regulatory information:

TSCA Inventory Status: All ingredients listed or exempt  
TSCA 12 (b) Export Notification: Not listed  
CERCLA Section 103 (40 CFR 302.4): N  
SARA Section 302 (40 CFR 355.30): N  
SARA Section 304 (40 CFR 355.40): N  
SARA Section 313 (40 CFR 372.65): N  
OSHA Process Safety (29 CFR 1910.119): N

SARA Hazard Categories, SARA Sections 311/312 (40 CFR 370.21) –  
Acute Hazard: N  
Chronic Hazard: N  
Fire Hazard: N  
Reactivity Hazard: N  
Sudden Release Hazard: N

**State Regulations:** Not on California Proposition 65 list. Does not contain any contaminants or by-products known to the State of California to cause cancer or reproductive toxicity.

**Note:** There are no known safety, health or environmental restrictions or prohibitions in any country where this product is produced, imported or marketed.

Chemical Inventories:

DSL (Canada): All ingredients listed or exempt  
EINECS (European Union): All ingredients listed or exempt  
ENCS/ISHL (Japan): All ingredients listed or exempt  
IECSC (Peoples Republic of China): All ingredients listed or exempt  
TSCA (United States of America): All ingredients listed or exempt

**Section 16 – Other Information**

NFPA Hazard Classification:

Health: 1      Flammability: 1      Reactivity: 0      Special Hazards: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency personnel to address the hazards that are presented by short-term, acute exposure to material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

**PR5504**  
**Medium Consistency Silicone**  
**Valve and O-Ring Lubricant**  
**Safety Data Sheet**

**HMIS Hazard Classification:**

**Health: 1      Flammability: 1      Reactivity: 0      Protection: B (See PPE section)**

Hazardous Material Identification System (HMIS) hazard ratings are designed to inform employees of chemical hazards in the workplace. The ratings are based on inherent properties of the material under expected conditions of normal use and are not intended for use in emergency situations.

**Prepared by:**

PremierRepak, Inc.  
<http://premierrepak.com/>

These data are offered in good faith as typical values and not as product specifications. No warranty, either expressed or implied, is hereby made. The recommended industrial hygiene and safe handling procedures are believed to be generally applicable. However, each user should review these recommendations in the specific context of the intended use and determine whether they are appropriate. The information on this material safety data sheet represents our current data and best opinion as to the proper use in handling of this product under normal conditions. Any use of the product which is not in conformance with this data sheet or which involves using the product in combination with any other product or any other process is the user's responsibility. PremierRepak specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of PremierRepak products.