

Sensor

Weight	½ lb (8 oz)
Power supply	9V battery lithium
Range	up-to 1 mile away (line of site)



Installation Steps:

- 1 Connect the sensor to the instrument being monitored.
- 2 Make sure the sensor and instrument are within a 1 mile line of site range of the collector (in commercial and industrial settings range may be closer). Reading delivery will start within 24 hours.
- 2a If you would like readings to come in within 1 hour, open the unit up with a t-10 screwdriver. Remove the 9v battery from the sensor for 30 seconds and re-install. Close up the sensor enclosure.
- 3 If you have issues with readings coming into the dashboard, or if you want to ensure the units are within range of each other, please follow the “Range Check” guide.
- 4 Contact VMG for your new account site setup and to be able to login to view your readings.

You will need to provide us with:

- Sensor ID number (on the back label of the sensor starting with the letter N)
- Tank size
- Instrument type
- Product being monitored

We can create as many user logins as you like with different access levels and provide any other training needed.

Vendor Managed Gas™

The First Affordable
Cylinder Gas Telemetry System

VMG.us.com

Cyndi Blalock

Chief Development Officer

Cell: (513) 478-9105

Cyndi@VMG.us.com

Mike Ahrens

Technical Lead

Office: (513) 936-5910 ext 103

Cell: (513) 346-0918

Mikey@VMG.us.com