

# Puller



The CM Puller is designed for heavy-duty construction and industrial applications. Used to pull, lift, drag or stretch, it features:


- Tough aluminum alloy construction and powder coat finish
- Weatherproof for outdoor service
- Simple construction with fewer parts for ease of maintenance and lower inventories
- Hoistaloy hardened steel link type load chain for strength, long wear life and flexibility
- Weatherized Weston-type automatic braking system for positive load control
- Easy, one-hand operation and control — only 58 pounds of pull required for 3/4 ton model capacity
- Forged upper and lower hooks with latches standard
- Free wheeling for fast and easy attachment to load
- Upper and lower Latchlok hooks available for all capacities
- Optional Load Limiter protection device stops transmission of lever forces protecting against dangerous overload
- Optional anchor sling simplifies attachment to allow anchor hook to swivel in tight space applications (3/4 & 1 1/2 ton units only)
- Optional Load Sentry warns of overload condition
- Optional zinc-plated chain available
- Unlimited lift
- Lifetime warranty
- Metric rated
- Made in U.S.A.



**Optional Load Limiter**



**Optional anchor sling (3/4 and 1 1/2 ton)**



**Latchlok type hook**



**3/4 ton**

## Puller specifications - standard unit

Rated capacity* (tons)	Product code	Standard lift† (ft.)	Pull to lift full loads (lbs.)	Minimum distance between hooks (in.)	Lever length (in.)	Reeving	Hook throat openings (in.)	Approx. shipping weight (lbs.)
3/4	4043	5	58	10 3/4	21 1/4	1	1 1/32	16
1 1/2	4045	5	89	14 1/4	21 1/4	1	1 1/8	26
3	4047	5	95	16 15/16	21 1/4	2	1 7/32	38
6	4050	5	96	21 3/8	21 1/4	4	1 3/4	73

† Can be supplied with lifts longer than 5 feet

## Optional kits

Rated capacity* (tons)	Load Limiter		Load Sentry kit			Anchor sling kit	
	Product code	Approx. shipping weight (lbs.)	Product code	Lever length (in.)	Approx. shipping weight (lbs.)	Product code	Approx. shipping weight (lbs.)
3/4	4190	8 1/4	4096	23 3/4	4 1/2	4071	2
1 1/2	4191	8 1/4	4098	23 3/4	4 1/2	4072	4 3/4
3	4191	8 1/4	4098	23 3/4	4 1/2	—	—
6	4191	8 1/4	4098	23 3/4	4 1/2	—	—