

MS6/MS7 - 36 sqm

Mobile LED Screen



Safety

All our Mobile LED Screens

- are built and approved according to TÜV regulations
- have all required construction books/"Baubücher"
- are approved to be used up to wind speeds of 20 m/s or 72 km/h
- have multiple safety lock systems for the hydraulic system
- are equipped with dual video processors linked in a redundant system

Add ons

Please contact us for further information about Digital Banners, Info Channels etc.

Technical Specifications

Technical Specifications	
Screen	
Display size	36 m ²
Display dimensions:	W: 8000 H: 4500 mm
Display resolution:	W: 1280 H: 720 px
Picture format:	16:9
Pixel pitch:	6,25 mm
Brightness:	5000 nits
Viewing angle:	H: 80° V: 60°
Screen rotation:	360°
Min. rotation space from trailer body (each side):	2000 mm
Input signals:	CVBS, 3G-SDI, DVI, HDMI, VGA
Trailer	
Trailer dimensions:	L: 11082 W: 2550 H: 4000 mm
Ground space outriggers when rigged:	L: 6670 W: 2750 mm
Trim height:	4000 - 4420 mm
Weight:	22000 kg
Built in studio:	No
Built in generator:	Yes, 75 kVA
Running time generator:	90 h (11L hour / 1000L tank)
External power connector:	32 A / 63 A, 3 phase, 400V, CEE
Power consumption (max):	24,6 A
Truck & Trailer	
Length, total:	14600 mm
Weight, total:	29500 kg