

# Create LED AirMAG 3

## Modular LED Screen



- High-definition real 3,9 mm pixel pitch black SMD-LED
- Black mask delivers fantastic high contrast and black levels
- More vivid image, more impressive performance
- Ultra slim, lightweight and completely silent (fanless)

### Technical Specifications

Type:	Indoor black body SMD display
LED type:	SMD 3 in 1, 1R1G1B
Cabinet area:	0.25 m <sup>2</sup>
Screen dimensions, W x H x D:	500 x 500 x 65 mm
Pixel pitch:	3,9 mm
Cabinet resolution:	128 x 128 dots
Physical density:	65,536 pixels/ m <sup>2</sup>
Panel configuration:	1:1
Brightness:	1,200 nits
Weight:	7 kg / panel
Viewing angle, Horizontal:	140 degrees
Viewing angle, Vertical:	120 degrees
Colors:	281 trillion
Lifetime:	100,000 hours (50% brightness)
Power supply:	AC 110V - 380V ± 10%
Power consumption (max):	120 W/ display panel
Typical power consumption:	66 W/ display panel
Display gradations/colours:	16 bits
Refresh rate:	600-3000 Hz
Input signals:	DVI
Signal connection:	CAT5E
Processor:	CX-Pro-603
Certification:	CE class A (TUV), ETL
Ingress protection:	Front and back

