

INFECTION CONTROL

MEDIGENIC WIRELESS INFECTION-CONTROL KEYBOARD AND MOUSE

The Wireless model is designed for cordless operation in Dental applications or anywhere a keyboard is used on a moving arm or tray. There are no wires to tangle or interfere with the movement of the tray, and the compact size fits in any space. The Medigenic Wireless features the same flat, silicone surface as the rest of the product line, ensuring rapid and effective disinfection in just ten seconds. Below this surface resides a high-quality scissor style keyboard with excellent tactile feedback, enabling comfortable typing and efficient data entry.

WIRELESS KEYBOARD HIGHLIGHTS



Cost-Effective



Sanitize in Seconds



Easy to Move



High-Speed Data Entry Capability



Hypo-Allergenic



MEDIⁱGENIC



HEALTHCARE

Contact us to request a **free trial** of the Medigenic Wireless Keyboard and Mouse today.



SPECIFICATIONS

MEDI ⁱ GENIC WIRELESS KEYBOARD (K080WB1-US)	WIRELESS MOUSE (WMB)
SIZE / WEIGHT / COLOR	
<ul style="list-style-type: none"> * Keyboard Length: 12.6" (320 mm) * Keyboard Width: 7.0" (179 mm) * Keyboard Depth/Height (at rear minimum): .75" (19 mm) * Keyboard Weight: 1.67 lbs (760 g) * Keyboard Color: light blue * Battery Life: 2 AA Batteries, 3 months 	<ul style="list-style-type: none"> 4.5" (113 mm) 2.7" (67 mm) 1.5" (37 mm) .23 lbs (106 g) light blue or light gray 1 AA Batteries, 3 months
INTERFACES	
<ul style="list-style-type: none"> * Wireless: 2.4 GHz ISM * Protocol: Standard HID 	<ul style="list-style-type: none"> Wireless: 2.4 GHz ISM Protocol: Standard HID
KEYBOARD OPERATING SYSTEMS	
<ul style="list-style-type: none"> * Microsoft Windows®, Linux®, and Mac® * USB port for dongle 	<ul style="list-style-type: none"> (same as wireless kb) (same as wireless kb)
MECHANICAL	
<ul style="list-style-type: none"> * QWERTY Key Life: 10,000,000 actuations per key * Function Key Life: 5,000,000 actuations per key 	<ul style="list-style-type: none"> 1,000,000 actuations (same as wireless kb)
ENVIRONMENTAL	
<ul style="list-style-type: none"> * Storage Temperature & Humidity -40° F (-40° C) to 140° F (60° C) at 5% to 65% relative humidity (non-condensing) * Operating Temperature & Humidity 32° F (0° C) to 104° F (40° C) at 5% to 80% relative humidity (non-condensing) * Environmental Sealing Compliance: IP54 	<ul style="list-style-type: none"> (same as wireless kb) (same as wireless kb) (same as wireless kb)

