

## INFECTION CONTROL

### MEDIGENIC COMPLIANCE INFECTION-CONTROL KEYBOARD

The Medigenic Compliance Infection Control Keyboard uniquely helps monitor its own cleaning status to safeguard both patients and staff with user defined, time-based cleaning alerts. Clinical studies show that this system improves compliance to cleaning protocols from 27% to 87%. Featuring a flat, flexible silicon surface, the Medigenic keyboard can be disinfected effectively in just ten seconds without having to unplug it. In addition, a high-quality scissor style keyboard under the surface enables comfortable and efficient typing, with backlighting for low light operation.

### COMPLIANCE KEYBOARD HIGHLIGHTS



Sanitize in Seconds



Medigenic Alert System Indicator will flash



High-Speed Data Entry Capability



Back lit Keys Keyboard is usable in low-light environments



Disinfection without disconnection



#### CART SIZE (101/102 KEY)



#### FULL SIZE (104/105 KEY)





Contact us to request a **free trial** of the Medigenic Compliance Keyboard today.



## SPECIFICATIONS

MEDI <i>G</i> ENIC COMPLIANCE KEYBOARD	CART SIZE (K101C02-US)	FULL SIZE (K104C02-US)
<b>SIZE / WEIGHT / COLOR</b>	<b>101/102 KEY</b>	<b>104/105 KEY</b>
✦ Keyboard Length:	15.24" (387 mm)	18.2" (462 mm)
✦ Keyboard Width:	6.5" (165 mm)	6.7" (170 mm)
✦ Keyboard Depth/Height (at rear minimum):	0.77" (19.5 mm)	1.4" (34 mm)
✦ Keyboard Weight:	1.9 lbs (0.86 kg)	2.5 lbs (1.2 kg)
✦ Keyboard Color:	light blue	light blue
✦ Cable Length:	6 ft. (2 m)	6 ft. (2 m)
<b>INTERFACES</b>		
✦ USB, HID	high or low current	high current port
<b>KEYBOARD LAYOUT AND LANGUAGE SET AVAILABILITY</b>		
✦ Multiple Languages	101/102 key	104/105 key
<b>INTEGRATED KEYBOARD BACKLIGHTING</b>		
✦ Controllable via keyboard command		
<b>MECHANICAL</b>		
✦ QWERTY Key Life: 10,000,000 actuations per key		
✦ Function Key Life: 5,000,000 actuations per key		
<b>ENVIRONMENTAL</b>		
✦ Storage Temperature & Humidity -40° F (-40° C) to 140° F (60° C) at 5% to 65% relative humidity (non-condensing)		
✦ Operating Temperature & Humidity 32° F (0° C) to 104° F (40° C) at 5% to 80% relative humidity (non-condensing)		
✦ Environmental Sealing Compliance: IP67		

