

# STOUT

# >> HIGHLIGHTS

- + Mid-back suspension seat
- + Kawasaki Premium FR Engine 3 yr. warranty
- + 1-1/2" x 3" steel tubular frame rails
- + 10 ga. fabricated deck
- + 13" caster tires and 22" drive tires
- + Tool-less removable pulley covers
- + Flip-up seat pan
- + Removable floor pan





#### bigdogmowerco.com/stout

Visit your BigDog dealer for details.

Specifications subject to change without notice.



# >> SPECIFICATIONS

#### **DECKS**

**CUTTING WIDTH** 48" 54" 60" **CUTTING HEIGHT** 1.5" to 4.5" **DECK LIFT** Foot Operated **DEPTH BLADES** 48" Deck: 3 54" Deck: 3 60" Deck: 3 **BLADE LENGTH** 48" Deck: 16.5" 54" Deck: 18.5" 60" Deck: 20.5" **SPINDLES** Aluminum casting with steel shafts and sealed ball bearings **DRIVE** V-belt drive to spindles with electric clutch 10 ga. fabricated CONSTRUCTION SPINDLE MOUNTS Reinforced 11 ga. **IMPACT/TRIM AREAS** Solid 1" x .375" steel bar

#### **DIMENSIONS**

| DECK SIZE                                  | 48"      | 54"      | 60"      |
|--|----------|----------|----------|
| HEIGHT                                     | 45.5"    | 45.5"    | 45.5"    |
| LENGTH                                     | 76"      | 76"      | 76"      |
| OVERALL WIDTH<br>(with discharge chute up) | 49.1"    | 55.1"    | 61.1"    |
| WEIGHT                                     | 862 lbs. | 891 lbs. | 916 lbs. |

#### **GENERAL**

**SEAT** Mid-back suspension seat

**FUEL CAPACITY** 5 gal. **CUP HOLDER** Yes

**FRONT TIRE** 48" Deck: 13 x 5 - 6, smooth tread

54" Deck: 13 x 6.5 – 6, smooth tread

60" Deck: 13 x 6.5 - 6, smooth tread

**DRIVE TIRE** 48" Deck: 22 X 9.5 – 10

54" Deck: 22 x 11 - 10

60" Deck: 22 x 11 - 10

#### **ENGINE**

MANUFACTURER Kawasaki

**HORSEPOWER** 48" Deck: FR691 – 23 hp

54" Deck: FR691 - 23 hp 60" Deck: FR730 - 24 hp

.. . . .

**COOLING** Air Cooled

**ENGINE WARRANTY** 3 yrs.

## **DRIVE SYSTEM**

TYPE Dual Hydrostatic
TRANSMISSION Hydro-Gear ZT3100

**SPEED** Up to 8 mph

PARKING BRAKES Patented Automatic

### CONSTRUCTION

FRAME 1.5" x 3" x 0.120" steel tubing

FRONT AXLE Fabricated with sealed ball bearings
FRONT CASTER WHEELS Heavy-duty ball bearing-greasable

FRONT CASTER FORKS Fabricated 3/8"