



2020 - FRP Tire Data

F1600									
3/17/20									
General Settings:			COLD	HOT					
FRONT	Camber	Toe	PSI	PSI					
	-3.0, +/- .5	1mm out, per side	16-17	19-20					
FRONT		SIZE	CIRCUMF.	OVERALL DIAMETER	TREAD WIDTH	SECTION WIDTH	MEASURED RIM	MEASURED PSI	TIRE WEIGHT
CATALOG #		DESIGNATION	(in.)	(in.)	(in.)	(in.)	(in.)		(lbs.)
43321	DRY	185/60R13 F1600	68.75	21.88	6.375"	7.688"	13X5.5	20	14.8
44421	WET	185/60R13 WET	68	21.65	6.5	7.55	13X5.5	20	15.8
VERTICAL DEFLECTION DATA:									
43321	DRY	Load(lbs)	16psi	20psi	24psi				
		250	1056	1228	1345				
		350	1090	1261	1382				
		450	1122	1287	1413				
General Settings:									
REAR	Camber	Toe	PSI	PSI					
	-2.0, +/- .5	1mm in , per side	16-17	19-20					
REAR		SIZE	CIRCUMF.	OVERALL DIAMETER	TREAD WIDTH	SECTION WIDTH	MEASURED RIM	MEASURED PSI	TIRE WEIGHT
CATALOG #		DESIGNATION	(in.)	(in.)	(in.)	(in.)	(in.)		(lbs.)
43326	DRY	205/60R13 F1600	71.44	22.74	8	8.69	13X5.5	20	17.6
44426	WET	205/60R13 WET	72.75	23.16	7.38	8.4	13x5.5	20	17.3
VERTICAL DEFLECTION DATA:									
43326	DRY	Load(lbs)	16psi	20psi	24psi				
		350	1021	1217	1382				
		450	1026	1223	1388				
		550	1032	1229	1392				



2020 - FRP Tire Data

F2000									
3/17/20									
General Settings:				COLD	HOT				
FRONT	Camber	Toe	PSI	PSI					
	-3.0, +/- .5	1mm out, per side	13-14	17-18					
				OVERALL	TREAD	SECTION	MEASURED	MEASURED	TIRE
FRONT		SIZE	CIRCUMF.	DIAMETER	WIDTH	WIDTH	RIM	PSI	WEIGHT
CATALOG #		DESIGNATION	(in.)	(in.)	(in.)	(in.)	(in.)		(lbs.)
43370	DRY	20.5X7.0R13 R35B	65.3	20.8	7.3	7.7	13X6	20	12
44442	WET	20.5X7.0R13 W3	65.3	20.8	7.4	7.5	13x6	20	14
VERTICAL DEFLECTION DATA									
43370		Load(lbs)	20psi						
	DRY	400	1180						
General Settings:									
REAR	Camber	Toe	PSI	PSI					
	-2.0, +/- .5	1mm in , per side	16-17	19-20					
				OVERALL	TREAD	SECTION	MEASURED	MEASURED	TIRE
REAR		SIZE	CIRCUMF.	DIAMETER	WIDTH	WIDTH	RIM	PSI	WEIGHT
CATALOG #		DESIGNATION	(in.)	(in.)	(in.)	(in.)	(in.)		(lbs.)
43380	DRY	22.5X8.0R13 R35B	70.31	22.38	8.38	9.56	13X8	20	14
44443	WET	22.5X8.0R13 WET	70.31	22.38	8.25	9	13X8	20	16
43380		Load(lbs)	20psi						
	DRY	550	1138						



2020 - FRP Tire Data

FA									
3/17/20									
General Settings:			COLD	HOT					
FRONT	Camber	Toe	PSI	PSI					
	-3.0, +/-	1mm out, per side	16-17	19-20					
				OVERALL	TREAD	SECTION	MEASURED	MEASURED	TIRE
FRONT		SIZE	CIRCUMF.	DIAMETER	WIDTH	WIDTH	RIM	PSI	WEIGHT
CATALOG #		DESIGNATION	(in.)	(in.)	(in.)	(in.)	(in.)		(lbs.)
43572	DRY	23.0x9.5R15 R35B	72	22.9	9.4	10.7	15x10	20	17
44511	WET	23.0x9.5R15 W3	72.31	23.02	9.38	10.68	15x10	20	16.2
VERTICAL DEFLECTION DATA									
43572		Load(lbs)	18psi	20psi	22psi				
	DRY	305	1172	1252	1297				
		465	1230	1318	1375				
		625	1250	1346	1412				
General Settings:									
REAR	Camber	Toe	PSI	PSI					
	-2.0, +/-	1mm in , per side	16-17	19-20					
				OVERALL	TREAD	SECTION	MEASURED	MEASURED	TIRE
REAR		SIZE	CIRCUMF.	DIAMETER	WIDTH	WIDTH	RIM	PSI	WEIGHT
CATALOG #		DESIGNATION	(in.)	(in.)	(in.)	(in.)	(in.)		(lbs.)
43587	DRY	24.5x13.75R15 R35B	77	24.5	13.75	14.5	15x14	20	23
44516	WET	24.5x13.75R15 W3	76.625	24.39	13.94	15.13	15x14	20	21.6
VERTICAL DEFLECTION DATA									
43587		Load(lbs)	18psi	20psi	22psi				
	DRY	405	1340	1449	1503				
		615	1379	1501	1583				
		825	1394	1520	1607				



2020 - FRP Tire Data

F1000									
3/17/20									
General Settings:			COLD	HOT					
FRONT	Camber	Toe	PSI	PSI					
	-1.0, +/- .5	1mm out, per side	13-14	17-18					
FRONT		SIZE	CIRCUMF.	OVERALL DIAMETER	TREAD WIDTH	SECTION WIDTH	MEASURED RIM	MEASURED PSI	TIRE WEIGHT
CATALOG #		DESIGNATION	(in.)	(in.)	(in.)	(in.)	(in.)		(lbs.)
43164	DRY	20.5X7.0-13 R25B	66.2	20.8	6.8	8	13X6	20	11
43164	DRY	20.5X7.0-13 R35B	66.2	20.8	6.8	8	13X6	20	11
44421	WET	21.0x6.5-13 W3	66.6	21.2	6.7	7.55	13x6	20	13.9
VERTICAL DEFLECTION DATA:									
43164	20.5x7.0-13	Load(lbs)	14psi	16psi	18psi				
	DRY	200	736 lbs/in	798 lbs/in					
		300	767 lbs/in	835 lbs/in					
		400	835 lbs/in	852 lbs/in					
General Settings:									
REAR	Camber	Toe	PSI	PSI					
	-0.5, +/- .5	1mm out, per side	14-15	18-19					
REAR		SIZE	CIRCUMF.	OVERALL DIAMETER	TREAD WIDTH	SECTION WIDTH	MEASURED RIM	MEASURED PSI	TIRE WEIGHT
CATALOG #		DESIGNATION	(in.)	(in.)	(in.)	(in.)	(in.)		(lbs.)
43285	DRY	22.0X8.0-13 R25B	69	22	8.5	9.9	13X8	20	11
43285	DRY	22.0X8.0-13 R35B	69	22	8.5	9.9	13X8	20	11
43290	DRY	22.0X9.0-13 R25B	69.5	22.1	8.8	10	13X8	20	13
43290	DRY	22.0X9.0-13 R35B	69.5	22.1	8.8	10	13X8	20	13
VERTICAL DEFLECTION DATA:									
43285	22.0x8.0-13	Load(lbs)	16psi	18psi	20psi				
	DRY	300	957 lbs/in	1014 lbs/in	1071 lbs/in				
		400	1004 lbs/in	1067 lbs/in	1129 lbs/in				
		500	1027 lbs/in	1104 lbs/in	1183 lbs/in				
43290	22.0x9.0-13	Load(lbs)	16psi	18psi	20psi				
	DRY	300	940 lbs/in	1007 lbs/in	1033 lbs/in				
		400	1033 lbs/in	1059 lbs/in	1128 lbs/in				
		500	1093 lbs/in	1139 lbs/in	1194 lbs/in				



2020 - FRP Tire Data

RCFF									
3/17/20									
FRONT			OVERALL	TREAD	SECTION	MEASURED	MEASURED	TIRE	
BIAS PLY	SIZE	CIRCUMF.	DIAMETER	WIDTH	WIDTH	RIM	PSI	WEIGHT	
CATALOG #	DESIGNATION	(in.)	(in.)	(in.)	(in.)	(in.)		(lbs.)	
43130	DRY	20.0x6.0-13 R60A	65	20.7	6	7	13X5.5	20	10
44421	WET	21.0x6.5-13 W3	65.9	21.2	6.5	7	13X5.5	20	11
General Settings:			COLD	HOT					
FRONT	Camber	Toe	PSI	PSI					
	-1.0, +/- .1mm out, per side		13-14	17-18					
VERTICAL DEFLECTION DATA:									
43130	DRY	Load(lbs)	14psi	16psi	18psi				
		200	930	940	973				
		300	995	1021	1048				
		400	1025	1058	1099				
REAR			OVERALL	TREAD	SECTION	MEASURED	MEASURED	TIRE	
BIAS PLY	SIZE	CIRCUMF.	DIAMETER	WIDTH	WIDTH	RIM	PSI	WEIGHT	
CATALOG #	DESIGNATION	(in.)	(in.)	(in.)	(in.)	(in.)		(lbs.)	
43307	DRY	22.5x7.2-13 R60A	71	22.6	7.25	9.8	13X5.5	20	16
44196	WET	22.0x8.0-13 W3	69	22	7.38	8.4	13x5.5	20	15
General Settings:			COLD	HOT					
REAR	Camber	Toe	PSI	PSI					
	-2.0, +/- .1mm in , per side		16-17	18-19					
VERTICAL DEFLECTION DATA:									
43307	DRY	Load(lbs)	16psi	18psi	20psi				
		200	890	897	927				
		300	976	1008	1022				
		400	1037	1072	1104				
REAR			OVERALL	TREAD	SECTION	MEASURED	MEASURED	TIRE	
RADIAL	SIZE	CIRCUMF.	DIAMETER	WIDTH	WIDTH	RIM	PSI	WEIGHT	
CATALOG #	DESIGNATION	(in.)	(in.)	(in.)	(in.)	(in.)		(lbs.)	
43326	DRY	205/60R13 F1600	71.44	22.74	8	8.69	13X5.5	20	17.6
44426	WET	205/60R13 WET	72.75	23.16	7.38	8.4	13x5.5	20	17.3
General Settings:			COLD	HOT					
REAR	Camber	Toe	PSI	PSI					
	-2.0, +/- .1mm in , per side		16-17	19-20					
VERTICAL DEFLECTION DATA:									
43326	DRY	Load(lbs)	16psi	20psi	24psi				
		350	1021	1217	1382				
		450	1026	1223	1388				
		550	1032	1229	1392	SECTION	MEASURED	MEASURED	TIRE
RADIAL	SIZE	CIRCUMF.	DIAMETER	WIDTH	WIDTH	RIM	PSI	WEIGHT	
CATALOG #	DESIGNATION	(in.)	(in.)	(in.)	(in.)	(in.)		(lbs.)	
43326	DRY	205/60R13 F1600	71.44	22.74	8	8.69	13X5.5	20	17.6
44426	WET	205/60R13 WET	72.75	23.16	7.38	8.4	13x5.5	20	17.3
General Settings:			COLD	HOT					
REAR	Camber	Toe	PSI	PSI					
	-2.0, +/- .1mm in , per side		16-17	19-20					
VERTICAL DEFLECTION DATA:									
43326	DRY	Load(lbs)	16psi	20psi	24psi				
		350	1021	1217	1382				
		450	1026	1223	1388				
		550	1032	1229	1392				