



## Fixed Jaw **SUPERCLAMP** Adjustable Girder Clamps

### Incorporating Adjusting Mechanism and Lifting Shackle.

These girder clamps are truly versatile in application and may be used for lifting, pulling, or as an anchor point. Designed specifically to provide maximum jaw grip adjustment.

These products are engineered for practical use where mobility is essential. The clamps are speedily applied and do not require additional tools or width adjusting components, such as spacing washers. The left and right-hand threaded adjusting bar ensures a secure grip on the beam flange.

Model	WLL	Adjust	Dimensions									Weight
			A	B	C	D	E	G	H	J	K	
<b>S1</b>	2032kg	76-190	125	3	22	90	188	275	20	77	250	4kg
<b>S2</b>	3048kg	76-190	125	6	22	90	188	275	20	77	250	5.1kg
<b>S2A</b>	3048kg	76-190	130	12.5	22	102	250	275	20	103	268	8kg
<b>S2AX</b>	3048kg	127-350	130	12.5	22	102	375	560	20	102	373	11.5kg
<b>S3</b>	4064kg	150-254	130	10	22	112	327	410	25	98	332	11kg
<b>S3A</b>	5080kg	150-305	140	12.5	32	116	373	410	25	110	360	15kg
<b>S3X</b>	5080kg	76-190	130	12.5	22	116	237	295	25	110	300	10kg
<b>S4</b>	7112kg	101-228	140	12.5	42	118	323	410	32	120	382	17.5kg
<b>S4A</b>	10160kg	203-457	140	20	42	118	498	560	32	112	476	28kg
<b>S4S</b>	6096kg	203-457	140	12.5	42	116	498	560	25	110	459	18.8kg
<b>S12</b>	15241kg	203-457	170	20	50	116.5	611	660	40	185	616	49.5kg
<b>S14</b>	15241kg	406-610	175	20	63	116.5	795	810	40	185	673	58.5kg

