




Green Pin® Self Locking Hook E EN 1677-3 GR8

Grade 8 eye self locking hook EN 1677-3

- **Material:** alloy steel, grade 8, quenched and tempered
- **Safety factor:** MBL equals 4 x WLL
- **Standard :** EN 1677-3
- **Finish:** painted yellow (J), red (R) or white
- **Temperature range:** -40°C up to +200°C
- **Certification:** 2.1 2.2 3.1 MPI[®] DGUV
- **Note:** from 12.8 t without flat part



XLO



for chain diameter		working load limit	length	diameter		width opening	thickness	width	width outside	width outside	length	width	thickness	weight each
mm	inch			a mm	b mm									
5 - 6	$\frac{3}{16}$ - $\frac{7}{32}$	1.12	111	24	32	16	26	47	77	147	11	7	0.51	
7 - 8	$\frac{1}{4}$ - $\frac{5}{16}$	2	134	29	43	23	29	57	92	176	14	7	0.91	
10	$\frac{3}{8}$	3.2	168	35	47	32	35	69	111	219	17	10	1.79	
13	$\frac{1}{2}$	5.4	199	46	61	37	45	87	142	264	20	13	3.36	
16	$\frac{5}{8}$	8.2	247	59	74	43	56	111	185	328	26	16	7	
18 - 20	$\frac{3}{4}$	12.8	282	69	88	51	63	126	207	374	28	20	9.22	




Green Pin® Self Locking Hook EN 1677-3 CL GR8

Grade 8 clevis self locking hook EN 1677-3

- **Material:** alloy steel, grade 8, quenched and tempered
- **Safety factor:** MBL equals 4 x WLL
- **Standard :** EN 1677-3
- **Finish:** painted yellow (J), red (R) or white
- **Temperature range:** -40°C up to +200°C
- **Certification:** 2.1 2.2 3.1 MPI[®] DGUV



XLC



for chain diameter		working load limit	length	width	width opening	thickness	width	width outside	width outside	length	diameter pin	weight each
mm	inch											
5	$\frac{3}{16}$	0.8	92	7	32	16	26	28	77	131	6	0.49
6	$\frac{7}{32}$	1.12	92	7	32	16	26	28	77	131	8	0.49
7-8	$\frac{1}{4}$ - $\frac{5}{16}$	2	116	9	43	23	29	32	92	161	9	0.91
10	$\frac{3}{8}$	3.2	143	12	47	32	35	42	111	200	13	1.77
13	$\frac{1}{2}$	5.4	167	15	61	37	45	54	142	242	16	3.33
16	$\frac{5}{8}$	8.2	201	19	74	43	56	68	185	293	20	6.75
18 - 20	$\frac{3}{4}$	12.8	232	23	88	51	63	82	207	341	24	9.57