




## Green Pin® Self Locking Hook E GR8

### Grade 8 eye self locking hook

- **Material:** alloy steel, grade 8, quenched and tempered
- **Safety factor:** MBL equals 4 x WLL
- **Finish:** painted yellow (J), red (R) or white
- **Temperature range:** -40°C up to +200°C
- **Certification:** 2.1 2.2 MPI<sup>3</sup>



GKO



for chain diameter		working load limit	length	diameter inside eye	width opening	thickness	width	width outside	width outside	length	width	thickness	weight each
mm	inch												
7 - 8	$\frac{1}{4} - \frac{5}{16}$	2	113	24	32	17	25	48	77	151	13	9	0.53
10	$\frac{3}{8}$	3.2	134	30	43	24	29	59	92	180	17	10	0.94
13	$\frac{1}{2}$	5.4	170	39	47	32	34	75	111	225	20	12	1.86
16	$\frac{5}{8}$	8.2	207	49	61	37	46	93	142	273	22	15	3.49
18 - 20	$\frac{3}{4}$	12.8	257	60	74	43	57	117	185	341	28	21	7.33
22	$\frac{7}{8}$	15.5	290	71	88	52	62	133	207	383	31	21	9.91




## Green Pin® Self Locking Hook CL GR8

### Grade 8 clevis self locking hook

- **Material:** alloy steel, grade 8, quenched and tempered
- **Safety factor:** MBL equals 4 x WLL
- **Finish:** painted yellow (J), red (R) or white
- **Temperature range:** -40°C up to +200°C
- **Certification:** 2.1 2.2 MPI<sup>3</sup>



GKC



for chain diameter		working load limit	length	width	width opening	thickness	width	width outside	width outside	length	diameter pin	weight each
mm	inch											
7 - 8	$\frac{1}{4} - \frac{5}{16}$	2	85	9	32	17	25	32	77	136	9	0.55
10	$\frac{3}{8}$	3.2	116	12	43	24	29	42	92	168	13	1.02
13	$\frac{1}{2}$	5.4	153	15	47	32	34	54	111	218	16	2.01
16	$\frac{5}{8}$	8.2	166	19	62	37	46	66	142	247	20	3.7
18 - 20	$\frac{3}{4}$	12.8	215	23	74	43	57	80	185	312	24	7.59
22	$\frac{7}{8}$	15.5	242	25	88	52	62	98	207	353	28	10.3