




Green Pin® Sling Hook E EN 1677-2 GR8

Grade 8 eye sling hook EN 1677-2



CSO



- **Material:** alloy steel, grade 8, quenched and tempered
- **Safety factor:** MBL equals 4 x WLL
- **Standard :** EN 1677-2
- **Finish:** painted yellow (J), red (R) or white
- **Temperature range:** -40°C up to +200°C
- **Certification:** 2.1 2.2 3.1 * MPI^b * DGUV *
- **Note:** from 8.2 t without flat part

for chain diameter		working load limit	length	diameter		width opening	thickness	width	diameter		length outside	width	thickness	weight each
mm	inch			inside eye	outside				eye outside	outside				
5-6	3/16 - 7/32	1.12	a	b	c	d	e	f	g	h	i	j		kg
7 - 8	1/4 - 5/16	2	84	23	26	15	20	43	72	114	10	6	0.28	
10	3/8	3.2	103	26	30	20	24	51	87	139	12	8	0.56	
13	1/2	5.4	128	35	33	24	29	65	106	172	15	10	1.09	
16	5/8	8.2	152	41	37	32	39	77	133	209	18	12	1.98	
18 - 20	3/4	12.8	190	52	44	40	44	94	165	255	21	16	3.55	
22	7/8	15.5	237	60	61	49	62	115	208	327	28	21	7.1	
26	1	21.6	280	72	75	54	65	132	242	375	30	23	9.9	
32	1 1/4	32.8	259	70	73	70	75	144	235	371	37	37	13.3	
			299	66	87	78	89	150	281	430	42	42	21.6	

* Excluding sizes 26 mm and 32 mm




Green Pin® Sling Hook CL EN 1677-2 GR8

Grade 8 clevis sling hook EN 1677-2



CSC



- **Material:** alloy steel, grade 8, quenched and tempered
- **Safety factor:** MBL equals 4 x WLL
- **Standard :** EN 1677-2
- **Finish:** painted yellow (J), red (R) or white
- **Temperature range:** -40°C up to +200°C
- **Certification:** 2.1 2.2 3.1 MPI^b DGUV

for chain diameter		working load limit	length	width	width opening	thickness	width	width		length outside	diameter pin	weight each
mm	inch							outside	outside			
5	3/16	0.8	a	b	c	d	e	f	g	h	i	kg
6	7/32	1.12	76	7	26	15	20	28	72	108	6	0.29
7 - 8	1/4 - 5/16	2	75	7	26	15	20	28	72	108	8	0.29
10	3/8	3.2	95	9	30	20	24	32	87	136	9	0.58
13	1/2	5.4	113	12	33	24	29	42	106	164	13	1.1
16	5/8	8.2	138	15	37	32	39	54	133	208	16	2.12
18 - 20	3/4	12.8	198	19	44	40	44	68	165	240	20	3.67
22	7/8	15.5	236	23	61	49	62	82	208	305	24	7.32
			259	25	75	54	65	97	242	350	28	10.63