




Green Pin® EH Turnbuckle

Turnbuckle with eye-hook end-fitting, generally to ASTM F1145-92

- **Material:** drop forged high tensile steel SAE 1035 or 1045
- **Safety factor:** MBL equals 5 x WLL
- **Standard:** generally to ASTM F1145-92
formerly U.S. Federal Specification FF-T-791b
- **Finish:** hot dipped galvanized
- **Certification:** 2.1 2.2 3.1 MTC[®] CE



G-6314



working load limit	diameter thread	take up	length closed position	length open position	thickness hook	thickness hook	opening hook	diameter eye	width inside eye	length inside eye	length closed position	weight each
t	a inch	inch	b mm	c mm	d mm	e mm	f mm	g mm	h mm	i mm	j mm	kg
0.54	3/8	6	285	422	13	16	15	10	13	29	49	0.47
1	1/2	6	315	445	16	22	16	12	18	36	58	0.82
1	1/2	9	390	598	16	22	16	12	18	36	57	1.06
0.68	1/2	12	466	750	13	19	16	12	18	36	57	1.28
1.59	5/8	6	368	491	16	23	21	14	21	45	79	1.31
1.59	5/8	9	443	644	20	24	21	14	21	45	78	1.56
1.59	5/8	12	519	796	16	23	21	14	21	45	78	1.71
2.36	3/4	6	403	521	22	27	24	17	26	54	89	2.04
1.36	3/4	9	479	675	20	27	24	17	26	54	89	4.49
2.36	3/4	12	554	827	22	27	24	17	26	54	88	2.3
2.36	3/4	18	707	1133	22	27	24	17	26	54	89	2.85
2.27	1	6	488	595	26	35	31	24	36	75	118	3.87
4.54	1	12	636	897	26	35	31	24	36	75	117	5.09
2.27	1	18	789	1202	26	35	31	24	36	75	117	6
2.27	1	24	939	1506	26	35	31	24	36	75	116	7.52

In inch

working load limit	diameter thread	take up	length closed position	length open position	thickness hook	thickness hook	opening hook	diameter eye	width inside eye	length inside eye	length closed position	weight each
t	a inch	inch	b inch	c inch	d inch	e inch	f inch	g inch	h inch	i inch	j inch	lbs
0.54	3/8	6	11 1/4	16 5/8	1/2	5/8	19/32	13/32	1/2	1 5/32	1 15/16	1.04
1	1/2	6	12 3/8	17 9/16	5/8	7/8	5/8	15/32	23/32	1 7/16	2 9/32	1.81
1	1/2	9	15 11/32	23 9/16	5/8	7/8	5/8	15/32	23/32	1 7/16	2 1/4	2.34
0.68	1/2	12	18 11/32	29 17/32	1/2	3/4	5/8	15/32	23/32	1 7/16	2 1/4	2.82
1.59	5/8	6	14 1/2	19 11/32	5/8	29/32	13/16	9/16	13/16	1 25/32	3 1/8	2.89
1.59	5/8	9	17 1/2	25 11/32	25/32	15/16	13/16	9/16	13/16	1 25/32	3 3/32	3.44
1.59	5/8	12	20 7/16	31 5/16	5/8	29/32	13/16	9/16	13/16	1 25/32	3 3/32	3.77
2.36	3/4	6	15 7/8	20 17/32	7/8	1 3/32	15/16	11/16	1 1/32	2 1/8	3 17/32	4.5
1.36	3/4	9	18 7/8	26 9/16	25/32	1 3/32	15/16	11/16	1 1/32	2 1/8	3 17/32	9.9
2.36	3/4	12	21 13/16	32 9/16	7/8	1 3/32	15/16	11/16	1 1/32	2 1/8	3 1/2	5.07
2.36	3/4	18	27 13/16	44 5/8	7/8	1 3/32	15/16	11/16	1 1/32	2 1/8	3 17/32	6.28
2.27	1	6	19 1/4	23 7/16	1 1/32	1 3/8	1 1/4	15/16	1 7/16	2 15/16	4 5/8	8.53
4.54	1	12	25 1/32	35 5/16	1 1/32	1 3/8	1 1/4	15/16	1 7/16	2 15/16	4 19/32	11.22
2.27	1	18	31 1/32	47 5/16	1 1/32	1 3/8	1 1/4	15/16	1 7/16	2 15/16	4 19/32	13.23
2.27	1	24	36 15/16	59 5/16	1 1/32	1 3/8	1 1/4	15/16	1 7/16	2 15/16	4 9/16	16.58

INFO CAD