

**3M™ DBI-SALA® Nano-Lok™ Hot Work Self-Retracting Lifeline.**  
The first ever self retracting lifeline designed for welding, grinding and high heat applications.

**Durable**  
Reinforced webbing with Nomex®/Kevlar® fibre to withstand sparks, weld splatter and other high heat exposure.

**Versatile**  
5 different Nano-Lok configurations, single and twin-leg, that can be connected at foot level to meet your specific needs.

**Safe**  
Arc flashed to 8 calories (8 cal/cm²), for hot work use in applications like welding, grinding and torching. Meets or exceeds industry standards. CE EN360:2002. Weight capacity 140 kg.



**Nano-Lok Web SRL Hot Work Use**



	↔	🔗	🔗	🔗	🔗	🔗
3101521	2 m	🔗	🔗	🔗	63 mm	1.75
3101524	2 m	■	🔗	🔗	63 mm	3.60

**3M™ DBI-SALA® Talon™ Edge Tested Web SRL**



**Best Seller 3101048**

	↔	🔗	🔗	🔗	🔗	🔗
3101045	4.5 m	🔗	🔗	63.5 mm	2.08	
3101046	4.5 m	🔗	🔗	19 mm	1.71	
3101047	4.5 m	🔗	🔗	57 mm	1.84	
3101048	4.5 m	🔗	🔗	19 mm	1.84	
3101049	4.5 m	🔗	🔗	63.5 mm	1.94	

- Anti-ratchet system. Dyneema®/Kevlar® webbing.
- Thermoplastic housing.
- Anchorage connector: Twist Lock.



**Nano-Lok Hot Work Web SRL**



	↔	🔗	🔗	🔗	🔗	🔗
3101522	2 m	🔗	🔗	57 mm	1.50	
3101525	2 m	■	🔗	57 mm	3.20	

**Nano-Lok Hot Work Web SRL**



	↔	🔗	🔗	🔗	🔗	🔗
3101523	2 m	🔗	🔗	19 mm	1.66	

**3M™ DBI-SALA® Load Arrestor**

**Best Seller KD4PLA5005**

	↔	🔗	🔗	🔗	Working Load	🔗
KD4PLA3012	12 m	🔗	🔗	5 mm	300 kg	8.70
KD4PLA5005	5 m	🔗	🔗	7 mm	500 kg	8.30

Not suitable for personal fall arrest. Load arrestors are safety devices used in conjunction with lifting devices such as cranes and hoists. The Load arrestor provides independent protection that will arrest the fall of a load in the event of the primary system failing and reduces the risk of equipment damage and protects personnel in and around the danger zone. Models available to protect loads from 100 kg to 3,000 kg.



3M™ DBI-SALA® Nano-Lok™ XL Web Self-Retracting Lifeline - providing up to 33% more lifeline to the user. The additional length increases the anchorage options for the user and further establishes Nano-Lok as the most versatile personal SRL on the market.

- Single leg and twin leg option.
- Can be connected at foot level.
- 2.7 m to 3.3 m length models available.
- 10 different models with different carabiner and snap hooks.
- The most compact 3 m unit on the market.
- Industry standards. CE EN360:2002.
- Weight capacity 141 kg.

Applications



Nano-Lok XL Web SRL



CE EN360

	←→	🔗	🔒	🌀	📏	⚖️
3101614	3.4 m	🔗	🔒	🌀	19 mm	1.20

3M™ DBI-SALA® Nano-Lok™ XL Web Self-Retracting Lifeline



CE EN360

	←→	🔗	🔒	🌀	📏	⚖️
3101620	2.8 m	🔗	🔒	🌀	57 mm	1.50

Nano-Lok XL Web SRL



CE EN360

	←→	🔗	🔒	🌀	📏	⚖️
3101619	3 m	🔗	🔒	🌀	52 mm	1.50

Nano-Lok XL Web SRL



CE EN360

	←→	🔗	🔒	🌀	📏	⚖️
3101643	2.8 m	🔗	🔒	🌀	52 mm	1.50

Nano-Lok XL Web SRL



CE EN360

	←→	🔗	🔒	🌀	📏	⚖️
3101616	3.4 m	🔗	🔒	🌀	19 mm	1.50

Nano-Lok XL Web SRL



CE EN360

	←→	🔗	🔒	🌀	📏	⚖️
3101617	3.4 m	🔗	🔒	🌀	19 mm	1.20

Nano-Lok XL Web SRL



CE EN360

	←→	🔗	🔒	🌀	📏	⚖️
3101644	2.8 m	🔗	🔒	🌀	57 mm	1.50

Best Seller  
3101644

Nano-Lok XL Web SRL



CE EN360

	←→	🔗	🔒	🌀	📏	⚖️
3101636	2.8 m	🔗	🔒	🌀	52 mm	2.90

Nano-Lok XL Web SRL



CE EN360

	←→	🔗	🔒	🌀	📏	⚖️
3101637	2.98 m	🔗	🔒	🌀	57 mm	2.90