

3M™ Nano-Lok™ Edge Cable Self-Retracting Lifeline - the zero radius edge rated SRL

Nano-Lok Edge is specifically designed for foot level tie-off and sharp edge applications often found in construction. It is ergonomically designed for ease-of-use and is ideal for direct connection to most harnesses. The extremely compact and lightweight design is virtually unnoticeable on your back, staying out of the worker's way and making it ideal as a lanyard replacement. Whether your application requires single or twin leg configurations, mounting to an overhead anchor or for connection directly to harness, there are numerous models to choose from to suit almost any application. Nano-Lok locks quickly - stopping a fall within inches - providing more protection at low heights. In addition, tension is always kept on the lifeline, which reduces dragging, snapping and trip falls. Both features are key safety improvements.

Applications



3M™ DBI-SALA® Nano-Lok™ Edge Tested Cable Self-Retracting Lifeline



	↔	⚙	🔗	🔒	🌀	📊
3500245	2.4 m		🔗	🔒	19 mm	1.30
3500242	2.4 m	■	🔗	🔒	19 mm	3.28

Nano-Lok Edge Tested Cable SRL



	↔	⚙	🔗	🔒	🌀	📊
3500224	2.4 m		🔗	ⓐ	19 mm	1.70
3500239	2.4 m	■	🔗	ⓐ	19 mm	2.49

Dedicated Foot Level Tie-Off

Dedicated design minimises fall forces, auto retraction of unused lifeline minimises trip hazards.

Integrated Back-Pack Style Energy Absorber

Works with connector to limit fall forces, for extreme sharp edge performance. Back pack design stays tight, evenly disperses weight.

Designed to Meet Sharp Edge Standards

Cable - Galvanised steel 5 mm lifeline - Extreme sharp edge protection - Meets CE EN:2002 & standard requirements of VH11.60 rev 7.

Web - High-resistance web 20 mm Dyneema® web makes lightweight and extreme resistance performance possible.



Easy-Fit Connector

360° rotation, full integration with energy absorber, frees D-Ring for other equipment.

Impact-Resistant Housing

Lightweight but extremely durable.

141 kg Weight Capacity

Ultimate jobsite flexibility to accommodate users who carry more equipment.

Galvanised Steel 5 mm Lifeline

Extreme sharp edge protection.

Multiple Hook Options

Configure to your unique requirements.

Nano-Lok Edge Tested Cable SRL



	↔	⚙	🔗	🔒	🌀	📊
3500243	2.5 m		🔗	ⓐ	63.5 mm	1.30
3500240	2.4 m	■	🔗	ⓐ	63.5 mm	2.81

Nano-Lok Edge Tested Cable SRL



	↔	⚙	🔗	🔒	🌀	📊
3500244	2.4 m		🔗	ⓐ	57 mm	1.46
3500241	2.4 m	■	🔗	ⓐ	57 mm	2.49

Best Seller 3500244

3M™ DBI-SALA® Nano-Lok™ Edge Tested Web Self-Retracting Lifeline



CE EN360

	↔	🔗	🔗	🔗	🔗	kg
3101430	2.4 m		🔗	Ⓐ	19 mm	1.30
3101440	2.4 m	■	🔗	Ⓐ	19 mm	2.22

Nano-Lok Edge Tested Web SRL



CE EN360

	↔	🔗	🔗	🔗	kg	
3101432	2.5 m		🔗	Ⓐ	63.5 mm	1.70

3M™ DBI-SALA® Nano-Lok™ Edge Tested Web Self-Retracting Lifeline



CE EN360

	↔	🔗	🔗	🔗	🔗	kg
3101448	2.5 m	■	🔗	Ⓢ	63.5 mm	3.22

Nano-Lok Edge Tested Web SRL



CE EN360

	↔	🔗	🔗	🔗	🔗	kg
3101433	2.5 m		🔗	Ⓐ	57 mm	1.30
3101443	2.5 m	■	🔗	Ⓐ	57 mm	2.22

Best Seller
3101433

Nano-Lok Edge Tested Web SRL



CE EN360

	↔	🔗	🔗	🔗	kg	
3101436	2.4 m		🔗	Ⓐ	19 mm	1.46

Nano-Lok Edge Tested Web SRL



CE EN360

	↔	🔗	🔗	🔗	🔗	kg
3101435	2.4 m		🔗	Ⓢ	50 mm	1.63
3101445	2.4 m	■	🔗	Ⓢ	50 mm	2.88

