



# 3M™ Protecta® Rebel™ Self-Retracting Lifeline

Total compliance, absolute confidence.

Rebel SRLs are available with a heavy duty aluminium or a durable lightweight thermoplastic housing, providing an economical fall protection solution without compromising on performance or safety. Integrated ergonomic carrying handle and top swivel connector ensure easy transport and installation. Built-in fall indicator hook allows visual yearly inspection. Rebel Cable blocks meets the latest CE sharp edge certification when used with an extension sling.

## Applications



### Anchor Swivel

Allows the block to align with lifeline and avoid any torsion of the cable when the user is working.

### Choice of Housing (Thermoplastic or Aluminium)

Durable thermoplastic for lightweight or aluminium for ultimate ruggedized housing allows for job site flexibility.

### Galvanized or Stainless Steel 5 mm Cable or High-strength polyester webbing

Larger cable diameter for added strength and safety.

### Side Cable Exit

Allows best alignment of the cable and minimises cable guide wear.

### 140 kg Weight Capacity

High capacity allows for use by most users and tools ensuring the highest level of safety.

### Ergonomic Cable Bumper

Allows the block to align with lifeline and avoid any torsion of the cable when the user is working.

### Ergonomic Carrying Handle

Allows easier transportation of the block.



**3M™ Protecta® Rebel™ Cable Self-Retracting Lifelines - 4.5 m**



CE EN360

	←→	⚙	⚙	⚙	⚙	kg
3590024	4.5 m	⚙	Ⓣ	Ⓞ		2.80

**Rebel Cable SRL - 6 - 15 m**



Best Seller  
3590521 & 3590570

CE EN360

	←→	⚙	⚙	⚙	⚙	kg
3590520	6 m	⚙	Ⓣ	Ⓞ		5.30
3590521	10 m	⚙	Ⓣ	Ⓞ		5.60
3590522	10 m	⚙	Ⓣ	Ⓞ		5.60
3590570	15 m	⚙	Ⓣ	Ⓞ		7.50
3590571	15 m	⚙	Ⓣ	Ⓞ		7.50

**Rebel Cable SRL - 20 - 30 m**



Best Seller  
3590610

CE EN360

	←→	⚙	⚙	⚙	⚙	kg
3590610	20 m	⚙	Ⓣ	Ⓞ		10.00
3590611	20 m	⚙	Ⓣ	Ⓞ		10.00
3590650	25 m	⚙	Ⓣ	Ⓞ		13.00
3590651	25 m	⚙	Ⓣ	Ⓞ		13.00
3590690	30 m	⚙	Ⓣ	Ⓞ		13.40
3590691	30 m	⚙	Ⓣ	Ⓞ		13.40

**3M™ Protecta® Rebel™ Horizontal Use Extension Sling**

CE EN360

	kg
3500050	2.00

Mandatory for Rebel cable blocks to be compliant with the latest horizontal sharp edge requirements VG 11.

**3M™ Protecta® Rebel™ Cable SRL Cover**



Best Seller  
3590010

	Description	kg
3590010	For 6 m, 10 m Rebel models	0.20
3590011	For 15 m Rebel models	0.20
3590012	For 20 m, 25 m, 30 m Rebel models	0.28

**3M™ Protecta® Rebel™ Web Self-Retracting Lifelines - 2 m**



Best Seller  
3100418

CE EN360

	←→	⚙	⚙	⚙	⚙	⚙	kg
3100418	1.9 m	⚙	17 mm	⚙	Ⓣ	Ⓞ	1.00
3100419	2 m	⚙	57 mm	⚙	Ⓣ	Ⓞ	1.20
3100420	2 m	⚙	17 mm	⚙	Ⓣ	Ⓞ	1.20
3100421	2 m	⚙	57 mm	⚙	Ⓣ	Ⓞ	1.40
3100422	2.1 m	■	57 mm	⚙	Ⓣ	Ⓞ	2.60

**Rebel Cable Leading Edge SRL**



CE EN360

	←→	⚙	⚙	⚙	⚙	⚙	kg
3590542	6 m	Ⓞ	5.6 mm	⚙	Ⓣ	Ⓞ	5.60
3590545	12 m	Ⓞ	5.6 mm	⚙	Ⓣ	Ⓞ	8.50

The only SRL that complies to extreme sharp edge (VG11.054, type B, 0 mm radius). Users are now able to tie-off at foot level with the 6 m Leading Edge Rebel without requiring to connect the sharp edge extension sling. This built-in sharp edge product was put through extensive sharp edge testing to ensure absolute protection against sharp, abrasive and leading edges found at construction sites.

**Rebel Cable Retrieval SRL**



CE EN360

EN 1496

	←→	⚙	⚙	⚙	⚙	⚙	kg
3591002	15 m	Ⓞ	5 mm	⚙	Ⓣ	Ⓞ	11.90
3591003	15 m	Ⓞ	5 mm	⚙	Ⓣ	Ⓞ	11.90

These Retrieval models incorporate fall arrest and a built-in emergency retrieval winch for rescue, making them a versatile solution for many job sites.

- 15 m SRL with rescue winch
- Brackets available for easy tripod integration
- Designed for confined space applications

3590498 - Bracket for AM100 Protecta tripod  
3590499 - Bracket for DBI-SALA® tripods KM1PT7 and KM1PT9

**Rebel Web SRL - 3 m**



Best Seller  
3100423

CE EN360

	←→	⚙	⚙	⚙	⚙	kg
3100423	3 m	⚙	Ⓣ	Ⓞ		1.40

**Rebel Web SRL - 6 m**



Best Seller  
3100437

CE EN360

	←→	⚙	⚙	⚙	⚙	kg
3100437	6 m	⚙	Ⓣ	Ⓞ		2.20