

3M™ Protecta® Sanchoc™ Webbing Lanyard



- Supple & flexible webbing offers great ease of use
- Highly abrasion resistant 45 mm webbing
- Terminations sewn with high strength polyester thread
- Identification labels protected within transparent shock pack cover
- Wide range of designs and connector options available

	↔	EW	🔗			🔗			CE EN355
			🔗	🔗	🔗	🔗	🔗	🔗	kg
AE529/1	1.5 m		🔗	17 mm	Ⓢ	🔗	17 mm	Ⓢ	0.73
AE529/61	1.5 m		🔗	17 mm	Ⓢ	🔗	50 mm	Ⓢ	1.00
AE529	2 m		🔗	17 mm	Ⓢ	🔗	17 mm	Ⓢ	0.77
AE529/6	2 m		🔗	17 mm	Ⓢ	🔗	50 mm	Ⓢ	1.08
AE529E/5	2 m	■	🔗	18 mm	Ⓢ	🔗	50 mm	Ⓢ	1.16

3M™ Protecta® Sanchoc™ Kernmantle Rope Edge - Tested Lanyard



- Tested over a 0.50 mm Radius edge
- Enhanced protection for workers exposed to working over edges
- 12.50 mm Kernmantle rope offers exceptional durability and product life
- Available with Twist Lock carabiner body connector for even greater security
- Differentiated from standard Sanchoc kernmantle rope lanyards by Orange colour yarn

	↔	🔗	🔗	🔗			🔗			CE EN355
				🔗	🔗	🔗	🔗	🔗	🔗	kg
AE5220REK/SE	2 m		1	🔗	19 mm	Ⓢ	🔗	60 mm	Ⓐ	1.25
AE5315REK/SE	1.5 m	■	2	🔗	19 mm	Ⓢ	🔗	60 mm	Ⓐ	1.80
AE5220RBB/SE	2 m		1	🔗	18 mm	Ⓢ	🔗	18 mm	Ⓢ	0.90
AE5220RBK/SE	2 m		1	🔗	18 mm	Ⓢ	🔗	60 mm	Ⓐ	1.40

3M™ Protecta® Sanchoc™ Kernmantle Rope Lanyard



- 10.50 mm diameter kernmantle rope leg material
- Rope terminations sewn with high strength polyester thread
- Identification labels protected within transparent shock pack cover
- Wide range of designs and connector options available

	↔	🔗	🔗	🔗			🔗			CE EN355
				🔗	🔗	🔗	🔗	🔗	🔗	kg
AE522/13	1.5 m		1	🔗	19 mm	Ⓢ	🔗	19 mm	Ⓢ	0.85
AE522/15	1.5 m		1	🔗	19 mm	Ⓢ	🔗	50 mm	Ⓢ	1.13
AE522/1	1.5 m		1	🔗	17 mm	Ⓢ	🔗	17 mm	Ⓢ	0.77
AE522/3	2 m		1	🔗	19 mm	Ⓢ	🔗	19 mm	Ⓢ	0.88
AE522/5	2 m		1	🔗	19 mm	Ⓢ	🔗	50 mm	Ⓢ	1.16
AE522/6	2 m		1	🔗	17 mm	Ⓢ	🔗	50 mm	Ⓢ	1.10
AE525	Adj. 2 m		1	🔗	17 mm	Ⓢ	🔗	17 mm	Ⓢ	0.86
AE525/1	Adj. 2 m		1	🔗	17 mm	Ⓢ	🔗	50 mm	Ⓢ	1.22
AE5310RAK	1 m	■	2	🔗	17 mm	Ⓢ	🔗	60 mm	Ⓐ	1.60
AE532/31	1.30 m	■	2	🔗	19 mm	Ⓢ	🔗	50 mm	Ⓢ	1.74
AE532/2	1.50 m	■	2	🔗			🔗			0.54
AE5318RAK	1.80 m	■	2	🔗	17 mm	Ⓢ	🔗	60 mm	Ⓐ	1.60
AE532/1	1.80 m	■	2	🔗	17 mm	Ⓢ	🔗	50 mm	Ⓢ	1.75
AE532/3	1.80 m	■	2	🔗	19 mm	Ⓢ	🔗	50 mm	Ⓢ	1.73

3M™ Protecta® Restraint Lanyard



Protecta rope connecting lanyards are an ideal solution for the connecting element in a restraint system. Made from polyamide braided rope with safety stitching. Rope diameter 10.50 mm.

	↔	🔗	🔗			🔗			CE EN354
			🔗	🔗	🔗	🔗	🔗	🔗	kg
AL410B	1 m	1	-	-	-	-	-	-	0.11
AL410C	1 m	1	🔗			🔗			0.16
AL410C2	1 m	2	🔗			🔗			0.87
AL415B	1.5 m	1	-	-	-	-	-	-	0.15
AL415C	1.5 m	1	🔗			🔗			0.19
AL420B	2 m	1	-	-	-	-	-	-	0.18
AL420C	2 m	1	🔗			🔗			0.22
AL420C1	2 m	1	🔗	17 mm	Ⓢ	🔗	17 mm	Ⓢ	0.63
AL420C2	2 m	1	🔗	17 mm	Ⓢ	🔗	50 mm	Ⓢ	0.91
AL4000	1.8 m	1	🔗			🔗			0.23
AL432	1 m	2	-	-	-	-	-	-	0.25
AL432/1	1.3 m	2	🔗	17 mm	Ⓢ	🔗	50 mm	Ⓢ	1.39