


Universe	Professional
Type	Verticality
Category	Pulleys
Subcategory	Pulley-carabiners




ROLLCLIP Z

ROLLCLIP Z is a pulley-carabiner with a gate opening on the non-pulley side to facilitate installation on anchors and devices. It is available in two locking systems: automatic TRIACT-LOCK system or manual SCREW-LOCK system.



The ROLLCLIP Z pulley may be used as a directional point on the upper attachment point of the ASCENSION handled rope clamp, for short rope ascents. Gate opening on the non-pulley side facilitates installation on the ASCENSION.



The ROLLCLIP Z pulley can be used for tree care to attach the ZIGZAG descender to the attachment bridge on the SEQUOIA harness, for improved lateral mobility.

Short Description Pulley-carabiner that facilitates installation on anchors and devices



Selling Points

- Easier handling:
 - sheave mounted on sealed ball bearings for excellent efficiency
 - gate opening on the non-pulley side, to facilitate installation on devices
 - Keylock system prevents any accidental snagging of the carabiner when putting the pulley in place
- H cross-section of carabiner:
 - ensures an improved strength-to-weight ratio
 - protects markings from abrasion
- Two locking systems available:
 - TRIACT-LOCK: automatic locking with triple-action gate opening
 - SCREW-LOCK: the manual screw-lock with red band provides a visual warning when the carabiner is unlocked

Specification

- Material(s): aluminum
 - Min. rope diameter: 7mm
 - Max. rope diameter: 13mm
 - Sheave diameter: 18mm
 - Maximum working load: $2 \times 2 = 4\text{kN}$
 - Efficiency: 85%
 - Major axis strength: 20kN
 - Minor axis strength: 8kN
 - Open gate strength: 7kN
-

Specifications by reference

Reference(s)	P75 TL	P75 SL
		
Locking system	TRIACT-LOCK	SCREW-LOCK
Weight	110 g	105 g
Certification(s)	CE EN 362, EN 12278, EAC	CE EN 362, EN 12278, EAC
Gate opening	20 mm	21 mm
Made in	FR	FR
Guarantee	3 years	3 years
Packing	1	1
Case quantity	10	10
EAN	3342540815872	3342540815865