



Non-Asbestos Gaskets 150lb

Green compressed non-asbestos sheet is made from aramid and other synthetic fibers, and is bonded with NBR (nitrile). It is used in numerous applications in the process and water and wastewater industries. This material is resistant to oils and many mild chemicals and acids.

Rated to 464°F.





Ring Gaskets

Full Face Gaskets

Size	1/16	1/8	1/16	1/8
1"	\$1.01	\$1.26	\$1.51	\$1.85
1-1/4"	\$1.11	\$1.46	\$1.49	\$2.22
1-1/2"	\$1.21	\$1.67	\$1.61	\$2.47
2"	\$1.40	\$1.55	\$2.07	\$3.18
2-1/2"	\$1.54	\$2.29	\$2.35	\$3.96
3″	\$1.74	\$2.62	\$2.60	\$4.69
4"	\$2.29	\$3.64	\$3.57	\$6.29
5″	\$2.69	\$4.48	\$4.11	\$7.43
6"	\$3.24	\$5.48	\$4.44	\$8.57
8″	\$4.31	\$7.57	\$6.48	\$12.21
10″	\$5.69	\$10.93	\$8.40	\$15.55
12″	\$8.12	\$15.38	\$11.48	\$21.12
14"	\$9.64	\$18.50	\$13.33	\$26.17
16″		\$23.74	\$16.95	\$32.24
18″		\$25.83	\$18.07	\$37.88
20"	\$15.95	\$32.07		\$45.40
24"		\$42.50		\$60.12



Click on part to Buy Online.



Spiral Wound Gaskets 150lb

Tipco Gasket & Sealing Division inventories a full line of high performing, exceptional quality spiral wound gaskets.

Tipco offers in inventory, two styles of spiral wound gaskets:

- 1. Standard inner metal winding & outer centering ring
- 2. Tipco highly recommended spiral wound gasket with inner ring*.

We inventory these gaskets in 304 & 316 stainless steel with graphite filler winding.

Also available with PTFE filler.



Size	304SS	304SS with Inner Ring	316SS with Inner Ring
1"	\$1.09	\$1.55	\$1.83
1-1/4"	\$1.19	\$2.14	\$2.88
1-1/2"	\$1.36	\$2.45	\$3.97
2"	\$1.92	\$3.53	\$5.05
2-1/2"	\$2.62	\$4.43	\$6.88
3″	\$2.75	\$6.14	\$9.17
4"	\$4.59	\$10.10	\$13.00
5"	\$4.76	\$11.43	\$22.22
6"	\$5.80	\$14.45	\$20.88
8"	\$8.34	\$18.19	\$23.45
10"	\$11.09	\$22.19	\$34.57
12"	\$16.76	\$31.00	\$40.02
14"		\$49.11	
16"		\$43.12	
18"	\$30.26	\$61.63	
20"		\$55.24	
24"	\$41.60	\$71.76	



Click on part to Buy Online.


^{*} The inclusion of the inner ring helps prevent in service damage to the winding due to media flow and also assists in preventing over compression.

Red Rubber Gaskets 150lb

Red SBR rubber gasket material, this is a low-cost option typically used in heating and plumbing applications. This material is not oil-resistant, but offers good abrasion and aging resistance.

Rated to 180°F.





Ring Gaskets

Full Face Gaskets

Size	1/16	1/8	1/16	1/8
1″	\$0.79	\$0.38	\$0.29	0.63
1-1/4"	\$0.83	\$0.44	\$1.02	\$1.03
1-1/2"	\$0.29	\$0.79	\$0.46	\$1.12
"2"	\$0.36	\$1.00	\$0.55	\$1.54
2-1/2"	\$0.38	\$1.07	\$1.14	\$2.24
3″	\$0.96	\$1.45	\$0.95	\$2.07
4"	\$0.68	\$2.07	\$1.38	\$3.34
5″	\$0.80	\$1.53	\$1.67	\$4.60
6"	\$1.14	\$3.57	\$2.71	\$3.38
8"	\$1.30	\$5.79	\$5.19	\$4.69
10"	\$2.18	\$5.84	\$4.30	\$7.64
12"	\$5.27	\$9.65	\$10.24	\$9.79
14"	\$5.84	\$11.95	\$7.54	\$17.14
16"	\$12.38	\$8.68	\$8.77	\$20.52
18"	\$19.74	\$10.80	\$8.92	\$26.89
20"	\$25.36	\$23.10	\$9.36	\$33.41
24"	\$26.00	\$16.36	\$40.88	\$47.89



TIPCO Sealing Technologies

715 Ordnance Road, Suite 105-106

Glen Burnie. MD 21226

Phone: 410.710.6055 - Fax: 410.766.1825

gaskets@tipcotec.com