



Wide Range Coupling

Product Bulletin

10/2020

Simplify Coupling Installation with Ford's FC2W

The FC2W Wide Range Coupling can join virtually any pipe within a nominal pipe size. The unique gaskets are pre-lubricated and seal on the pipe with fewer wrench turns.



FEATURES

- Stab fit for easy installation, no field adaptation required
- Custom designed, pre-lubricated NBR (Buna-N) gaskets
- Fusion-bonded epoxy coating
- 350 psi rated working pressure, sizes 3" - 12"
- 250 psi rated working pressure, size 16"
- Available in a 12" sleeve length

NOMINAL PIPE SIZE	RANGE (INCHES)	RANGE (MM)	SLEEVE LENGTH*	PART NUMBER
3"	2.50 - 4.29	63.5 - 109.0	7"	FC2W-3
4"	3.96 - 5.60	100.5 - 142.2	7"	FC2W-4
6"	6.23 - 7.60	158.2 - 193.0	7"	FC2W-6
8"	8.40 - 9.75	213.3 - 247.6	7"	FC2W-8
10"	10.75 - 12.12	273.0 - 307.8	9"	FC2W-10
12"	12.75 - 14.38	323.8 - 365.2	9"	FC2W-12
16"	16.00 - 17.80	406.4 - 452.1	10"	FC2W-16

Smaller pipe diameters may be accommodated within each nominal size at a reduced pressure rating. Contact factory for details.

* For 12" sleeve in sizes 3" - 12", add "-L12" to the part number. Example: FC2W-8-L12

The Ford Meter Box Company, Inc. 775 Manchester Avenue, P.O. Box 443, Wabash, Indiana, USA 46992-0443
Telephone: 260-563-3171 • www.fordmeterbox.com