



Overview

Mirrored acrylic is a very versatile, lightweight product which is used in a number of markets and applications, a very unique product which is easy to use.

Main Benefits

- Mirror finish
- Flat & rigid
- Strong
- Lightweight
- Easy to cut

Typical Applications

- Point of sale
- Retail fit out
- Furniture & joinery
- Feature Wall
- Safety mirror

Mirror Acrylic

Product Range/Dimensions

Type	Thickness	Length x Width
Silver or Gold	3.0mm	2440mm x 1220mm

Colours



Note: Colours may not represent the physical product.

Panel Physical Properties

Property	Result
Density	1.19g/cm ³
Weight (3mm)	3.69kg/m ²
Gauge Tolerance	+/- 8%
UV Performance	Good*
Abrasive Resistance	Fair*
Impact Strength	Good*
Light Transmission	92% (Clear)
Service Temperature	80°C
Vicat Softening Temperature	115°C
Forming Temperature	160°C - 175°C
Minimum Cold Bending Radius	330 times the sheet thickness
Expansion/ Contraction Rate	5mm/m
Fire Rating	Group 4*
Cleaning	PSP Cleaner or warm soapy water & soft cloth

*More detailed technical information available upon request



Auckland - Albany
320 Rosedale Road
Ph: 09 415 2800
Fax: 09 415 2809
Email: info@psp.co.nz

Auckland - East Tamaki
60A Cryers Road
Ph: 09 274 1800
Fax: 09 271 2833
Email: auckland@psp.co.nz

Hamilton
39 McKee Street, Pukete
Ph: 07 850 6280
Fax: 07 850 6284
Email: hamilton@psp.co.nz

Wellington
61 Seaview Road, Seaview
Ph: 04 568 7180
Fax: 04 568 7183
Email: wellington@psp.co.nz

Christchurch
72 Hammersmith Drive, Sockburn
Ph: 03 341 0248
Fax: 03 341 0257
Email: christchurch@psp.co.nz