



**IMPERVIA
FLOORING**

Provided that our Storage Maintenance and Fitting Instructions are followed at all times the Product has the following specifications

Impervia Luxury Plank Flooring Product Specification & Technical Data Sheet

Product Code: IMP-6118-3

IMPERVIA LUXURY PLANK DRIFTWOOD GREY FLOORING



Sustainability:

The composite core is mainly made up of crushed stone, and with 1.5mm IXEP backing. For our commercial grade the top layers are virgin material for durability. **Waterproof, Fireproof and Formaldehyde Free Flooring.**

With our forests ever decreasing and precious resources being used for an increasing market in wood flooring, we have an alternative that uses less of our natural forests.

Impervia Luxury Flooring is extruded from natural element's and stone. The decorative layer is made from high quality photographic paper and our acoustic backing is VOC free with no cryogenic emissions or formaldehyde.

The finish has a ceramic quality for high traffic areas.

The IPXE backing has an acoustic property of 21 db.

The total thickness is 6.5mm and it requires no adhesive or other accessories or material to fit.

Product Details

| | |
|-----------------------|--|
| Type: | Impervia stone composite rigid floor board |
| Size: | 6.5mm thick (5mm plank + 1.5mm IXEP backing) x 228mm wide x 1524mm |
| Finish: | AC5 commercial grade surface guaranteed 15 years |
| Process : | Textured Surface |
| Length: | 1524mm Fixed Length |
| Profile: | Push fit Valinge 5G-I click system |
| Pattern: | Single width plank |
| Edge Profile: | Micro-Bevelled (all four sides) |
| Top Layer: | 0.5mm |
| Construction: | Composite stone centre, 1.5mm IXEP backing and 0.5mm EIR surface |
| Slip Resistance: | Low Risk in Pendulum Tests scoring 69 PTV in the Dry and 38 in the Wet using slider 96 |
| Acoustic Performance: | Impact Sound Reduction 21dB |
| Grade: | Natural looking to replicate a real timber floor. |
| Packing: | Cardboard cartons, shrink wrapped, 6 pieces per carton with 2.0848m ² |
| Weight: | Each carton will weigh approx. 20.8kgs |
| Durability: | Waterproof construction, stain resistant and hard wearing |
| Underfloor Heating: | This floor is suitable for underfloor heating |

Features and Benefits of Impervia Luxury Plank Flooring:




Protection for everyday use



Saves money & installation time



Including basements



Quick & easy to install



Installation Methods:

| | |
|--------------------------|---|
| Fully Bonded: | No |
| Secret nailed: | No |
| Floated: | Yes, direct to a substrate with a maximum of 3mm undulations over 3 metres |
| Over Underfloor Heating: | Yes, compatible for UFH subject to following the correct installation requirements. |

Aesthetics and Characteristics:

Impervia Luxury Plank Flooring is made by taking high resolution images of real floors to replicate quality wood flooring.

| Item | EN Norms | Result | ASTM Norms | Result |
|---------------------------------------|--|--|--------------|------------------|
| Size | EN 427 | 600 x 300 mm | ASTM F536 | 600.1 x 300.2 mm |
| Dimension Squareness and Straightness | EN 427 | Squareness:0.09mm Straightness:0.07m m | | |
| Chemical Resistance | EN 423 | Pass | ASTM F925 | Pass |
| Colour Fastness to Artificial light | EN 20105:B02 method A | Pass, >=Grade6 | ASTM F1515 | Pass |
| Wear Resistance | EN 660-1 | Weargroup: T | | |
| Scratch resistance | ISO 10582 | 3200g | ASTM F3261 | Pass |
| Resistant to impact | | | ASTM F1265 | Pass |
| Dimensional Stability | E434 | Stability:Pass 0.1% Curling: 0.06mm | ASTM F1700 | Pass, |
| Residual Indentation | EN 433 | Pass, 0.06mm | ASTM F970 | Pass |
| Acoustic | 21dB Impact Sound Reduction in accordance to BS EN ISO 717-2:2013 | | | |
| Slip Resistance | EN 13893 | Class DS | | |
| | Tested to BS 7967-2:2002+A1:2013 (Pendulum Test in PTV values using slider 96) Results: DRY (69) LOW RISK WET (38) LOW RISK | | | |
| Behaviour to Fire | EN 13501-1 | Bf1-S1 | ASTM E648-06 | Pass/Class 1 |
| Smoke Density | | | ASTM E662 | Pass, <=450 |

Manufacturing: Impervia floors are manufactured using the latest extrusion technology where the protective top layer, decorative layer and composite centre core are extruded as one fusing them together to create a natural looking surface and in accordance with accepted industry standards, which permit a tolerance not to exceed 5%. The variations may be of a manufacturing or natural type (this does not include colour variation). The surface is then finished on a UV line after been pressed to create the textured surface.

Samples: Small samples will give a representative example of the colour of the finished floor. However, inherent characteristics of wood will make every individual piece of wood unique and one small sample WILL NOT be representative of the overall effect of a natural wood floor. Therefore, should it be necessary to gain a better understanding of how a larger area will look, purchasing cartons for a sample area should be considered, before making a final decision.

Storage: See Impervia Storage Fitting and Maintenance Instructions part of our T&C's
DO NOT take boards onto site until all WET trades have been completed.

Fixing: See Impervia Storage Fitting and Maintenance Instructions part of our T&C's
The composite flooring we produce uses the latest Valinge push fit technology so it is very easy to install due to its stability in not being affected by moisture.

NBS:

NBS specifications can be written by request once we have full details of the subfloor build up.

Cleaning: See Impervia Storage Fitting and Maintenance Instructions part of our T&C's **(never use solvent cleaning solution)** Correct cleaning and maintenance is important. Contamination from paints, whether oil or acrylic based will prove to be difficult to remove without damaging the wood surface. If any paint finds its way onto the wood surface, then BEFORE it completely dries, gentle rubbing with a non-alcoholic wipe might soften and remove the paint - but once the paint has dried it will be almost impossible to remove.

Health & Safety:

Impervia Luxury Plank Flooring is a manmade product and on its own offers no recognisable health and safety risks. When re-manufacturing any wood product please follow HSE advice.

Company Approvals:

The Solid Wood Flooring Company operate a stringent sustainable environmental policy, details of which can be seen on the web site. We are certified by all the relevant organisations and our certificate numbers can be seen below.

FSC® - Solid Wood Flooring Trademark Licence Number: FSC® C007915

FSC® - Solid Wood Flooring Chain of Custody Number: NC-COC-005535 HA

PEFC™ - Solid Wood Flooring Trademark Licence Number: PEFC/16-37-1814

PEFC™ - Solid Wood Flooring Certificate Number: CATG-PEFC-400-AT

WWF® - The Solid Wood Flooring Company achieved the highest - 3 Trees - accreditation

Never build onto a stone composite floor: Impervia Luxury plank flooring doesn't provide a good foundation to build onto. Therefore, it is important to design any cabinets and internal furniture with their own structural base and not to be sat on the stone composite flooring, so that should any damage occur, the floor finish can be easily repaired or removed.