

Article number: 1072050

20W-50 Street Bike

4T Motorcycle Motoroil

DESCRIPTION

DEUTSCHÖL 20W-50 Street Bike is a semi-synthetic motor oil with extreme high temperature stability. Formulated for air- and water-cooled motorcycles with high speed fourstroke engines, equipped with a common oil reservoir of engine, gear box and wet clutch system. Guarantees maximum performance, without any negative influence on the stability of the engine.

THIS PRODUCT IS RECOMMENDED BY REKTOL IF THE FOLLOWING FILLING REQUIREMENTS ARE REQUIRED:

SAE 20W-50
API SN

JASO MA2 (T903:2011)

ADVANTAGES

- high operating safety
- excellent wear protection through outstanding lubrication
- outstanding corrosion protection
- very good oxidation stability
- low evaporation loss
- suitable for dry and oil bath clutch systems (please observe operational regulations!)

TYPICAL CHARACTERISTICS

Properties

Density at 15°C

CCS -15 °C

Pourpoint

Viscosity at 40 °C

Viscosity at 100 °C

Viscosity Index

Test according to

DIN 51757

ASTM-D 5293

DIN ISO 3016

DIN 51562

DIN 51562

DIN ISO 2909

Data Unit

0,870 g/ml

4900 cP

< -20 °C

165 mm²/sec

19 mm²/sec


130

Article number: **1072050**

Available Packaging



Item-number: 1072050-1 1072050-4 1072050-5 1072050-20



Item-number: 1072050-60 1072050-205

The information in this product data sheet is based on years of experience of our team and our partners. Our professional competence in the development and manufacturing of lubricants are based on the current state-of-the-art. Universally valid statements regarding the function of our lubricants are not possible, because the lubricant performance can be influenced by a series of factors. As a result, the lubricant filling process, the exact purpose of use, the general operating conditions, the system degree of wear and the system contamination etc. must be taken into account in particular in engines, machinery and equipment. The data given in this product data sheet represents general, non-binding guideline values. No warranty expressed or implied is given concerning the properties. We recommend to consult our team regarding the application conditions and requirements before the DEUTSCHÖL lubricant is used. The user should test the functional suitability of our lubricants in the intended application and use the product with the corresponding care and responsibility according to the manufacturer's specifications. Our products undergo continuous improvements. We therefore reserve the right to change our product program, the products and their manufacturing processes as well as all details at any time and without warning.

Please note: Our products may not be used in aircraft and spacecraft or parts thereof.