



### Features

Pure aluminum heatsink  
Seoul SMD3030  
Seoul dimmable driver  
Output 150lm/W  
5 years warranty

### General information

|                     |   |     |     |
|---------------------|---|-----|-----|
| Part No.            | GSPro-HB100W  |     |     |
| Power               | 100W ±5%  |     |     |
| Input Voltage       | Ac100-277V  |     |     |
| Power Factor        | >0.95   |     |     |
| CCT                 | 3000/4000/5000/5700K  |     |     |
| CRI                 | Ra70  |     |     |
| Lumen               | 15000lm ±5%   |     |     |
| Beam angle          | 140°(Regular)   | 90° | 45° |
| Installation height | 7m  | 7m  | 8m  |
| Dimmable            | 1-10V   |     |     |
| IP grade            | IP65  |     |     |
| Lifespan            | 50,000H at 50 ambient temperature   |     |     |
| Working Temperature | -40 - 50  |     |     |
| Installing method   | Hanging hook / Adjustable bracket / NPT   |     |     |
| Material            | Aluminum + Glass  |     |     |
| Weight              | 4.5KG   |     |     |
| Accessory           | Reflector, dust-proof shield, plug  |     |     |
| Remarks             | 1. Available with DALI dimming<br>2. Available with Sensor – Occupancy and Daylight |     |     |

### Dimensions

