

# OPR/OPK

OPR+/OPK+ RUPTURE DISC HOLDER

*Designed to ensure the **correct and safe performance** of our OPR+/OPK+ rupture discs. The holder bolts between standard ANSI flanges and interfaces with multiple flange ratings.*



OsecoElfab's OPR/OPK Holder is designed for the OPR+/OPK+ rupture disc. It is available with taps for an excess flow valve or pressure gauge and for the non-invasive, re-usable Flo-Tel+ burst sensor.

The holder also features a machined inlet for System-Loc to ensure correct installation. The design is compatible with ANSI, PN and DIN flange ratings.

## Sizes

1" - 12"

## Discs

OPR+/OPK

## Common Applications

- Safety Relief Valve Isolation
- Flanged Piping Systems

**Let us help you with all  
your pressure relief questions.**

**US office** | Broken Arrow

+1 (918) 258 5626 | [info@osecoelfab.com](mailto:info@osecoelfab.com)

**UK office** | North Shields

+44 (0)191 293 1234 | [uksales@osecoelfab.com](mailto:uksales@osecoelfab.com)

[osecoelfab.com](http://osecoelfab.com)



# TECHNICAL SPECIFICATIONS



Size range	1"-12" (25-300mm)
Standard materials	316 Series Stainless Steel
Relief Valve Isolation	Suitable for safety relief valve isolation
Design Standards	Designed to meet ASME standards

## Certifications

ASME UD  
CRN  
PED 2104/68/EU

## Related Products

### Rupture Discs

OPR+  
OPK+

### One Piece Unit

Oseco Safety  
Cartridge

### Sensors

Flo-Tel+



SIZE		ANSI RATING	O.D. (inches)	OVERALL HEIGHT (inches)
inches	DN (mm)			
1	25	150/300/600	2.75	1.59
1.5	40	150/300/600	3.63	1.67
2	50	150/300/600	4.25	1.73
3	80	150/300/600	5.75	2.17
4	100	150/300/600	7.00	2.28
6	150	150/300/600	9.75	2.91
8	200	150/300/600	10.88	3.58
10	250	150/300/600	13.25	4.14
12	300	150/300/600	16.00	4.76