

# SPECIFIC PROCESSING CONDITIONS

## CONVEX / INCLINED AND ANTISLIP FLOORS

### CONVEX/INCLINED (HEATED) FLOORS

#### Scope of these processing conditions

Type numbers: 570.000-571.000

#### Placement

- The floor elements are placed with suitable lifting claws: type of lifting claw depends on the weight of the element (see product drawings). Floor elements can also be placed with a suction cup of sufficient size.
- The bearing direction of the elements is indicated on the product drawings as well as the permissible load and the weight of the element.
- Floor elements may not be clamped at the height of the support edges.

#### Processing

- Heated floor elements must not be pierced unless explicitly stated otherwise on the product drawing.
- Couplings for the heating hoses are included. It is recommended to put water pressure on the circuit before smearing the openings.
- Openings in the floor elements are smeared after installation with cementitious mortar.

### PREFABRICATED ELEMENTS

#### Scope of these processing conditions

Floor elements type numbers: 573.000 - 574.000 - 0000.0000G000

Wall elements types: 0000.0000G000

#### Placement of the floor elements

- The floor elements are laid with a suction pad of sufficient size, unless otherwise indicated on the product drawings.
- The bearing direction of the elements is indicated on the production drawings as well as the permissible load and the weight of the element.
- Floor elements may not be clamped at the level of the support.

#### Placement of wall elements

- The wall elements are fabricated with lifting devices: hoisting holes, ball-head anchors or other collapsing anchors.
- The weight of the elements is indicated on the production drawings.
- The mould side/pouring side is indicated on the product drawing.

