

**Trafa B.V.**  
Tussendonk 13  
NL 4878 AM Etten-Leur  
Tel. +31 (0)76 501 3451  
Fax +31 (0)76 502 1454  
E-mail info@trafa.nl  
Internet www.trafa.nl



# Request for Quotation transformer

Print current document and fill out the following information as completely as possible and fax it to +31765021454 or e-mail to sales@trafa.nl.

COMPANY NAME : .....

ADDRESS : .....

ZIP CODE : .....

CITY : .....

COUNTRY : .....

TELEPHONE. : .....

FAX : .....

E-MAIL : .....

CONTACT : .....

**OFFER SHEET TRANSFORMER**

Name Project

- 1 – Phase
- 3 – Phase
  
- Separated windings
- Autotransformer

Power  VA or  kVA

Primary Voltage(s)  V

When 3- phase construction, always mention coupled voltages, both primary and secondary, not the voltage between phase and starpoint.

Rated power primary voltage  V

Frequency  Hz

Secondary Voltage(s)  V

Rated power secondary voltage  V

Connection and vectornumber

Standard if sepatated windings: Dyn5, (see NEN 3184). Standard if autotransformer: Yn

Short-circuit voltage %

Maximum ambient temperature > 40 °C  40 °C is standard

- Land construction
- Tropical construction
- Ship construction

- If ship construction choose :
- IEC 92-5
  - ABS
  - BV
  - DNV
  - GLRoS
  - LroS
  - Rina
  - Other,

- Open construction
    - Wallmounting
    - Floormounting
- Protection degree IP00. Terminals IP20. When the terminals do not suffice, a cover will be applied to prefont accidental contact

- Closed construction
  - Wallmounting
  - Floormounting

- Protection degree IP21 (standard)
- Protection degree IP23 (standard)
- Higher protectiondegree on request

**Trafa B.V.**  
Tussendonk 13  
NL 4878 AM Etten-Leur  
Tel. +31 (0)76 501 3451  
Fax +31 (0)76 502 1454  
E-mail info@trafa.nl  
Internet www.trafa.nl



- Color cabinet (standard)
- Other

RAL

Standard = RAL 7035. Other RAL-colors against extra charges

Number of transformers

Piece(s)

**Extra options (more choices possible )**

- Measuring transformer class 1
- Earthscreen
- More primary windings
- More secondary windings
- Primary protection ( preferred melting fuses )
- Secondary protection
- Various temperature protection
- Other wishes

Application area

Remarks