

SUPERWINCH® TALON 9500



9,500lb PREMIUM HIGH SPEED RECOVERY WINCH

PN: 1695200 – wire rope 12v
PN: 1695300 – wire rope 24v

FEATURES

Power in and Power Out
Free Spooling
Heavy duty 2 stage planetary gears
Innovative" Dual Stop" brake
Heavy-Duty Series Wound Motor
Commercial, heavy duty solenoid
Durable handheld remote, 4.5m coil lead
Battery cables with terminals
Roller fairlead

SPECIFICATIONS

Rated Line pull	9,500lb /4,309kg
Motor	5.2 hp
Gearing	Differential Planetary
Gear Ratio	148:1
Free spool clutch	Lift and Turn T Bar
Brake	Automatic, out of the drum
Switch Mechanism	Commercial Contactor
Fairlead	Roller Fairlead
Galv wire rope	9.5mm x 26m
Drum	76mm x 230mm
Weight	41kg wire

PERFORMANCE 12VDC (1st LAYER ON DRUM)

Line Pull		Line Speed		
Lbs	Amps Kgs	FPM	m/m	12v
0		62.1	18.9	73
2000	907	13.8	4.2	165
4000	1814	9.0	2.7	240
6000	2722	6.0	1.8	316
9500	4309	5.0	1.5	430

OPTIONAL ACCESSORIES

Pulley Block
Wireless Remote
Cable Dampener

DIMENSIONS (mm)

Mounting bolt pattern: 254mm x 114.3mm

