

## A700-M Fingerprint Module

- ✓ FBI Certified: PIV Specification, Mobile ID FAP 30
- ✓ Live Finger Detection (LFD)



Artek A700-M is certified by the FBI as FIPS 201/PIV 071006 and Mobile ID FAP 30 compliant fingerprint module. The larger sensing area (20.32 x 25.4 mm) enables it to cover a much bigger surface area and capture more biometric data from fingerprints. A700-M also comes with Live Finger Detection (LFD) technology, making it a perfect solution for applications that require an even higher standard of accuracy and security.

### Features

- **FBI Certified**  
FIPS 201/PIV 071006, FBI Mobile ID FAP 30
- **International Standards**  
ISO19794-2, ISO19794-4, ANSI 378, ANSI 381 and WSQ supported
- **Live Finger Detection (LFD)**  
LFD rejects spoofing attempts by screening the liveness of the finger being captured
- **Advanced Algorithm**  
NIST MINEX III compliance Bione® fingerprint algorithm delivers the highest extracting and matching performance
- **AES-256 Encryption**  
256-bit AES encryption (AES-256) to ensure the security of your fingerprint data in transit
- **Strong Adaption**  
Good adaption for dry, moist and rough fingerprints
- **Correction and Authentication**  
Supports auto correction and 360 degree rotation authentication
- **Cloud Platform**  
Seamlessly join in Artek TrustLink™ biometrics authentication platform
- **Different OS Support**  
Windows2000, XP, Vista, Windows 7 / 8 / 10, Android and other embedded systems
- **Comprehensive SDK**  
Comprehensive software development kit is available for development and integration
- **A Wide Range of Interfaces**  
Supports UART, SPI and USB interfaces for easy integration

### Applications

- PC/Network Security
- Hospitality
- Finance and Banking
- Telecommunication
- Healthcare
- Law Enforcement

# A700-M Fingerprint Module

## Physical Parameter

Dimension	34*57.5*18.0mm (L*W*H)
-----------	------------------------

## Performance Parameter

Capture Mode	Optical Touch
Platen Size	21.0*26.0 mm
Sensing Area	20.32*25.4 mm
Fingerprint Image Size	400*500 pixels
Image Resolution	500 dpi
Gray level	256 level

## Communication Mode

Communication Interface	UART (TTL 115200bps default) USB 1.1 / 2.0 SPI (Slave 3.3V)
-------------------------	---

## Operation Environment

Work Voltage	5.0 V (USB)
Work Current	150 mA
Temperature	-10°C~55°C
Humidity	10~93%R.H
ESD	Contact: ±8KV, Air: ±15KV

## Certification

FBI PIV specification, FBI Mobile ID FAP 30
---

## Supported OS

Windows, Android, Linux, Embedded systems
---



### Aratek Biometrics Co., Ltd.

© 10F, No. 131, Songjiang Road, Zhongshan District, Taipei City 10491, Taiwan

☎ +886 2-2501-0001

✉ sales@aratek.co

🌐 www.aratek.co

©Copyright 2021. Aratek Biometrics Co., Ltd.

Aratek logo is a registered trademark of Aratek or a related company. All other product and company names mentioned are used for identification purposes only and may be the trademark of their respective owners.

All specifications are subject to change without notice. All rights reserved.